

This document was generated on 11/22/2018 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number:	<u>0194270109</u>		
Status:	Active		
Overview:MX150L Industrial SealedDescription:5.84mm Pitch MX150L R		ht-Angle PCB Header, Single Row, without PCB Flange,	
	Gold (Au) Plated, 2 Circuits	3	MK FREEDOW
Documents:			
3D Model		Packaging Specification PK-19427-001 (PDF)	
Drawing (PDF)		RoHS Certificate of Compliance (PDF)	
	tion PS-19427-001-001 (PDF)	Product Literature (PDF)	
			Series image - Reference only
Agency Certificat	tion		
UL		E152602	EU ELV
General			Not Relevant
Product Family		PCB Headers	EU RoHS China RoHS
Series		19427	EU RoHS China RoHS Compliant
Application		Power, Wire-to-Board	REACH SVHC
Comments		IP67 rated; conforms to UL 1977. NOT suitable for	Not Contained Per -
Johimenta		automotive applications with requirements such as	ED/108/2014 (17 Dec
		USCAR-2, USCAR-25, GMW3191, AK Testing, J2030,	2014)
		Volvo Technology Requirements, and Toyota Connector	Halogen-Free
		Spec (TCS)	<u>Status</u>
Overview		MX150L Industrial Sealed Connector System	Low-Halogen
Product Literature Order No		987650-2181	For more information, please visit <u>Contact U</u>
Product Name		MX150L	To more mornation, please visit <u>contact o</u>
UPC		822348736201	China ROHS Not Relevant ELV Not Relevant
Physical			ELV Not Relevant RoHS Phthalates Not Reviewed
Breakaway		No	Rui 13 Filliaiales Not Reviewed
Circuits (Loaded)		2	
Circuits (maximum)		2	
Durability (mating cycles max)		100	Search Parts in this Series
Flammability		94V-0	<u>19427</u> Series
Glow-Wire Capable		No	
Lock to Mating Part		Yes	Mates With
Material - Plating Mating		Gold	19418 Receptacle Assemblies
Material - Plating Termination		Tin	, .
Net Weight		19.632/g	
Number of Rows		1	
Orientation		Right Angle	
PC Tail Length		3.30mm	
PCB Locator		Yes	
PCB Retention		None	
PCB Thickness - Recommended		1.60mm	
Packaging Type		Tray	
Pitch - Mating Inte		5.84mm	
Polarized to Matin	g Part	Yes	
Polarized to PCB		No	
Shrouded		Fully	
Stackable		No	
Surface Mount Compatible (SMC)		No	
Temperature Rang		-40° to +125°C	
Termination Interfa	ace: Style	Through Hole	
Electrical			

Electrical

Current - Maximum per Contact

Material Info

Reference - Drawing Numbers Packaging Specification Product Specification Sales Drawing

PK-19427-001 PS-19427-001-001 SD-19427-018

This document was generated on 11/22/2018 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Automotive Connectors category:

Click to view products by Molex manufacturer:

Other Similar products are found below :

003-018-000 600858 60403001 60993906-B 60993913-B 629515004020001 M902-2131 M902-2161 M902-2344 72.330.1035.1 73.353.4028.0 F118010 F119300-B F132210 F132210-B F166900 F180100 F258300 F258300-B F294300-B F339100 F339700 F358300-B F374110 F407400 F412210 F427600 F444110 F487000 F495100-B F500900-B F509500B-B 770444-1 776880-1 827153-1 881735-1 8N1515-32-24P 9-1326727-8 9-1326729-8 925467-1 925474-1 928905-1 936398-2 964562-1 964562-4 964731-2 965051-1 968782-1 GT17SA-8DS-HU GT17VS-10DP-5.2CF