


Specification Control Drawing

99M0111 Issue 8 18th August 2011

Page 1 of 2 Page 2 is for internal use only

WIRE, MODIFIED POLYESTER INSULATED, 600 VOLT, 120°C, LIGHTWEIGHT The complete requirements for procuring the wire described herein shall consist of this document



Part	CONDUCTOR			FINISHED WIRE				
Description	Stranding	Diameter		Maximum	Minimum	Diameter (mm)		Maximum
	No./ Diam.	(mm)		Resistance	Insulation	Lower	Upper	Weight
	(mm)			@ 20°C	Thickness	Spec	Spec	(kg/ km)
	, ,	Min.	Max.	(ohms/ km)	Total (mm)	Limit	Limit	,
99M0111-28-*	7/0.12	0.33	0.38	259	0.15	0.65	0.80	1.50
99M0111-26-*	19/0.10	0.46	0.53	141.5	0.15	0.85	0.95	2.18
99M0111-24-*	19/0.12	0.55	0.62	95.6	0.15	0.90	1.05	3.45
99M0111-22-*	19/0.15	0.72	0.80	60.0	0.15	1.05	1.20	4.90
99M0111-20-*	19/0.20	0.94	1.04	33.2	0.15	1.30	1.50	7.56
99M0111-18-*	19/0.25	1.18	1.29	21.1	0.15	1.55	1.75	10.4
99M0111-16-*	19/0.30	1.39	1.53	14.5	0.15	1.80	2.00	16.5
99M0111-14-*	37/0.25	1.68	1.82	10.9	0.20	2.15	2.35	20.7
99M0111-12-*	37/0.30	2.02	2.18	7.6	0.20	2.50	2.70	27.1

COLOUR CODE: The '*' in the part number shall be replaced by a standard colour code

designator inaccordance with Mil Std 681.

e.g. 99M0111-20-9, White insulation

PERFORMANCE To be tested to and meet the requirements of Def Stan 61-12(Part 18) Issue 5. **REQUIREMENTS:**

99M0111 is approved to Type 1 of Def Stan 61-12(Part 18) Issue 5.

Certificate No: S&AS/SS/BCC/30/12/002/001A Issue Number: 8

Website: www.te.com

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Multi-Conductor Cables category:

Click to view products by TE Connectivity manufacturer:

Other Similar products are found below:

89182-010-1000 89705-008-500 89842-002-1000 6000FE-877-1000 6120UL-002-1000 CS2885-000 M27500-20SP2S23 6300FE-877-U1000 6309UE-877-1000 M3905-BK005 6502FE 8771000 6541PA-008-U1000 CV6807-000 CW9530-000 CX6543-000 CXA-0066-20-4-9CS2973 CXA-0078-16-1-9CS2405 CXA-0078-22-4-9CS2405 CXA-0078-24-4-9CS2405 CXA-0140-16-6/9-9CS2405 CY0660-000 720451-000 752687-000 768146-000 773159-000 82841-877-5000 83318E-009-500 8348-060-500 83559-002-1000 83653-002-5000 83659-002-1000 83709-002-1000 8404-060-500 8469 060100 858171-000 8628-060-500 868361-001 8730-060-1000 8737-060-U1000 8747-060-100 8747-060-1000 8769-060-1000 8775-060-500 8780-060-1000 8782-001-U1000 88444-002-1000 9159-060-500 9318-060-1000 939870-000 9423 060U500