

## Datasheet for part number KPSE07F20-16SY-F0

Our Catalog Part Number: KPSE07F20-16SY-F0

Brand: Cannon Product Category: Circular Product Line: 26482 - Style Series I & Mil Battery Series: KPT / SE

| Product Datasheet                      |  |
|--|--|
| Shell Style                            | Jam nut receptacle   |
| Endbell Style                          | Grommet seal with strain relief  |
| Gender                                 | Socket   |
| Shell Size                             | 20   |
| Contact Arrangement                    | 20-16  |
| Number of contacts                     | 16 contacts size 16  |
| Contact Type                           | Crimp Contacts   |
| Contact Plating                        | Size 12 & 16: gold plated Size 20: Contact body: tin / Contact area: gold plated                                     |
| Contacts installed                     | no, delivery without contacts  |
| Insulator Rotation                     | 333°   |
| Shell Material                         | Aluminium alloy  |
| Shell Plating                          | Olive drab chromate over cadmium plating   |
| Insulator and Gromet Material          | Polychloroprene  |
| Contact Material                       | Copper alloy   |
| Water Tightness                        | Acc. To VG95319 Part 2, Test No. 5.9.2   |
| Operating Temperature                  | -55°/+125°C<br>(-67/257°F)   |
| Mating Cycles                          | 500 min  |
| Vibration                              | 200 m/s² at 10 to 2000 Hz  |
| Contact Rating AWG16                   | 13,0 A   |
| Insulator Resistance                   | ≈5000 MOhm   |
| Test Voltage                           | 2300 Vrms  |
| Operating Voltage                      | In case of voltages greater than 50V the connector must be used in accordance with DIN VDE part 410, IEC 60364-4-41. |
| Safety Provisions                      | IP67 acc. to DIN 40 050<br>(0,2 bar pressure over 48 hrs)  |
| General Info                           | All tests in accordance with VG95319 and/or if applicable with VG95210   |
| Harnessing Info: Contact Cross-Section | See assembly instruction   |
| Harnessing Info: Insulator Diameter    | See assembly instruction   |
| DISCLAIMER                             | Our facility is not currently certified by the DLA and this product is not covered by the QPL/QML.                   |

## **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

## Click to view similar products for itt manufacturer:

Other Similar products are found below:

BKAF3-68102-25 MDM-37PCBR-F222 CA3108E14S-5PBA176A232 KPSE06F20-41SA206F0 CB2-18-3SCA232 MS3106E22-14P

CT6E18-11SCA206 CA3101E10SL-4SF80DN MS3100F14S-7S CA3101E10SL-4PBA176F42 MS3101E181SW 024251-0016-R 0242530025 024265-0001 024270-0015 024271-0022 024273-0043 024288-0001 M24308/24-21F M24308/24-33Z CT1F22-7SS CT2-20-23SWS

CT2-20-23SXS CT2-36-10PCAU CT6-24-11PSA206 CT6F36-10PCA152 CT6F9767-14-4-14S-5PC CT6T9767-14-4-14SA7SS

D38999/20FG16PA-LC - MD1-21PS MDM-15PH001B-A174 MDM-15PH003B-A174 MDM-21SCBR-A174 MDM-21SCBRP-A174

MDM-21SH003B MDM25PH003BF222 MDM-31SBRP MDM-37PBRT MDM37SH004PA174 MDM-37SH013P MDM-51PSF MDM-51SCBRPL56 MDM96514-336 MDM-9PCBRM7 MDM-9PH006B-A174 MDM9SSM5 MDMV96638-13 MDVB1-21SL1 MEB97318-219

MIKQ67SH019