

RH35 Desktop Radar Hygro-Thermometer Alert



Extech's RH35 monitors Humidity, Temperature, and Dew Point for the previous 24 hours and alerts users to indoor mold hazard conditions starting with a frown icon warning when humidity reaches 60%RH. When the RH exceeds 65%, a loud audible alarm and bright flashing red LED will be triggered. The frown icon will also appear if the environment is too dry (<40%RH) where static electricity becomes a concern.

Applications:

- Commercial, retail and residential sites prone to mold
- Laboratories, R&D, server rooms, clean rooms and bio-pharmaceutical manufacturing
- Museums and storage and document archive facilities



Features

- Innovative graphical display shows the measured humidity values of the last 24 hours like a radar screen
- Large, easy-to-read LCD displays % Relative Humidity, Indoor Temperature and Dew Point
- Measurement ranges:
 - Humidity: 10 to 99%RH
 - Temperature: 14 to 140°F (-10 to 60°C)
- Basic Accuracy of ±4%RH (30% to 80%), ±5%RH (<35% or >75%), ±1.8°F/1°C
- Beeper sounds and bright LED flashes when humidity level exceeds 65%RH
- Facial icons indicate comfort zone (between 40 to 60%RH) and uncomfortable zone (too dry < 40%RH or too humid > 60%RH) - see icon chart on the right

- Stores and recalls Max/Min readings
- Desktop stand can be removed for wall mount use
- Dimensions: 3.9x3.9x0.9" (98x98x23mm); with stand 3.9x4.3x 2" (98x109x55mm); Weight: 3.1oz (87g)
- Complete with stand and 2 AAA batteries

Display Indicators

	too dry < 40%RH or too humid > 60%RH
	comfort zone between 40 to 60%RH

Ordering

RH35..... Desktop Radar Hygro-Thermometer Alert



UPC Code: 793950440353

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Environmental Test Equipment](#) category:

Click to view products by [Extech](#) manufacturer:

Other Similar products are found below :

[CW40](#) [F150C10E3DRT](#) [F150LTC20](#) [F150CD10E2](#) [F150L75](#) [F150LRS](#) [S-11](#) [FLUKE-LDG](#) [382153](#) [FM100](#) [RH210](#) [382253](#) [MO290-P](#)
[GEO-CABLE-REEL-50M](#) [T197914](#) [RD300-L](#) [IR11BD](#) [IR11GM](#) [IR12GM](#) [IR21BD](#) [IR31CE](#) [IR32BC](#) [IR33BC](#) [MP7217TC](#) [NGM-1](#) [SGX-](#)
[7NH3](#) [UT381](#) [F150-SLC50](#) [AW-CO-1000](#) [AW-NmHc-100](#) [3.000.401](#) [AX-7535](#) [CS-9S6SS-A](#) [P 2800 A](#) [P 2801](#) [P 2802](#) [P 5039](#) [P 5130](#) [P](#)
[5055](#) [P 5060](#) [P 5065](#) [P 5086](#) [P 5090](#) [P 5110](#) [P 5115](#) [P 5135](#) [P 5140](#) [P 5145](#) [P 5150](#) [P 5160](#)