

## 45170CM 5-in-1 Environmental Meter with CFM/CMM

Extech's convenient 5-in-1 Environmental Meter measures Air Velocity, Air Flow, Humidity, Temperature, and Light. This multi-functional meter is ideal for professional or home use in testing the environmental quality in a building.





Air Flow

• Ergonomic housing with large dual "smart" LCD where

characters on display reverse direction depending on

· Utilizes precision photo diode and color correction filter

• Thin-film capacitance humidity sensor for fast response

• Low friction vane wheel improves accuracy of Air

Velocity and Air Flow measurements







Air Velocity

the function in use

for light measurements

**Features** 

Light Level Relative Humidity

ourlace remperature

## • Thermistor measures ambient Temperature

- Type K input measures Temperature to 2372°F (1300°C) using optional Type K probe
- Data Hold and Min/Max
- Auto power off with disable feature
- Low battery and overrange indication
- Complete with built-in sensors, wrist strap, and 9V battery; Type K thermocouple probe sold separately

Specifications		Range	Resolution	Basic Accuracy
Air Velocity	ft/min	80 to 5910 ft/min	1ft/min	±3% FS
	m/s	0.4 to 30m/s	0.1m/s	±3% FS
	km/h	1.4 to 108km/h	0.1km/h	±3% FS
	MPH	0.9 to 67MPH	0.1MPH	±3% FS
	knots	0.8 to 58.3 knots	0.1knots	±3% FS
Air Flow	CFM (CMM)	0.01 to 1,908,400CFM (0.001 to 54,000CMM)	0.001CFM (CMM)	
Light Level	Fc (Lux)	0 to 1860Fc (0 to 20,000Lux)	0.1Fc (1Lux)	±(5% rdg + 8 digits)
Relative Humidity		10 to 95%RH	0.1%RH	±4%RH of rdg
Temperature (Thermistor)		32 to 122°F (0 to 50°C)	0.1°	±2.5°F (1.2°C)
Temperature (Type K)		-148°F to 2372°F (-100°C to 1300°C)	0.1°	±(1%+2°F)/ (1%+1°C) of rdg
Dimensions/ Weight		Meter: 6.1 x 2.4 x 1.3" (156 x 60 x 33mm); Vane: 1.2" (31mm)/ 5oz (160g)		

## Ordering

## **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Environmental Test Equipment category:

Click to view products by Extech manufacturer:

Other Similar products are found below :

 CW40
 F150C10E3DRT
 F150LTC20
 F150CD10E2
 F150L75
 F150LRS
 S-11
 FLUKE-LDG
 382153
 FM100
 RH210
 382253
 MO290-P

 GEO-CABLE-REEL-50M
 T197914
 RD300-L
 IR11BD
 IR11GM
 IR21BD
 IR31CE
 IR32BC
 IR33BC
 MP7217TC
 NGM-1
 SGX 

 7NH3
 UT381
 F150-SLC50
 AW-CO-1000
 AW-NmHc-100
 3.000.401
 AX-7535
 CS-9S6SS-A
 P 2800 A
 P 2801
 P 2802
 P 5039
 P 5130
 P

 5055
 P 5060
 P 5065
 P 5086
 P 5090
 P 5115
 P 5135
 P 5140
 P 5145
 P 5150
 P 5160