Manual Switches Electronic Control Pushbutton

INCANDESCENT OR NON-LIGHTED DISPLAY



Buttons ordered separately.



Electrical Data	page 19
Buttons	page 43
Lamps and LEDs	page 58
Accessories	pages 56, 57
Mounting Dimensions	pages 59, 62

FEATURES

- 1, 2, or 4 poles.
- Silver or gold contacts.
- Full guard bezel option.Momentary or 2-level alternate action (push-on, push-off).
- ÜL recognized, CSA certified.
- Lamps can be furnished installed or ordered separately.
- Lamp circuit independent of switch circuit.



*AML21 Series: 1 pole and 2-pole only.

AML21 ORDER GUIDE AML21 B	B	A T	2 T	<u>A</u>	A	
Housing Type	Bezel Color	Incandescent Lamp Type	Terminal Type		Circuitry Codes (Each pole has double-throw)	
Standard Bezel: AML21B Square Non-Lighted AML21C Square 1 Lamp Ckt. AML21E Rect. Non-Lighted	B Black	A No Lamp Installed	2 .110 × .020 (Solder or Quick-Connect)	Silver Contacts	Mom. Action AA 1-Pole AC 2-Pole CC 4-Pole	
AML21F Rect. 1 Lamp Ckt. AML21G Rect. 2 Lamp Ckts. Full Guard Bezel: AML21H Square Non-Lighted		B 6 V Lamp* C 14 V Lamp*	3 .025 × .025 (Printed Ckt. or Push-On)		Alt. Action AB 1-Pole AD 2-Pole CD 4-Pole	
AML21JSquare 1 Lamp Ckt.AML21KRect. Non-LightedAML21LRect. 1 Lamp Ckt.AML21MRect. 2 Lamp Ckts.		E 28 V Lamp*		Gold Contacts	Mom. Action BA 1-Pole BC 2-Pole DC 4-Pole	
					Alt. Action BB 1-Pole BD 2-Pole DD 4-Pole	
				Gold-Plated Silver Contacts	Mom. Action EA 1-Pole EC 2-Pole	
					Alt. Action EB 1-Pole ED 2-Pole	
		* Lamps will be installed	per each lamp circuit specifi	ed in the Housing Type.		

Example: AML21BBA2AA

Square pushbutton switch housing nonlighted; black bezel; .110 × .020 termination; momentary action; 1-pole, doublethrow; silver contacts.

AML21 Series

Manual Switches

Electronic Control Pushbutton


LED DISPLAY



Buttons with LED "window" ordered separately. LEDs are not replaceable.

FEATURES

- Identical to AML21 switches, except furnished with high efficiency LED display.
- Rectangular LED's are flush with button surface, providing wide angle indication.
- Optional diode protection for LED's.
- 5 thru 24 VDC LED devices have an • internal resistor to maintain current at nominal 20 mA.
- UL recognized, CSA certified. •
- LED circuit independent of switch • circuit.



*AML22 Series: 1 pole and 2-pole only.

Manuals


AML22 ORDER GUIDE AML22 C Housing Type	B Bezel Color	B LED Color∕ Voltage	2 T Terminal Type	Circuitry Codes (Each pole has double-throw)	
Standard Bezel: AML22C Square 1 LED AML22H Square 1 High- Profile LED (For use with AML52-A buttons) Full Guard Bezel: AML22J Square 1 LED	B Black	Red B V* C 5V D 10V E 15V F 24V Yellow H J 5V K 10V L 15V M 24V Green R V* S S 5V T 10V W 15V X 24V	$\begin{array}{c} 2 \\ .110 \times .020 \\ (Solder or \\ Quick-Connect) \end{array}$ $\begin{array}{c} 3 \\ .025 \times .025 \\ (Printed Ckt., \\ or Push-On) \end{array}$ $\begin{array}{c} 8 \\ .110 \times .020 \\ With Diode \\ Protection \\ for LED \end{array}$	Silver Contacts Gold Contacts Gold-Plated	Mom. Action AA 1-Pole AC 2-Pole CC 4-Pole Alt. Action AB 1-Pole AD 2-Pole CD 4-Pole Mom. Action BA 1-Pole BC 2-Pole DC 4-Pole Alt. Action BB 1-Pole BD 2-Pole DD 4-Pole Mom. Action
				Silver Contacts	EA 1-Pole EC 2-Pole Alt. Action EB 1-Pole ED 2-Pole

* See LED information for devices without current limiting resistor, page 58.

Example: AML22CBB2AA

Square pushbutton switch housing with one LED, black bezel; red LED (without resistor); .110 × .020 termination; momentary action, 1-pole, double-throw; silver contacts.

CONTACT ARRANGEMENT



AML22 Series





X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Pushbutton Switches category:

Click to view products by Honeywell manufacturer:

Other Similar products are found below :

LW1L-M1C10V-A LW2L-A1C20M-GD LW2L-M1C20M-A 60324L M7E-HRN2 67021K512 67081K512X 701PB580 719-5504-000 MDPSSGLFS 810KSV30B MML23KA3AC05K-001 MML23KW3AA01W 8418K2 8646AB6X718UL 8646ABUL FSDWH 9001KXRK 9001T8BK 9533CD4+U574+U4922 1203MRA A22EM01S A595 1202A6 12037A2ULCSA 1203A2UL ABD122N-B 1211390004 ABN111-Y 1211500044 1211580012 1212MRA 1232A6NF RA3CSH6A 1241.1183.7047 1241.2511 1241.3428 1223A2ULCSA 1223MRA 1232AX2119 1241.1183.8000 1241.1183.8029 1241.2506 1241.2606 12MA6 1301940184 RELBARF6X10(PLASTIC) 13435AG 13440AD2G25X822+U4546 13445A4GX768