

# FLEX STACK

TLW-118-06-T-D

MTLW-130-05-G-S-110

(2.54 mm) .100"


TLW, MTLW SERIES

# LOW-PROFILE .025" SQ POST HEADERS

**Board Mates:**  
BSW, CES, SLW, HLE

## FEATURES

These headers provide the ultimate low-profile (0.64 mm) .025" square post board stacking system. The high quality Phosphor Bronze terminals are available with a standard short post height (TLW Series) for mating with low-profile sockets, or the post height can be Modified (MTLW Series) to accommodate IDC assemblies and other applications.



**TLW** — **1** **NO. PINS PER ROW**

**01 thru 40**  
= Single Row

→ (2.54) .100 x No. of Positions ←

**01 thru 36**  
= Double Row

**LEAD STYLE**

Specify **LEAD STYLE** from chart

LEAD STYLE	A	C
-01	N/A	(5.84) .230
-05	(4.32) .170	(2.67) .105
-06	(3.43) .135	(2.67) .105

**PLATING OPTION**

**-F**  
= Gold flash on post, Matte Tin on tail

**-G**  
= 10 μ" (0.25 μm) Gold on post, Gold flash on tail

**-T**  
= Matte Tin

**ROW OPTION**

**-S**  
= Single Row

**-D**  
= Double Row

**OTHER OPTION**

**-RA**  
= Right-angle  
(-01 Lead Style only)

**-“XX”**  
= Polarized Position  
Specify position for omitted pin.

**ALSO AVAILABLE**  
(MOQ Required)

- Other platings

## SPECIFICATIONS

For complete specifications see [www.samtec.com?TLW](http://www.samtec.com?TLW) or [www.samtec.com?MTLW](http://www.samtec.com?MTLW)

**Insulator Material:** Black Liquid Crystal Polymer  
**Terminal Material:** Phosphor Bronze  
**Plating:** Au or Sn over 50 μ" (1.27 μm) Ni  
**Current Rating (TLW/SLW):** 5.2 A per pin (2 pins powered)  
**Operating Temp Range:** -55 °C to +105 °C with Tin  
-55 °C to +125 °C with Gold  
**RoHS Compliant:** Yes  
**Lead-Free Solderable:** Yes

## RECOGNITIONS

For complete scope of recognitions see [www.samtec.com/quality](http://www.samtec.com/quality)



**Note:** Some lengths, styles and options are non-standard, non-returnable. MTLW Series is non-standard, non-returnable.

**MTLW** — **1** **NO. PINS PER ROW**

**01 thru 40**  
= Single Row

→ (2.54) .100 x No. of Positions ←

**01 thru 36**  
= Double Row

**LEAD STYLE**

Specify **LEAD STYLE** from chart

LEAD STYLE	OAL
-05	(8.51) .335
-06	(7.62) .300
-07	(10.92) .430
-08	(13.46) .530
-09	(18.54) .730
-10	(21.08) .830
-22	(16.00) .630
-23	(11.30) .445
-24	(12.19) .480

**PLATING OPTION**

**-F**  
= Gold flash on post, Matte Tin on tail

**-L**  
= 10 μ" (0.25 μm) Gold on post, Matte Tin on tail

**-G**  
= 10 μ" (0.25 μm) Gold on post, Gold flash on tail

**-T**  
= Matte Tin

**ROW OPTION**

**-S**  
= Single Row

**-D**  
= Double Row

**POST HEIGHT**

**-“XXX”**  
= Post Height Dimension (In inches)

Due to technical progress, all designs, specifications and components are subject to change without notice.

[WWW.SAMTEC.COM](http://WWW.SAMTEC.COM)

All parts within this catalog are built to Samtec's specifications. Customer specific requirements must be approved by Samtec and identified in a Samtec customer-specific drawing to apply.

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Headers & Wire Housings](#) category:*

*Click to view products by [Samtec](#) manufacturer:*

Other Similar products are found below :

[95000-104TRLF](#) [10135584-644402LF](#) [DF62W-EP2022PCA](#) [95000-106TRLF](#) [DF62W-2022SCA](#) [DF62W-EP2022PC](#) [2203348](#) [DF62W-2022SC](#) [1084018](#) [1029039](#) [1084017](#) [802-10-012-10-002000](#) [1112640](#) [1112639](#) [000-34000](#) [0009482033](#) [0009507031](#) [57102-S06-03LF](#) [57202-S52-04LF](#) [PCN6-15S-2.5E](#) [0039019024](#) [58102-G61-06LF](#) [582553-1](#) [0009485154](#) [0009508121](#) [0022285053](#) [0050291907](#) [018731A](#) [LY20-4P-DT1-P1E-BR](#) [02.125.8002.8](#) [60101931](#) [60598-1 \(Cut Strip\)](#) [M1625-3R/100](#) [61062-3](#) [61082-181009](#) [636-1427](#) [638009-1](#) [641938-9](#) [641991-4](#) [644168-1](#) [647662-1](#) [65039-019ELF](#) [65781-047](#) [65817-002LF](#) [65817-015LF](#) [65863-015LF](#) [66207-023LF](#) [67016-026LF](#) [67046-001LF](#) [67095-007LF](#)