

3M™

Acetate Cloth Electrical Tape 11

With Rubber Thermosetting Pressure-Sensitive Adhesive

Data Sheet

September 2015

Description 3M Acetate Cloth Electrical Tape 11 is an aesthetically pleasing tape which offers excellent conformability in coil wrapping applications up to 105°C. Acetate cloth tapes also offer excellent absorption of resins and varnishes.

Agency Approvals & Self Certifications For RoHS information, please visit www.3M.com/ROHS

Applications

- Conformable; for use as coil cover
- Printable
- Easy hand tear, wire harness bundle

Typical Properties

Data is not for specifications. Values are typical and should not be considered minimum or maximum. Properties measured at room temperature 73°F (23°C) unless otherwise stated.

Physical Property (Test Method) (ASTM D1000) unless noted	Typical Value US units (metric)
Color	Black
Adhesive	Thermosetting Rubber
Total Thickness	8 mils (0,203 mm)
Elongation (% at break)	10 %
Breaking Strength	35 lb/in (62 N/10 mm)
Operating Temperature	221°F (105°C)
Adhesion to Steel	40 oz/in (4.4 N/10 mm)

Electrical Property (Test Method) (ASTM D1000) unless noted	Typical Value US units (metric)
Dielectric Breakdown	2000 V
Insulation Resistance	2 x 10 ⁴ megohms
Electrolytic Corrosion Factor (3M ETM 54001)	1.0

3M™ Acetate Cloth Electrical Tape 11

Specifications

3M Acetate Cloth Electrical Tape 11 is an acetate cloth electrical tape with a rubber thermosetting adhesive. The tape shall be black and 8 mils (0,203 mm) thick. This tape shall be coated on one side with pressure-sensitive adhesive, which shall not require heat, moisture or other preparation prior to or subsequent to application. The adhesive coating shall be smooth and uniform and be free of lumps and bare spots. There shall be no separator between adjacent layers of the roll. 3M Electrical Tape 11 shall perform at a temperature of 221°F (105°C) to -40°F (-40°C) without loss of physical or electrical properties.

To achieve maximum solvent resistance and holding performance, we suggest thermosetting the tape at one of the following cycles:

- 1 hour @ 150°C (300°F)
- 2 hours @ 135°C (275°F)
- 3 hours @ 120°C (250°F)

Shelf Life & Storage

This product has a 5-year shelf life from date of manufacture when stored in a humidity controlled storage (10°C/50°F to 27°C/80°F and <75% relative humidity).

Availability

3M electrical tape 11 is available in standard and custom lengths and widths. Standard length is 72 yards.

Please contact your local distributor. Names and addresses are available from 3M.com/electrical [Where to Buy], or call 1.800.676.8381 or 1.800.828.9329.

Important Notice

All statements, technical information, and recommendations related to 3M's products are based on information believed to be reliable, but the accuracy or completeness is not guaranteed. Before using this product, you must evaluate it and determine if it is suitable for your intended application. You assume all risks and liability associated with such use. Any statements related to the product, which are not contained in 3M's current publications, or any contrary statements contained on your purchase order, shall have no force or effect unless expressly agreed upon, in writing, by an authorized officer of 3M.

Warranty; Limited Remedy; Limited Liability

This product will be free from defects in material and manufacture at the time of purchase. **3M MAKES NO OTHER WARRANTIES INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.** If this product is defective within the warranty period stated above, your exclusive remedy shall be, at 3M's option, to replace or repair the 3M product or refund the purchase price of the 3M product. **Except where prohibited by law, 3M will not be liable for any direct, indirect, special, incidental or consequential loss or damage arising from this 3M product, regardless of the legal theory asserted.**

3M is a trademark of 3M Company.



Electrical Markets Division
6801 River Place Blvd.
Austin, TX 78726-9000
800.676.8381
FAX: 800.828.9329
www.3M.com/oem

Please recycle
© 3M 2015 All rights reserved
78-8124-4861-7 B

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Adhesive Tapes](#) category:

Click to view products by [3M](#) manufacturer:

Other Similar products are found below :

[56-YELLOW-34"X72YD](#) [00-021200-13972-7](#) [021200-64630](#) [60 TAPE \(1"\)](#) [62-GRAY-12"X36YD](#) [62-GRAY-1"X36YD](#) [69-1"X36YD](#) [764-1"x36yd-Red](#) [764-1"x36yd-White](#) [9500PC-3/4](#) [967454-1](#) [1181 19MM X 16,5 METERS](#) [130C-1X15FT](#) [E39-RS1-CA](#) [1900-48mm](#) [22-1/2X36YD](#) [88-SUPER-34X44FT](#) [890103N001](#) [2670](#) [96](#) [EVK-TA-TM047NBH01](#) [20-1"X60YDS](#) [2020-18mmx55m](#) [H150](#) [363](#) [3900-Blue](#) [3939-24mmx55m](#) [44-TAN-14"X90YD](#) [4504-34x18](#) [471-Trans-1"x36yd-Bulk](#) [5414 34X36](#) [35-Gray-1/2](#) [4008-12"X36YD](#) [4104-34"x18yd](#) [4116](#) [444-1"x36yd](#) [4466 1"](#) [4466W-1/2"x36yd](#) [4492B-12"x72yd](#) [4492B-1"x72yd](#) [4496W-12"x36yd](#) [4508-1"x36yd](#) [4516-3/8x36](#) [4726](#) [1/2"X36YD](#) [054007-43154](#) [054007-43152](#) [06149](#) [11-32-2857](#) [5419 1/2"](#) [56 TAPE \(1/2"\)](#)