3M

Shielding Tape 1115

Aluminum Foil with Conductive Acrylic Adhesive

Data Sheet

Product Description

3MTM Shielding Tape 1115 consists of a 5mil aluminum foil backing and a unique electrically conductive pressure-sensitive acrylic adhesive.

- 5mil aluminum foil backing
- Conductive acrylic adhesive
- Supplied on a removable liner for easy handling and die cutting.

Like all 3M shielding tapes, 3M 1115 is available in standard and custom widths and lengths

 Longer lengths up to several times normal length, dependent upon width. Check with customer service.

Applications

3M Shielding Tape 1115 is typically used for applications requiring excellent electrical conductivity from the application substrate through the adhesive to the foil backing. Common uses include grounding and EMI shielding in equipment.

Shielding Effectiveness

Many factors determine the true shielding effectiveness of a shielding tape, including type and thickness of foil, adhesive type, intimacy of contact, smoothness of application surface, strength and frequency of the EMI signal, etc. Before using this product, the user must evaluate it and determine if it is suitable for the intended application.

Properties	Typical Value
Backing thickness	5.0 mil (0,125mm)
Total thickness (backing plus adhesive)	7.0 mil (0,177mm)
Breaking strength ¹	55 lb/in (96 N/10mm)
Adhesion to steel ¹	52 oz/in (5,6 N/10mm)
Electrical resistance through adhesive ²	0.005 ohm

^{*} Foot notes: 1. ASTM-D-1000 Test method

^{2.} MIL-STD-202 Method 307 maintained at 5 psi (3,4 N/cm²) measured over 1 in² surface area. Conductive particles in the adhesive provide the electrical path between the application substrate and the foil backing.

3M is a trademark of 3M Company.

Important Notice

All statements, technical information, and recommendations related to 3M's products are based on information believed to be reliable, but the accuracy or completeness is not guaranteed. Before using this product, you must evaluate it and determine if it is suitable for your intended application. You assume all risks and liability associated with such use. Any statements related to the product which are not contained in 3M's current publications, or any contrary statements contained on your purchase order shall have no force or effect unless expressly agreed upon, in writing, by an authorized officer of 3M.

Warranty; Limited Remedy; Limited Liability. This product will be free from defects in material and manufacture as of the date of purchase. 3M MAKES NO OTHER WARRANTIES INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. If this product is defective within the warranty period stated above, your exclusive remedy shall be, at 3M's option, to replace or repair the 3M product or refund the purchase price of the 3M product. Except where prohibited by law, 3M will not be liable for any loss or damage arising from this 3M product, whether direct, Indirect, special, Incidental or consequential regardless of the legal theory asserted.

3M

Electrical Markets Division 6801 River Place Blvd. Austin, TX 78726-9000 www.3M.com/electrical

Litho in USA © 3M 2003 78-8126-6190-4-A

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for EMI Gaskets, Sheets, Absorbers & Shielding category:

Click to view products by 3M manufacturer:

Other Similar products are found below:

8101010140 8563-0090-89 1194-7.7X10 1245-34"X18YD 1267 1345-3/8x18yrd 1380-2"X8" 1554907-1 2320002000 2320014700

SG293037DS ST005PCN50 3070-500-STD 55005107 38M4040AA0606 46J5N02020.NN00 1125-8X10 1126X1" 1170-3/4X18YDS 1170
7.7x10 1183-12"X18YD 6-34T-BD-0.315 SG125187D-24 SG125250R-24 SG187375R-24 SG284050DS 8402010540 KIT TECH CLIP

1194 10-40450-28S 3013350A 1267-1/2"x18yd 46J8501020.NN00 1170-1/4"x18yd 3013310A 1194X1" 3013325A 3020604 3021302

3031313 3021310 6-34UT-070-BD-16 303076048 46J5N03020.NN00 30395641 3030403 3690103020 46X7501020.NN00 302095032

46J5N02520.NN00