3M[™] Lapping Film Aluminum Oxide 254X, 261X, 262X, 263X, 265X, 266X, 268X, 264M

Product Description

Tightly graded aluminum oxide minerals slurry coated onto a polyester film backing. Available with or without PSA (Pressure Sensitive Adhesive).

Applications

Fiber optic connector polishing, flat lapping, superfinishing, media head finishing, hard disk drive lube buff.

Key Features

- Produces excellent surface finish
- Reduces overall process time
- Produces high yields
- Non-slurry processing

Product I.D.

Product ID (plain back)	Product ID (with PSA backing)	Backing	Resin Type
254X	N/A	2 mil	standard
261X	268X	3 mil	stanard
262X	265X	3 mil	stanard
263X	266X	3 mil	hard (Type P)
264M	N/A	3 mil	standard

^{*}not all products are available in all grades.

Converted Forms

Sheets, Discs and Rolls. Maximum width 26".

Backing

Polyester Film

Nominal thickness: 2 and 3 mil.

Mineral Size Grading Chart

Micron Grade (nominal)	Color	
0.05	White	
0.3	White	
0.5	White	
1	Green	
2	Teal	
3	Pink	
5	Brown	
9	Blue	
12	Yellow	
30	Green	
40	Blue	
60	White	

Storage and Shelf Life

Recommended Storage Conditions:

Temperature: 50-90°F Relative humidity: 30-70%

(There is no degradation with time. It is recommended that

product be used within 24 months of purchase.)



3M[™] Lapping Film Aluminum Oxide 254X, 261X, 262X, 263X, 265X, 266X, 268X, 264M

Precautionary Information

Refer to Product Label and Material Safety Data Sheet for Health and Safety Information before using this product. For additional health and safety information, call 1-800-364-3577 or (651) 737-6501.

For Additional Information

To request additional product information or to arrange for sales assistance, call toll free 1-800-251-8634. Address correspondence to: 3M Electronics Markets Materials Division, Building 21-1W-10, 900 Bush Avenue, St. Paul, MN 55144-1000. Our fax number is 651-778-4244 or 1-877-369-2923.

In Canada, phone: 1-800-364-3577. In Puerto Rico, phone: 1-787-750-3000.

In Mexico, phone: 52-70-04-00.

Important Notice

Before using this product, you must evaluate it and determine if it is suitable for your intended application.

You assume all risks and liability associated with such use.

Warranty; Limited Remedy; Limited Liability.

This product will be free from defects in material and manufacture at the time of purchase. 3M MAKES NO OTHER WARRANTIES INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. If this product is defective within the warranty period stated above, your exclusive remedy shall be, at 3M's option, to replace or repair the 3M product or refund the purchase price of the 3M product. Except where prohibited by law, 3M will not be liable for any indirect, special, incidental or consequential loss or damage arising from this 3M product, regardless of the legal theory asserted.





X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Fibre Optic Connectors category:

Click to view products by 3M manufacturer:

Other Similar products are found below:

0004700001 6100-R 6313 F709722200 F709730000 F718183204 F727403500 F727752800 8119 9440F20-27S-190 944-120-6001 9441F10SL-3S 9444W28-21S 9444W36-10S 9446W20-16S 953-101-5310-P 954-101-57202B A0270169 12-9122 12-5702 AX101713 AX102420 AX103923 AX104024 AX104193 AX104230 AX104562 AX105203-B25 AX105205-S1 EHSC2M 17-300800 181-011-126 181-011-S 181-057-126 NKSOPBUY 20500002116 2064996-1 20800001065 2170 9132 2612 2620 9291 9440F16-10S 9440F20-18S 9444W32-73S 9446F16-10S-190 953-106-50231 953-120-5003 955-120-5110