



Polyester Protective Tape

335 • 336

Technical Data

February 2017

Product Description 3M™ Polyester Protective Tape 335 and 336 are thin polyester tapes with a low tack adhesive. Designed to protect finished surfaces from light abrasion, nicks and scratches during production, packing, shipping and installation.

Product Construction

Backing	Adhesive	Color	Standard Roll Length
Polyester	Rubber	Pink (3M tape 335)	144 yds.
		Transparent (3M tape 336)	(131.6 m)

Typical Physical Properties

Note: The following technical information and data should be considered representative or typical only and should not be used for specification purposes.

		ASTM Test Method
Adhesion to Steel:	61 gm/in. width (0.93 N/100 mm)	D-3330
Tensile Strength at Break:	25 lbs./in. width (438 N/100 mm)	D-3759
Elongation at Break:	115%	D-3759
Backing Thickness:	0.94 mils (37 mm)	D-3652
Total Tape Thickness:	1.5 mils (59 mm)	D-3652
Temperature Use Range:	Extended periods: Up to 150°F (66°C) Up to 30 min.: Up to 250°F (121°C)	

Features

- Low tack rubber adhesive adheres to a wide variety of surfaces with minimal adhesion build-up and clean removal when finished.
- Provides excellent abrasion, tear, scratch, puncture and moisture resistance to help protect surfaces.
- Extensible, abrasion resistant backing is ideal for forming operations.
- Pink color of the 3M tape 335 provides easy visibility for either application or removal, providing quick identification of protected versus unprotected areas.
- The transparent backing of the 3M tape 336 allows visual inspection without tape removal.
- These tapes can be used for extended periods of time up to 150°F (66°C) and for 30 minutes or less at 250°F (121°C).

Application Ideas

- Protection from fumes and splash during plating processes on the upper portion of printed wiring boards.
- Protection of polished stainless steel and aluminum in fabrication, shipping, and storage.
- Protection of nameplates and instrument panels during shipping and installation.
- Protection of finished non-metallic surfaces.
- Protection of non-image side of inner layers of multilayer printed wiring boards.

3M™ Protective Polyester Tape

335 • 336

Application Techniques

- Adhesion levels can increase from any of the following conditions:
 - Extended exposure to direct sunlight
 - High stacking pressures
 - Extended application to copper bearing surfaces
- Sharp dies must be used when stamping parts protected with 3M tape 336 since dull dies result in nicked edges which cause tape slivering upon removal.

Storage Store under normal conditions of 60° to 80°F (16° to 27°C) and 40 to 60% R.H. in the original packaging.

Shelf Life To obtain best performance, use this product within 12 months from date of manufacture.

Technical Information The technical information, guidance, and other statements contained in this document or otherwise provided by 3M are based upon records, tests, or experience that 3M believes to be reliable, but the accuracy, completeness, and representative nature of such information is not guaranteed. Such information is intended for people with knowledge and technical skills sufficient to assess and apply their own informed judgment to the information. No license under any 3M or third party intellectual property rights is granted or implied with this information.

Product Selection and Use Many factors beyond 3M's control and uniquely within user's knowledge and control can affect the use and performance of a 3M product in a particular application. As a result, customer is solely responsible for evaluating the product and determining whether it is appropriate and suitable for customer's application, including conducting a workplace hazard assessment and reviewing all applicable regulations and standards (e.g., OSHA, ANSI, etc.). Failure to properly evaluate, select, and use a 3M product and appropriate safety products, or to meet all applicable safety regulations, may result in injury, sickness, death, and/or harm to property.

Warranty, Limited Remedy, and Disclaimer Unless a different warranty is specifically stated on the applicable 3M product packaging or product literature (in which case such warranty governs), 3M warrants that each 3M product meets the applicable 3M product specification at the time 3M ships the product. 3M MAKES NO OTHER WARRANTIES OR CONDITIONS, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR ARISING OUT OF A COURSE OF DEALING, CUSTOM, OR USAGE OF TRADE. If a 3M product does not conform to this warranty, then the sole and exclusive remedy is, at 3M's option, replacement of the 3M product or refund of the purchase price.

Limitation of Liability Except for the limited remedy stated above, and except to the extent prohibited by law, 3M will not be liable for any loss or damage arising from or related to the 3M product, whether direct, indirect, special, incidental, or consequential (including, but not limited to, lost profits or business opportunity), regardless of the legal or equitable theory asserted, including, but not limited to, warranty, contract, negligence, or strict liability.

ISO 9001

This Industrial Adhesives and Tapes Division product was manufactured under a 3M quality system registered to ISO 9001 standards.



Industrial Adhesives and Tapes Division
3M Center, Building 225-3S-06
St. Paul, MN 55144-1000
800-362-3550 • 877-369-2923 (fax)
www.3M.com/industrial

3M is a trademark of 3M company.
Printed in U.S.A.
©3M 2017 (E)70070909091 (2/17)

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Adhesive Tapes](#) category:

Click to view products by [3M](#) manufacturer:

Other Similar products are found below :

[56-YELLOW-34"X72YD](#) [00-021200-13972-7](#) [021200-64630](#) [60 TAPE \(1"\)](#) [62-GRAY-12"X36YD](#) [62-GRAY-1"X36YD](#) [69-1"X36YD](#) [764-1"x36yd-Red](#) [764-1"x36yd-White](#) [9500PC-3/4](#) [967454-1](#) [1181 19MM X 16,5 METERS](#) [130C-1X15FT](#) [E39-RS1-CA](#) [1900-48mm](#) [22-1/2X36YD](#) [88-SUPER-34X44FT](#) [890103N001](#) [2670](#) [96](#) [EVK-TA-TM047NBH01](#) [20-1"X60YDS](#) [2020-18mmx55m](#) [H150](#) [363](#) [3900-Blue](#) [3939-24mmx55m](#) [44-TAN-14"X90YD](#) [4504-34x18](#) [471-Trans-1"x36yd-Bulk](#) [5414 34X36](#) [35-Gray-1/2](#) [4008-12"X36YD](#) [4104-34"x18yd](#) [4116](#) [444-1"x36yd](#) [4466 1"](#) [4466W-1/2"x36yd](#) [4492B-12"x72yd](#) [4492B-1"x72yd](#) [4496W-12"x36yd](#) [4508-1"x36yd](#) [4516-3/8x36](#) [4726](#) [1/2"X36YD](#) [054007-43154](#) [054007-43152](#) [06149](#) [11-32-2857](#) [5419 1/2"](#) [56 TAPE \(1/2"\)](#)