## 3M<sup>TM</sup> Round Conductor Flat Cable .025" 30 AWG Stranded, PVC

#### 3754 Series



- Close spacing permits higher signal density
- PVC insulation provides excellent flexibility
- 30 AWG stranded on .025 inch spacing allows for mass termination as well as increased flexibility
- Recommended for use with the 82XXX-600X Series .050" x.100" Tripolarized Wiremount Mini Socket (82XXX-600X) and Pak 25 (P25E-XXX-STGF)
- See Regulatory Information Appendix (RIA for chemical compliance information (RIA E1 & C1 apply)

Hun	Date Modified: May 14, 2009	TS-0875-C Sheet 1 of 2

#### **Physical**

Insulation:	
Material:	Polyvinyl Chloride (PVC)
Color:	Gray
Marking:	
Standard:	None
Conductors:	30 AWG 7 X 38 [ 7 X 0.102 ] Tinned Stranded Copper

### **Electrical**

Voltage Rating:	USA: 30V	EU: <50V
<b>Insulation Resistance:</b>	$>1 \ge 10^{10} \Omega / 10 \text{ ft} [3 \text{ m}]$	
Characteristic Impedance:	Unbalanced 73 Ω	Balanced 122 Ω
Capacitance:	20.8 pF/ft (68.2 pF/m)	12.0 pF/ft (39.4 pF/m)
Inductance:	.11 μH/ft (0.36 μH/m)	.18 μH/ft (0.59 μH/m)
<b>Propagation Delay:</b>	1.51 ns/ft (4.95 ns/m)	1.45 ns/ft (4.76 ns/m)
Velocity of Propagation:	67%	70%

Note: Unbalanced is measured between ground-signal-ground conductors. Balanced is measured between signal conductors within a pair.

#### **Environmental**

**Temperature Rating:** -20°C to +105°C **Flammability Rating:** USA:VW-1

UL File No.: E42769, Style No.: 20596

# $3M^{\text{TM}}$ Round Conductor Flat Cable

### .025" 30 AWG Stranded, PVC

3754 Series

	Number of Conductors	3M Part Number	Dimension A	Dimension B					
	20	3754/20	0.500 ± .006 [ 12.70 ]	0.475 ± .004 [ 12.07 ]					
	26	3754/26	0.650 ± .006 [ 16.51 ]	0.625 ± .004 [ 15.88 ]					
<b>7</b>	30	3754/30	0.750 ± .006 [ 19.05 ]	0.725 ± .006 [ 18.42 ]					
	32	3754/32	0.800 ± .008 [ 20.32 ]	0.775 ± .006 [ 19.69 ]					
	34	3754/34	0.850 ± .009 [ 21.59 ]	0.825 ± .006 [ 20.96 ]					
	3754/36	0.900 ± .009 [ 22.86 ]	0.875 ± .006[ 22.23 ]						
	3754/40	1.000 ± .009[ 25.40 ]	0.975 ± .006 [ 24.77 ]						
	50	3754/50	1.250 ± .009 [ 31.75 ]	1.225 ± .006 [ 31.12 ]					
	52	3754/52	1.300 ± .009 [ 33.02 ]	1.275 ± .006 [ 32.39 ]					
	60	3754/60	1.500 ± .012 [ 38.10 ]	1.475 ± .009 [ 37.47 ]					
	68	3754/68	1.700 ± .012 [ 43.18 ]	1.675 ± .009 [ 42.55 ]					
	80	3754/80	2.000 ± .015 [ 50.80 ]	1.975 ± .011 [ 50.17 ]					
	100	3754/100	2.500 ± .015 [ 63.50 ]	2.475 ± .012 [ 62.87 ]					
			— A ———	P					
			— В ———						
			1 1 .						
013 ± . [0.33]				25 ± .002 Typ ).64 ]					
[0.00]									
$1 \\ 025 \pm 003$			44	$\frown$					
$\begin{bmatrix} .025 \pm .003 \\ [0.64] \end{bmatrix} \qquad \left\{ \begin{array}{c} \begin{array}{c} \begin{array}{c} \\ \\ \end{array} \right\} \\ \begin{array}{c} \end{array} \\ \end{array} \\ \begin{array}{c} \end{array} \\ \begin{array}{c} \end{array} \\ \begin{array}{c} \end{array} \\ \begin{array}{c} \end{array} \\ \end{array} \\ \begin{array}{c} \end{array} \\ \begin{array}{c} \end{array} \\ \end{array} \\ \end{array} \\ \begin{array}{c} \end{array} \\ \end{array} \\ \end{array} \\ \end{array} \\ \end{array} \\ \begin{array}{c} \end{array} \\ \end{array} $									
			$\gamma / \sim \sim$	$\bigcirc \bigcirc \bigcirc \bigcirc$					
30 AWG 7 X 38 ( 7 X 0.102 ) Tinned Stranded Copper Conductors PVC Insulation									
· · · · · · · · · · · · · · · · · · ·		onductors							
				lash					
				Inch [mm]					
				Tolerance Unless Noted					
				.0 .00 .000					
			Ir	nch ±.1 ±.01 ±.005					
Note: Red marking on one edge of cable designates wire #1.			[]	Dimensions for Reference Only					
Ordening Information									
Ordering Information									
	3754								
Number of Conductors									
Number of Conductors (See Table)									
Note: Available in standard 100 ft or 300 ft rolls, please specify									
when ordering. Contact 3M for availability of additional conductor counts and/or custom roll lengths.				TS-0875- Sheet 2 of					
				Sheel 2 01					

#### ЗМ

Electronic Solutions Division Interconnect Solutions http://www.3M.com/interconnects/

# **Regulatory Information Appendix**

### **3M Electronic Solutions Division/Interconnect**

### **EUROPE**

### Appendix E1: European Union RoHS

Directive 2002/95/EC, Restriction of the Use of Certain Hazardous Substances in Electrical & Electronic Equipment, as amended by EU Commission Decision 2005/618/EC.

#### This product is RoHS Compliant 2005/95/EC.

"RoHS Compliant 2005/95/EC" means that the product or part ("Product") does not contain any of the substances in excess of the maximum concentration values in EU Directive 2002/95/EC, as amended by Commission Decision 2005/618/EC, unless the substance is in an application that is exempt under EU RoHS. Unless otherwise stated by 3M in writing, this information represents 3M's best knowledge and belief based upon information provided by third party suppliers to 3M.

In the event any product is proven not to conform with 3M's Regulatory Information Appendix, then 3M's entire liability and Buyer's exclusive remedy will be in accordance with the Warranty stated below.

### Appendix E2: European Union RoHS

Directive 2002/95/EC, Restriction of the Use of Certain Hazardous Substances in Electrical & Electronic Equipment, as amended by EU Commission Decision 2005/618/EC.

# This product contains lead in the compliant pin area in excess of the maximum concentration value allowed but is compliant by exemption under EU Commission Decision 2005/747/EC.

"RoHS Compliant 2005/95/EC" means that the product or part ("Product") does not contain any of the substances in excess of the maximum concentration values in EU Directive 2002/95/EC, as amended by Commission Decision 2005/618/EC, unless the substance is in an application that is exempt under EU RoHS. Unless otherwise stated by 3M in writing, this information represents 3M's best knowledge and belief based upon information provided by third party suppliers to 3M.

In the event any product is proven not to conform with 3M's Regulatory Information Appendix, then 3M's entire liability and Buyer's exclusive remedy will be in accordance with the Warranty stated below.

## Appendix E3: European Union RoHS

Directive 2002/95/EC, Restriction of the Use of Certain Hazardous Substances in Electrical & Electronic Equipment as amended by Commission Decision 2005/618/EC.

#### This product contains lead in the solder tail area in excess of the maximum concentration value allowed.

Unless otherwise stated by 3M in writing, this information represents 3M's best knowledge and belief based upon information provided by third party suppliers to 3M.

In the event any product is proven not to conform with 3M's Regulatory Information Appendix, then 3M's entire liability and Buyer's exclusive remedy will be in accordance with the Warranty stated below.

## Appendix E4: European Union RoHS

Directive 2002/95/EC, Restriction of the Use of Certain Hazardous Substances in Electrical & Electronic Equipment, as amended by EU Commission Decision 2005/618/EC, as amended by EU Commission Decision 2005/717/EC, as amended by EU Court of Justice Decision 2008/C 116/04

# This product contains decaBDE in the insulating material in excess of the maximum concentration allowed for finished products subject to EU RoHS that are placed on the EU market after June 30, 2008.

Unless otherwise stated by 3M in writing, this information represents 3M's best knowledge and belief based upon information provided by third party suppliers to 3M.

In the event any product is proven not to conform with 3M's Regulatory Information Appendix, then 3M's entire liability and Buyer's exclusive remedy will be in accordance with the Warranty stated below.

### Appendix E5: European Union RoHS

Directive 2002/95/EC, Restriction of the Use of Certain Hazardous Substances in Electrical and Electronic Equipment, as amended by EU Commission Decision 2005/618/EC.

#### This product contains lead in excess of the maximum concentration value allowed but is compliant by exemption under Item 6 of the Annex to the Directive.

"RoHS Compliant 2005/95/EC" means that the product or part ("Product") does not contain any of the substances in excess of the maximum concentration values in EU Directive 2002/95/EC, as amended by Commission Decision 2005/618/EC, unless the substance is in an application that is exempt under EU RoHS. Unless otherwise stated by 3M in writing, this information represents 3M's best knowledge and belief based upon information provided by third party suppliers to 3M.

In the event any product is proven not to conform with 3M's Regulatory Information Appendix, then 3M's entire liability and Buyer's exclusive remedy will be in accordance with the Warranty stated below.

### CHINA Appendix C1: China RoHS

Electronic Industry Standard of the People's Republic of China, SJ/T11363-2006, Requirements for Concentration Limits for Certain Hazardous Substances in Electronic Information Products.

This symbol, per Marking for the Control of Pollution Caused by Electronic Information Products, SJ/T11364-2006, means that the product or part does not contain any of the following substances in excess of the following maximum concentration values in any homogeneous material: (a) 0.1% (by weight) for lead, mercury, hexavalent chromium, polybrominated biphenyls or polybrominated diphenyl ethers (excluding decaBDE); or (b) 0.01% (by weight) for cadmium. Unless otherwise stated by 3M in writing, this information represents 3M's best knowledge and belief based upon information provided by third party suppliers to 3M.

In the event any product is proven not to conform with 3M's Regulatory Information Appendix, then 3M's entire liability and Buyer's exclusive remedy will be in accordance with the Warranty stated below.

# Appendix C2: China RoHS



Electronic Industry Standard of the People's Republic of China, SJ/T11363-2006, Requirements for Concentration Limits for Certain Hazardous Substances in Electronic Information Products.

This symbol, per Marking for the Control of Pollution Caused by Electronic Information Products, SJ/T11364-2006, means that the product or part does contain a substance, as detailed in the chart below, in excess of the following maximum concentration values in any homogeneous material: (a) 0.1% (by weight) for lead, mercury, hexavalent chromium, polybrominated biphenyls or polybrominated diphenyl ethers (excluding decaBDE); or (b) 0.01% (by weight) for cadmium. Unless otherwise stated by 3M in writing, this information represents 3M's best knowledge and belief based upon information provided by third party suppliers to 3M.

The numerical reference in the symbol above should not be construed as a representation regarding the product's life or an extension of a product warranty. The product warranty is stated below. In the event any product is proven not to conform with 3M's Regulatory Information Appendix, then 3M's entire liability and Buyer's exclusive remedy will be in accordance with the product Warranty stated below.

#### 产品中有毒有害物质或元素的名称及含量 Name and Content of Hazardous Substances or Elements

<u>」而于日本日古物质或九家的石标及日里</u> 一代une und Content of Huzurdous Substances of Elements								
部件名称	有毒有害物质或元素(Hazardous Substances or Elements)							
(Part or Component Name)	铅(Pb)	汞 (Hg)	镉 (Cd)	六价铬(Cr(VI))	多溴联苯 (PBB)	多溴二苯醚 (PBDE)		
端子镀层(contact plating)	×	0	0	0	0	0		
O: 表示该有毒有害物质在该部件所有均质材料中的含量均在SJ/T11363-2006 标准规定的限量要求以下。(Indicates that this hazardous substance contained in all of the homogeneous materials for this part is below the limit requirement in SJ/T11363-2006.) ×: 表示该有毒有害物质至少在该部件的某一均质材料中的含量超出SJ/T11363-2006 标准规定的限量要求。(Indicates that this hazardous substance contained in at least one of the homogeneous materials used for this part is above the limit requirement in SJ/T11363-2006.)								

## Appendix C3: China RoHS



Electronic Industry Standard of the People's Republic of China, SJ/T11363-2006, Requirements for Concentration Limits for Certain Hazardous Substances in Electronic Information Products.

This symbol, per Marking for the Control of Pollution Caused by Electronic Information Products, SJ/T11364-2006, means that the product or part **does** contain a substance, as detailed in the chart below, in excess of the following maximum concentration values in any homogeneous material: (a) 0.1% (by weight) for lead, mercury, hexavalent chromium, polybrominated biphenyls or polybrominated diphenyl ethers (excluding decaBDE); or (b) 0.01% (by weight) for cadmium. Unless otherwise stated by 3M in writing, this information represents 3M's best knowledge and belief based upon information provided by third party suppliers to 3M.

The numerical reference in the symbol above should not be construed as a representation regarding the product's life or an extension of a product warranty. The product warranty is stated below. In the event any product is proven not to conform with 3M's Regulatory Information Appendix, then 3M's entire liability and Buyer's exclusive remedy will be in accordance with the product Warranty stated below.

#### 产品中有毒有害物质或元素的名称及含量 Name and Content of Hazardous Substances or Elements

部件名称	有毒有害物质或元素 (Hazardous Substances or Elements)					ents)
(Part or Component Name)	铅(Pb)	汞 (Hg)	镉 (Cd)	六价铬(Cr(VI))	多溴联苯 (PBB)	多溴二苯醚 (PBDE)
合金(Metal alloy)	×	0	0	0	0	0

○:表示该有毒有害物质在该部件所有均质材料中的含量均在SJ/T11363-2006 标准规定的限量要求以下。(Indicates that this hazardous substance contained in all of the homogeneous materials for this part is below the limit requirement in SJ/T11363-2006.) ×:表示该有毒有害物质至少在该部件的某一均质材料中的含量超出SJ/T11363-2006 标准规定的限量要求。(Indicates that this hazardous substance

×:表示该有毒有害物质至少在该部件的某一均质材料中的含量超出SJ/T11363-2006 标准规定的限量要求。(Indicates that this hazardous substance contained in at least one of the homogeneous materials used for this part is above the limit requirement in SJ/T11363-2006.)

#### **Important Notice**

All statements, technical information, and recommendations related to 3M's products are based on information believed to be reliable, but the accuracy or completeness is not guaranteed. Before using this product, you must evaluate it and determine if it is suitable for your intended application. You assume all risks and liability associated with such use. Any statements related to the product which are not contained in 3M's current publications, or any contrary statements contained on your purchase order shall have no force or effect unless expressly agreed upon, in writing, by an authorized officer of 3M.

#### Warranty; Limited Remedy; Limited Liability.

This product will be free from defects in material and manufacture for a period of one (1) year from the time of purchase. **3M MAKES NO OTHER WARRANTIES INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.** If this product is defective within the warranty period stated above, your exclusive remedy shall be, at 3M's option, to replace or repair the 3M product or refund the purchase price of the 3M product. **Except where prohibited by law, 3M will not be liable for any indirect, special, incidental or consequential loss or damage arising from this 3M product, regardless of the legal theory asserted.** 



**3M Electronics Solutions Division** 6801 River Place Blvd. Austin, TX 78726-9000 U.S.A. 1-800-225-5373 www.3m.com/interconnects

Please recycle. Printed in USA. © 3M 2008. All rights reserved. RIA-2217B-E

## **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Flat Cables category:

Click to view products by 3M manufacturer:

Other Similar products are found below :

 F28-A25G
 F28-A34G
 FST-23A-15
 AYT1510-US
 171-37G
 902220736002000
 902220736006000
 9L28010-008-H300
 9L28014-008-H300

 F28-A60G
 28100-0571
 28100-0664
 336506-100SF
 336512-300
 336518
 336537-CUT-LENGTH
 3447/10-100
 362514100MSF

 40WDY00005
 AYT51163
 336506-300
 336508-300
 C374910
 3625/24100M
 3749/10-100
 375630
 3-971111-6
 1-1437356-3
 812504
 5 

 1437214-8
 40WBY00007
 3609/12
 3539/26-100
 5111196336
 0281000624
 3801/04
 C3365/10-500
 3754/12
 902220736003000

 3625/22100MSF
 902220736005000
 902220736004000
 2L28026
 008H100
 C3811/10-100
 65-TF268M
 C3365/18-100
 28100-0597

 C3365/14SF-300
 3365/14-500
 050F28V10CR
 C3365/14-500
 050F28V10CR
 C3365/14-500
 C3365/14-500
 C3365/14-500