3M 1194 Tape Copper Foil with Nonconductive Adhesive Data Sheet

Product Description

3M[™] 1194 Tape consists of a 1-ounce deadsoft copper foil backing and an aggressive nonconductive pressure-sensitive acrylic adhesive.

- Deadsoft 1-ounce copper foil backing
- Nonconductive acrylic adhesive
- Supplied on a removable liner for easy handling and diecutting

Like all 3M shielding tapes, 3M 1194 is available in standard and custom widths and lengths. Standard length for 3M 1194 is 36 yards.

- Widths from 1/4" to 23"
- Longer lengths up to several times normal length, dependent upon width. Check with Customer Service.

Applications

3M 1194 Tape is typically used for applications requiring economical electrical bonding, grounding, and EMI shielding. The copper foil backing is solderable and resists oxidation and discoloration.

Shielding Effectiveness

Many factors determine the true shielding effectiveness of a shielding tape, including type and thickness of foil, adhesive type, intimacy of contact, smoothness of application surface, strength and frequency of the EMI signal, etc. However, using standard tests and fixtures, it is possible to determine a value for the attenuation.

For 3M 1194 Tape, typical shielding effectiveness (far field) is in the range of 50dB to 60dB (30 MHz to 1 GHz).

Properties	Typical Values	
Backing thickness ¹	1.4 mil (0,04mm)	
Total thickness (backing plus adhesive)	2.6 mil (0.066mm)	
Breaking strength ¹	25 lb./in (44 N/10mm)	
Adhesion to steel ¹	40 oz/in (4,4 N/10mm)	
Flame retardancy ²	Pass	

* Footnote: 1. Test method ASTM D 1000

2. UL-recognized for flame retardancy per UL 510, Product Category 0ANZ2, File E17385.

3M is a trademark of 3M.

Important Notice

All statements, technical information and recommendations related to the Seller's products are based on information believed to be reliable, but the accuracy or completeness thereof is not guaranteed. Before utilizing the product, the user should determine the suitability of the product for its intended use. The user assumes all risks and liability whatsoever in connection with such use.

Any statements or recommendations of the Seller which are not contained in the Seller's current publications shall have no force or effect unless contained in an agreement signed by an authorized officer of the Seller. The statements



Electrical Products Division

6801 River Place Blvd. Austin, TX 78726-9000 800-676-8381 http://www.3m.com/elpd contained herein are made in lieu of all warranties, expressed or implied, including but not limited to the implied warranties of merchantability and fitness for a particular purpose which warranties are hereby expressly disclaimed.

SELLER SHALL NOT BE LIABLE TO THE USER OR ANY OTHER PERSON UNDER ANY LEGAL THEORY, INCLUDING BUT NOT LIMITED TO NEGLIGENCE OR STRICT LIABILITY, FOR ANY INJURY OR FOR ANY DIRECT, INDIRECT, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES SUSTAINED OR INCURRED BY REASON OF THE USE OF ANY OF THE SELLER'S PRODUCTS THAT WERE DEFECTIVE.

> © 3M 1998 78-8124-4705-6

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Adhesive Tapes category:

Click to view products by 3M manufacturer:

Other Similar products are found below :

 56-YELLOW-34"X72YD
 00-021200-13972-7
 021200-64630
 60 TAPE (1")
 62-GRAY-12"X36YD
 62-GRAY-1"X36YD
 69-1"X36YD
 764

 1"x36yd-Red
 764-1"x36yd-White
 PG ASSY
 967454-1
 1181 19MM X 16,5 METERS
 130C-1X15FT
 E39-RS1-CA
 1900-48mm
 22

 1/2X36YD
 88-SUPER-34X44FT
 890103N001
 2670
 96
 SJ3527N-Black-1.5"x50yd
 EVK-TA-TM047NBH01
 20-1"X60YDS
 2020

 18mmx55m
 H150
 363
 3900-Blue
 3939-24mmx55m
 4462-SN100
 4462W-12"x72yd
 44-TAN-14"X90YD
 471-Trans-1"x36yd-Bulk
 35

 Gray-1/2
 4008-12"X36YD
 4104-34"x18yd
 4116
 444-1"x36yd
 4466 1"
 4466W-1/2"x36yd
 4492B-12"x72yd
 4492B-1"x72yd
 4496W

 12"x36yd
 4508-1"x36yd
 4516-3/8x36
 4726 1/2"X36YD
 054007-43154
 054007-43152
 06149
 5419 1/2"