	8	7	6	5	4	3	2	1
D	3M [™] INDUSTRI For enhanced catego	IAL RJ45 MODUL	OULAR PLUG AR, IDC, WIREMOUN (44)			PERFORMANCE 1) MECHANICAL INSERTION FORCE:20N MAX. WITHDRAWL FORCE:20N MAX. (EXCLUDE LATCH MECHANISM LATCH RETENTION FORCE:49 2) ELECTRICAL CURRENT RATING:0.5A VOLTAGE RATING:24V WITHSTANDING VOLTAGE:10C INSULATION RESISTANCE:5x RETURN LOSS: TO MEET ENHANCED CATEGOR (E1A/TIA-58B B.2 CATEGOR	N MIN. DVACrms :10° OHMS of 100VDC	I MATERIAL: BODY:GLASS. PEINFROCED THERMOPLASS. PEINFROCED THERMOPLASSIC.UL 94V0 CASE.COVER AND LATCH THERMOPLASTIC.UL 94V0 CONTACT:COPPER ALLOY 2 PLATING CONTACT AREA:1.270m GOLD MIN. TERMINAL AREA:5n PLATING 3 MATED WITH INDUSTRIAL RJ45 MODULAR JACK CONNECTOR 4 COMPATIBLE CABLE: ENHANCED CATEGORY 5 CABLE AS FOLLOWS
C						NEAR END CROSS TALK: TO MEET ENHANCED CATEGOR (EIA/TIA-S68 B.2 CATS) SHIELD RESISTANCE: IOO MILLI OHM AT INITIAI CONTACT RESISTANCE: IOO MILLI OHM AT INITIAI DELTA R 25 MILLI OHM MAX EVALUATION TEST BASED ON NOTE THE HIGH FREO.ELECTRICAL OF CABLES DIFFERS ACCORE SUCH AS CABLE STRUCTURE, AND INSTALLATION LAYOUT.	L CONDITION L CONDITION AFTER TB-5102-0130-0 PERFORMANCE DING TO FACTORS CABLE LENGTH,	1) WIRE AWG 24 SOLID AWG 24 STRANDED (7WIRES) AWG 26 STRANDED (7WIRES) 2) CABLE GROUNDING BRAIDED SHILED OR DRAIN WIRES 3) CABLE OUTER DIAMETER 6.8mm MAX. 5 ROHS COMPLIANT. SEE THE REGULATORY INFORMATION APPENDIX (RIA) IN THE "ROHS COMPLIANCE" SECTION OF
∆						THÈN TÒ CHẾCK THE HIGH F PERFORMANCE OF THE CABLE BEFORE INSTALLATION IS F 3)ENVIRONMENTAL TEMPERATURE RATING:-40°C NOTE FOR LOW TEMPERATURE LIMI EXCLUDING CABLE PERFORMA FOR HIGH TEMPERATURE LIMI INCLUDING TEMPERATURE RA	TO 70°C T: NCE,NO DEW CONDITION	WWW.3MCONNECTORS.COM FOR COMPLIANCE INFORMATION (RIA EI & CI APPLY). 6 6 FOR PRODUCT SPECIFICATION AND WARRANTY INFORMATION SEE 3M 78-5102-0130-0 4 7 IN THE EVENT OF CONFLICT BETWEEN THIS DATA AND THAT CONTAINED IN THE PRODUCT SPECIFICATION THE PRODUCT SPECIFICATION 8
В			A:BROWN B:BROWN B:BROWN B:WHITE,BROWN A:BLUE B:BLUE B:BLUE B:BLUE B:BLUE B:WHITE,BLUE B:WHITE,BLUE B:WHITE,BLUE		NGE IE.ORANGE TE.GREEN NGE	*8 •7 •4 •5 •0	*1 *2 *2 *3	B
A	3M™ ELECTRONIC SOLUTIO INTERCONNECT SOLUT VISIT http://www.3 3M IS A TRADEMARK OF 3 FOR TECHNICAL, SALES OF CALL YOUR LOCAL SALES F	mconnectors.com M COMPANY. R ORDERING INFORMATION	ON SE ORDER PRODUCTION SERIES: JRI: INDUSTRIAL RJ MODULAR PLUG	45	OF COVER M 5 MODULAR PLUG	27≠M GOLD MIN.		A 39561 MAR 20,2012 JAC JAB PRODUCTION RELEASE PRODUCTION RELEASE THE ECO ISSUE DATE AD CREATING OFFICIENT STATUS AND
	8	7	6	5	А́Т 4	3	2	1

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Modular Connectors / Ethernet Connectors category:

Click to view products by 3M manufacturer:

Other Similar products are found below :

 RJE231881317T
 MP1010RX-1000
 MP44RX-1000
 GAX-3-66
 GAX-8-62
 93606-0253
 GD-A-44
 GDCX-PA-66-50
 GDCX-PN-64
 GDCX-PN-64

 PN-66
 GDCX-PN-66-50
 GDLX-A-66
 GDLX-A-88
 GDLX-N-66
 GDLX-S-88K
 GDTX-S-88-50
 GDX-PA-1010
 GLX-N

 1010M-BLK
 GLX-S-88M-BLK
 GMX-N-1010
 GMX-S-1010
 GMX-S-66
 GMX-SMT2-N-1010
 GMX-SMT2-N-64-50
 GMX-SMT2-N-88

 GMX-SMT2-S6-88
 GMX-SMT4-N-88
 GPX-2-64
 GRT1-BT1-5
 GSGX-N-2-88
 GSX-NS2-88-3.05
 GSX-NS2-88-3.05-50
 GSX-NS-88-3.05-50
 GSX-NS-88-3.05-50
 GSX-NS-88-3.05

 30
 GSX-NS-88-3.05-50
 GSX-NS-88-3.68
 1-1775629-2
 GWLX-S-88-GR
 GWLX-S9-88-YG
 1300500326
 1300500227
 1300530003

 1300570002
 1324640-4
 RJ11FTVC2G
 RJ11FTVC2N
 RJFTVX2SA1G
 132764-001
 1400000
 1413235