

3M™ Water-Soluble Wave Solder Tape 5414, Transparent


Product Description

3M™ Water-Soluble Wave Solder Tape 5414 has a water-soluble poly-vinyl alcohol-backing and a synthetic water-soluble adhesive. It is designed for use in masking gold finger areas on printed circuit boards during the wave soldering and then will dissolve completely away during typical in-line aqueous cleaning processes.

Key Features

- No adhesive residue after removal
- Low static upon liner release and when taping circuit board
- Moisture barrier packaging plus desiccant
- Humidity extremes do not affect tape properties
- Easy manual and machine application
- Die-cuttable

3M™ Water-Soluble Wave Solder Tape 5414



Product Construction/Material Description

Note: The following technical information and data should be considered representative or typical only and should not be used for specification purposes.

3M™ Water-Soluble Wave Solder Tape 5414, Transparent	
Property	Value
Backing	Poly-vinyl alcohol (PVA) film
Adhesive	Synthetic water-soluble adhesive
Liner	Kraft paper
Color	Hazy, transparent
Product form	Roll
Standard roll length	36 yards (33 meters)

Applications

- Masking of gold finger areas on printed circuit boards for wave soldering.

Application Techniques

Best results are attained when applied to a clean, dry and non-dusty surface above 0°C. To improve adhesion, ensure that firm and even pressure is applied.

3M™ Water-Soluble Wave Solder Tape 5414, Transparent

Typical Physical Properties and Performance Characteristics

Note: The following technical information and data should be considered representative or typical only and should not be used for specification purposes. Final product specifications and testing methods will be outlined in the products Certificate of Analysis (COA) that is shipped with the commercialized product.

3M™ Water-Soluble Wave Solder Tape 5414, Transparent		
Property	Test Method*	Value
Adhesion to Stainless	ASTM D3330	4 oz/in
Adhesion to Stainless (metric)	ASTM D3330	0.1 kg/25.4 mm, 0.4 N/cm
Elongation at break	ASTM D3759	334%
Temperature range (Celsius)	3M test method	-40°C to 240°C
Temperature range (Fahrenheit)	3M test method	-40°F to 464°F
Tensile strength at break	ASTM D3759	6 lb/in
Tensile strength at break (metric)	ASTM D3759	105.1 N/100 mm
Total tape thickness without liner	ASTM D3652	2.1 mil
Total tape thickness without liner (metric)	ASTM D3652	0.053 mm

*Methods listed as ASTM are tested in accordance with the ASTM method noted

Storage and Shelf Life

The shelf life of 3M™ Water-Soluble Wave Solder Tape 5414 is 12 months from the date of manufacture when stored in the original packaging materials and stored at 21°C (70°F) and 50% relative humidity.

Certificate of Analysis (COA)

The 3M Certificate of Analysis (COA) for this product is established when the product is commercially available from 3M. The commercially available product will have a COA specification established. The COA contains the 3M specifications and test methods for the products performance limits that the product will be supplied against. The 3M product is supplied to 3M COA test specifications and the COA test methods. Contact your local 3M representative for this product's COA.

This technical data sheet may contain preliminary data and may not match the COA specification limits and/or test methods that may be used for COA purposes.

Final product specifications and testing methods will be outlined in the products Certificate of Analysis (COA) that is shipped with the commercialized product.

3M™ Water-Soluble Wave Solder Tape 5414, Transparent

Regulatory: For regulatory information about this product, contact your 3M representative.

Technical Information: The technical information, recommendations and other statements contained in this document are based upon tests or experience that 3M believes are reliable, but the accuracy or completeness of such information is not guaranteed.

Product Use: Many factors beyond 3M's control and uniquely within user's control can affect the use and performance of a 3M product in a particular application. Given the variety of factors that can affect the use and performance of a 3M product, user is solely responsible for evaluating the 3M product and determining whether it is fit for a particular purpose and suitable for user's method of application.

Warranty, Limited Remedy, and Disclaimer: Unless an additional warranty is specifically stated on the applicable 3M product packaging or product literature, 3M warrants that each 3M product meets the applicable 3M product specification at the time 3M ships the product. 3M MAKES NO OTHER WARRANTIES OR CONDITIONS, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY OR CONDITION ARISING OUT OF A COURSE OF DEALING, CUSTOM OR USAGE OR TRADE. If the 3M product does not conform to this warranty, then the sole and exclusive remedy is, at 3M's option, replacement of the 3M product or refund of the purchase price.

Limitation of Liability: Except where prohibited by law, 3M will not be liable for any loss or damage arising from the 3M product, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including warranty, contract, negligence or strict liability.



Electronics Materials Solutions Division
3M Center, Building 224-3N-11
St. Paul, MN 55144-1000
1-800-251-8634 phone
651-778-4244 fax
www.3M.com/electronics

3M is a trademark of 3M Company.
Please recycle.
©3M 2017. All rights reserved.
70-0709-4456-9

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Adhesive Tapes](#) category:

Click to view products by [3M](#) manufacturer:

Other Similar products are found below :

[56-YELLOW-34"X72YD](#) [00-021200-13972-7](#) [021200-64630](#) [60 TAPE \(1"\)](#) [62-GRAY-12"X36YD](#) [62-GRAY-1"X36YD](#) [69-1"X36YD](#) [764-1"x36yd-Red](#) [764-1"x36yd-White](#) [9500PC-3/4](#) [967454-1](#) [1181 19MM X 16,5 METERS](#) [130C-1X15FT](#) [E39-RS1-CA](#) [1900-48mm](#) [22-1/2X36YD](#) [88-SUPER-34X44FT](#) [890103N001](#) [2670](#) [96](#) [EVK-TA-TM047NBH01](#) [20-1"X60YDS](#) [2020-18mmx55m](#) [H150](#) [363](#) [3900-Blue](#) [3939-24mmx55m](#) [44-TAN-14"X90YD](#) [4504-34x18](#) [471-Trans-1"x36yd-Bulk](#) [5414 34X36](#) [35-Gray-1/2](#) [4008-12"X36YD](#) [4104-34"x18yd](#) [4116](#) [444-1"x36yd](#) [4466 1"](#) [4466W-1/2"x36yd](#) [4492B-12"x72yd](#) [4492B-1"x72yd](#) [4496W-12"x36yd](#) [4508-1"x36yd](#) [4516-3/8x36](#) [4726](#) [1/2"X36YD](#) [054007-43154](#) [054007-43152](#) [06149](#) [11-32-2857](#) [5419 1/2"](#) [56 TAPE \(1/2"\)](#)