# **3M**

# **Specialty Terminals**

61-S, 62-S, 63-S Butt Connector, Non-Insulated, Seamless



# **Data Sheet**

Product Number	Wire Range (AWG)	L	Thickness	Barrel Length	Barrel I.D.
61-S	22-18	0.63	0.031	0.28	0.062
62-S	16-14	0.66	0.031	0.30	0.095
63-S	12-10	0.81	0.038	0.38	0.142



UNDERWRITERS LABORATORIES STANDARD NO. UL 486C 3M FILE NO. E23438



CANADIAN STANDARDS ASSOCIATION STANDARD NO. 22.2 NO. 0, 65 3M FILE NO. LR22190

**Installation Information** 

### **△WARNING**

Turn power off before installing or removing terminal. All electrical work should be done according to appropriate electrical codes.

UL Listed and CSA Certified for use on stranded copper (AWG) wire only.

Strip away the end 3/8 inch of wire insulation.

Make the crimp in the proper station of a recommended 3M crimp tool: TH-440, TH-450 (scissor style) or TR-490 (ratchet style) hand tools.

## **Specifications**

Wire Size:
Barrel Seam:
Maximum Current:
Terminal Material:
Terminal Plating:

See Table Above Seamless Same as Wire ETP Copper Tin



■ Barrel Crimp (Required)

#### **Engineering Specification**

Crimp-type terminals shall, electrically and mechanically, connect permanently to the pre-stripped end of two stranded copper wires.

The connector line shall offer barrel variations in wire (AWG) size (22-18, 16-14, 12-10) and construction (non-insulated brazed seam, vinyl insulated butted seam, nylon insulated seamless, etc.). The connector line shall have regulatory agency coverage (UL Listing, CSA Certification). The connectors shall be marked with the wire range and manufacturer's symbol (个).

The non-insulated, seamless butt connector shall be tin plated, annealed copper, having a double-length, round seamless barrel with a center stop, sized for a specified (AWG) wire range (22-18, 16-14, 12-10).

Insulated connectors shall be UL Listed for 600 volts maximum, building wire: 1000 volts maximum, signs or fixtures and temperature rated 221°F (105°C) maximum.

3M is a trademark of 3M.



(UL) is a trademark of Underwriters Laboratories.



is a trademark of Canadian Standards Association.

#### IMPORTANT NOTICE

Before using this product, you must evaluate it and determine if it is suitable for your intended application. You assume all risks and liability associated with such use.

Warranty; Limited Remedy; Limited Liability. This product will be free from defects in material and manufacture as of the date of purchase. 3M MAKES NO OTHER WARRANTIES INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. If this product is defective within the warranty period stated above, your exclusive remedy shall be, at 3M's option, to replace or repair the 3M product or refund the purchase price of the 3M product. Except where prohibited by law, 3M will not be liable for any loss or damage arising from this 3M product, whether direct, indirect, special, incidental or consequential regardless of the legal theory asserted.



**Electrical Products Division** 

### **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Terminals category:

Click to view products by 3M manufacturer:

Other Similar products are found below:

00-054007-01074-6 00-054007-70206-1 00-054007-70210-8 00-054007-70217-7 00-054007-70226-9 00-054007-70228-3 00-054007-70248-1 00-054007-70256-6 00-054007-70301-3 00-054007-70316-7 00-054007-49560-4 00-054007-70209-2 00-054007-70225-2 00-054007-70227-6 00-054007-70231-3 00-054007-70241-2 00-054007-70242-9 00-054007-70244-3 00-054007-70246-7 00-054007-70263-4 00-054007-70288-7 00-054007-70290-0 00-054007-70300-6 00-054007-70304-4 01-2065-1-0216 01-2900-1-04412 00581P0075 600TS-10 60205-1 604200-1 605601-1 60598-1-CUT-TAPE 61314-6-C 61810-3 61-S 62149-1 626-0194 62-NBM-A 63-S 640179-1 M55155/059103 M55155/079C01 M55155/099B03 M55155/099H02 M55155/109H01 M55155/109H02 M55155/12XH05 M55155/16XH02 M55155/29-5S M55155/29XJ08