



Heat Shrink Tubing

SFTW-202 (A-B) High Flexible Polyolefin

Data Sheet

Product Description

SFTW-202 is a highly flexible, fast shrinking tubing, offering superior properties. With excellent chemical and thermal resistance it is capable of meeting the toughest demands of the aerospace, military, offshore and railway industries. It meets the stringent requirements of VG 95343, UL 224, Def Stan and other international specifications. SFTW-202 is available in various colours and is ideally suited for identification purposes.

Technical Features

Continuous operating temperature range:	-55°C to +135°C	Shrink ratio:	2 : 1
Base material:	Polyolefin	Shrink temperature:	100°C (min.)
Flammability:	Coloured - Self extinguishing Transparent – not self extinguishing	Longitudinal change:	-5% max.
Tensile strength:	18 N/mm ²	Dielectric strength:	450 kV/cm
Specifications:	MIL-I-23053/5 Class 1, 2, 3 UL 224 AFT 125°C ¹⁾ PANAVIA 6493 (except 51.0-102.0)	Det Norske Veritas ¹⁾ Def Stan 59-97/3 Type 2A&B DIN-VDE 0341 T9005	VG 95353/5 A and B ²⁾ CSA CUL

¹⁾ except transparent ²⁾ Approval held by 3M ECC Europa BV

Ordering Information Type SFTW-202 (A-B)

Bore as supplied minimum (mm)	Bore recovered maximum (mm)	Wall thickness fully recovered (mm)	Standard pack reel or 1.0m length (m)	Special pack Medium reel * (m)	Colours
1.2	0.6	0.4	400	100	Standard Colours: Black White Red Blue Yellow Transparent Brown Green
1.6	0.8	0.4	400	100	
2.4	1.2	0.5	400	100	
3.2	1.6	0.5	400	100	
4.8	2.4	0.5	300	75	
6.4	3.2	0.6	300	75	
9.5	4.8	0.6	150	50	
12.7	6.4	0.6	100	50	
19.0	9.5	0.8	50	25	
25.4	12.7	0.9	50	25	
38.0	19.0	1.0	50	Not Available	
51.0	25.4	1.1	35	Not Available	
76.0	38.0	1.3	25	Not Available	
102.0	51.0	1.4	25	Not Available	Special Colours: Violet Grey Orange

¹⁾ except transparent ²⁾ approval held by 3M ECC Europa BV

Important Notice

Technical information provided by 3M is based on experience and/or tests believed to be reliable, but their accuracy is not guaranteed and the results may not be relevant to every user's application. For this reason 3M does not accept responsibility or liability, direct or consequential, arising from reliance upon any information provided and the user should determine the suitability of the products for their intended use. Nothing in this statement will be deemed to exclude or restrict 3M's liability for death or personal injury arising from its negligence. All questions of liability relating to 3M products are governed by the seller's terms of sale subject where applicable to the prevailing law. If any goods supplied or processed by or on behalf of 3M prove on inspection to be defective in material or workmanship, 3M will (at its option) replace the same or refund to the Buyer the price paid for the goods or services. Except as set out above, all warranties and conditions, whether express or implied, statutory or otherwise are excluded to the fullest extent permissible at law. 3M is a trademark of the 3M Company. Printed in the UK. © 3M United Kingdom PLC, 2004.

Electrical Markets Division

3M United Kingdom PLC
Sales Office
PO Box 393
Bedford MK41 0YE
Telephone: 01234 229462
Fax: 01234 229433

3M Ireland
Sales Office
3M House, Adelphi Centre, Upper Georges Street
Dun Laoghaire, Co Dublin, Ireland
Telephone: 353 1 280 3555
Fax: 353 1 280 3509

3M United Kingdom PLC
Head Office
3M Centre, Cain Road
Bracknell, Berkshire RG12 8HT
Telephone: 01344 858000
Fax: 01344 858758

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Heat Shrink Tubing and Sleeves](#) category:

Click to view products by [3M](#) manufacturer:

Other Similar products are found below :

[770-006S102](#) [5685710001](#) [CR6145-000](#) [CR8248-000](#) [CR9960-000](#) [603312-4](#) [607381P039](#) [611112-000](#) [617867N001](#) [6500750004](#) [CZ1420-000](#) [D-306-38](#) [770-003S106W2](#) [770-005S105W1](#) [770-005S106W1](#) [770-007A303](#) [770-010Y106W1](#) [770-010Y706W1](#) [7771210001](#) [MFP-1/4"-Clear](#) [MFP-3/64"-Clear](#) [790-3012](#) [MFT-MT2000-NO.14-0-SP](#) [MHHT-4-15K2-G-104](#) [MIL-LT-1-1/2-4-SP](#) [MIL-LT-1-1/2-9-STK](#) [MIL-LT-1/2-2-STK](#) [MIL-LT-3-0-SP](#) [MIL-LT-3/32-0-SP](#) [MIL-LT-3/32-6-SP](#) [MIL-LT-3/4-6-SP](#) [MIL-LT-3/8-0-SP](#) [8159270001](#) [839602-000](#) [8423-6](#) [FP301-116-6"-Black](#) [FP301-1/2-48"-Black](#) [FP301-12-48"-Black-Hdr](#) [FP301-1/4-48"-Black](#) [FP301-1/4-48"-White-Hdr](#) [FP301-18-48"-Black-Hdr](#) [FP301-1/8-6"-Black](#) [FP301-18-6"-Black-Bulk](#) [FP301-316-48"-Blue-Hdr](#) [FP301-316-6"-Clear](#) [FP301-332-6"-Black](#) [912229N002](#) [120-126-16BL](#) [121-001-09](#) [121-018-32](#)