
## **3M**

# **Specialty Terminals**

72F-110-20-P

Female Disconnect, Vinyl Insulated, Butted Seam



## **Data Sheet**

Product Number	Wire Range (AWG)	<u>Mates with Male Tab</u> Width (W´) x Thickness	L	Barrel Length	Barrel I.D.	Maximum Insulation Diameter
72F-110-20-P	16-14	0.110 x 0.020 0.125 x 0.020	0.81	0.19	0.115	0.145

#### **Specifications**

Wire Size: See Table Above Barrel Seam: Butted

Maximum Operating Temp: 221°F (105°C)
Maximum Current: Same as Wire

Insulator Material: Vinyl
Terminal Material: Brass
Plating: Tin

#### **Installation Information**

#### **<b>△WARNING**

Turn power off before installing or removing terminal. All electrical work should be done according to appropriate electrical codes.

For use on stranded copper wire only.

Strip away the end 3/8 inch of wire insulation.

Make the crimp in the proper station of a recommended 3M crimp tool: TH-440, TH-450 (scissor style) or TR-490 (ratchet style) hand tools.





#### **Engineering Specification**

Crimp-Type Female Disconnect Terminals shall, electrically and mechanically, connect permanently to a prestripped end of a stranded copper wire, and have a tongue portion with fingers which grip a Male Disconnect in a separable, reusable manner, forming a Quick Connect Wiring Termination.

The connector line shall offer tongue variations (sized to grip Male Tabs: 0.110" x 0.020" or 0.110" x 0.032" per ANSI/NEMA CD-2) and barrel variations construction, non-insulated, vinyl insulated with insulation grip, nylon fully insulated, etc. The tongue portion shall be marked with the wire range and manufacturer's name or trade mark (\(\Tau\)).

The Vinyl Insulated Miniature 0.110" Female Disconnect shall be tin plated 0.010" thick brass with a tongue for gripping a 0.110" or 0.125" male tab of 0.020" thickness and with a 0.19" long barrel covered by a molded vinyl sleeve, color coded and sized for a specified (AWG) wire range (16-14).

3M is a trademark of 3M

#### IMPORTANT NOTICE

Before using this product, you must evaluate it and determine if it is suitable for your intended application. You assume all risks and liability associated with such use.

Warranty; Limited Remedy; Limited Liability. This product will be free from defects in material and manufacture as of the date of purchase. 3M MAKES NO OTHER WARRANTIES INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. If this product is defective within the warranty period stated above, your exclusive remedy shall be, at 3M's option, to replace or repair the 3M product or refund the purchase price of the 3M product. Except where prohibited by law, 3M will not be liable for any loss or damage arising from this 3M product, whether direct, indirect, special, incidental or consequential regardless of the legal theory asserted.



### **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Terminals category:

Click to view products by 3M manufacturer:

Other Similar products are found below:

00-054007-01074-6 00-054007-70206-1 00-054007-70210-8 00-054007-70217-7 00-054007-70226-9 00-054007-70228-3 00-054007-70248-1 00-054007-70256-6 00-054007-70301-3 00-054007-70316-7 00-054007-49560-4 00-054007-70209-2 00-054007-70225-2 00-054007-70227-6 00-054007-70231-3 00-054007-70241-2 00-054007-70242-9 00-054007-70244-3 00-054007-70246-7 00-054007-70263-4 00-054007-70288-7 00-054007-70290-0 00-054007-70300-6 00-054007-70304-4 01-2065-1-0216 01-2900-1-04412 00581P0075 600TS-10 60205-1 604200-1 605601-1 60598-1-CUT-TAPE 61314-6-C 61810-3 61-S 62149-1 626-0194 62-NBM-A 63-S 640179-1 M55155/059103 M55155/079C01 M55155/099B03 M55155/099H02 M55155/109H01 M55155/109H02 M55155/12XH05 M55155/16XH02 M55155/29-5S M55155/29XJ08