

# 3M™ Round Conductor Flat Cable for Link Connector

0.100", 19 AWG Stranded, PVC

79100 Series



- Designed for factory automation applications
- Recommended for use with 3M™ Link Connectors
- 19 AWG [0.75 mm<sup>2</sup>] on 0.100" [2.54 mm] centers permits IDC termination
- RoHS Compliant. See the Regulatory Information Appendix (RIA) in the "RoHS compliance" section of [www.3Mconnector.com](http://www.3Mconnector.com) for compliance information. (RIA E1 & C1 apply)

Date Modified: July 22, 2010

TS-2323-C  
Sheet 1 of 2

## Physical

### Insulation:

Material: Heat Resistant Polyvinyl Chloride (PVC)

Color: Black, Red, White, Green

**Marking:** 3M Cable 79100-075-4F1 0.75 mm<sup>2</sup> x 4  
E118773-K (UL) CL2 4C19AWG 90C \*\*  
(\* indicates production lot code)

### Conductors:

Description: 0.75 mm<sup>2</sup> [19 AWG], 30 strands x 0.18 mm [33 AWG], Tinned Stranded Copper

**Mating Connectors:** Link Connector, 38104-0018-000 FL, TS-2098

## Electrical

**Voltage Rating:** CL2 (UL 13)

**Insulation Resistance:** >1 x 10<sup>10</sup> Ω / 10 ft [3 m]

**Withstand Voltage:** 1,500 V<sub>AC</sub> for one minute

### Unbalanced

**Characteristic Impedance:** 67.36 Ω

**Capacitance @1 MHz:** 23.64 pF/ft (77.56pF/m)

**Inductance:** 0.11 uH/ft (0.35uH/m)

**Propagation Delay:** 1.59 ns/ft (5.22ns/m)

**Velocity of Propagation:** 63.80%

### Balanced

114.24 Ω

13.49 pF/ft (44.27pF/m)

0.18 uH/ft (0.58uH/m)

1.54 ns/ft (5.06ns/m)

65.90%

Note: Unbalanced is measured between ground signal – ground conductors. Balanced is measured between conductors within a pair.

## Environmental

**Temperature Rating:** CL2, 90°C Max

**Flammability Rating:** CL2 (UL 13)


UL File No. E118773-K

# 3M™ Round Conductor Flat Cable for Link Connector

0.100", 19 AWG Stranded, PVC

79100 Series

## Product Dimensions



Inch [mm]

## Ordering Information

**79100 - 075 - 4F1**

Note: Available in standard 200 meter rolls, please specify length when ordering. Contact 3M for availability of additional conductor counts and/or custom roll lengths.

TS-2323-C  
Sheet 2 of 2

**Important Notice**

All statements, technical information, and recommendations related to 3M's products are based on information believed to be reliable, but the accuracy or completeness is not guaranteed. Before using this product, you must evaluate it and determine if it is suitable for your intended application. You assume all risks and liability associated with such use. Any statements related to the product which are not contained in 3M's current publications, or any contrary statements contained on your purchase order shall have no force or effect unless expressly agreed upon, in writing, by an authorized officer of 3M.

**Warranty; Limited Remedy; Limited Liability.**

This product will be free from defects in material and manufacture for a period of one (1) year from the time of purchase. **3M MAKES NO OTHER WARRANTIES INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.** If this product is defective within the warranty period stated above, your exclusive remedy shall be, at 3M's option, to replace or repair the 3M product or refund the purchase price of the 3M product. **Except where prohibited by law, 3M will not be liable for any indirect, special, incidental or consequential loss or damage arising from this 3M product, regardless of the legal theory asserted.**

**3M Electronics Solutions Division**

6801 River Place Blvd.  
Austin, TX 78726-9000  
U.S.A.  
1-800-225-5373  
[www.3Mconnector.com](http://www.3Mconnector.com)

Please recycle. Printed in USA.  
© 3M 2010. All rights reserved.  
RIA-2217B-E

3M is a trademark of 3M Company.

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Flat Cables](#) category:*

*Click to view products by [3M](#) manufacturer:*

Other Similar products are found below :

[F28-A25G](#) [F28-A34G](#) [F28-A36G](#) [FST-23A-15](#) [AYT1510-US](#) [171-37G](#) [C336514-500](#) [902220736002000](#) [902220736006000](#) [28100-0614](#)  
[9L28010-008-H300](#) [9L28014-008-H300](#) [F28-A24G](#) [F28-A60G](#) [25WDY00002](#) [28100-0571](#) [28100-0602](#) [28100-0650](#) [28100-0664](#) [336506-](#)  
[100SF](#) [336512-300](#) [336518](#) [336537-CUT-LENGTH](#) [3447/10-100](#) [362514100MSF](#) [40WDY00005](#) [AYT51163](#) [336506-300](#) [C3302/16](#)  
[C374910](#) [3749/10-100](#) [375630](#) [3-971111-6](#) [1-1437356-3](#) [812504](#) [20WDY00001](#) [5-1437214-8](#) [3355/15](#) [40WBY00007](#) [3609/12](#) [5111196336](#)  
[607.5689.087](#) [607.5689.091](#) [3801/04](#) [3754/12](#) [3625/22100MSF](#) [902220736005000](#) [902220736004000](#) [C3811/10-100](#) [3625/22-30M](#)