

April, 2015

3M™ Double Coated Tape 93005LE

Product Description

3M™ 93005LE is a 50µm Double Coated Polyester Tape featuring 3M™ Type 300LSE Acrylic Adhesive. Performance features include superior adhesion to Polypropylene, great resistance to consumer chemicals and excellent holding power. 3M type 300LSE acrylic adhesive has a long history of successfully bonding a wide variety of similar and dissimilar materials such as metals, most plastics, glass, papers, and painted surfaces.



Technical Information Note

The following technical information and data should be considered representative or typical only and should not be used for specification purposes.

Typical Physical Properties

Property	Values		Notes
Total Tape Thickness without liner	0.05 mm	1.97 mil	
Total Thickness with liner	0.314 mm	12.4 mil	
Faceside Adhesive Thickness	0.019 mm	0.75 mil	Faceside adhesive is on the interior of the roll, exposed when unwound and liner removed.
Backside Adhesive Thickness	0.019 mm	0.75 mil	Backside adhesive is on the exterior of the roll, exposed when liner is removed.
Carrier Thickness	0.012 mm	0.5 mil	
Thickness Tolerance	± 10 %		
Faceside Adhesive Type	300LSE Acrylic		Faceside adhesive is on the interior of the roll, exposed when unwound and liner removed.
Backside Adhesive Type	300LSE Acrylic		Backside adhesive is on the exterior of the roll, exposed when liner is removed.
Adhesive Carrier	Transparent Polyester Film		
Primary Liner Type	Polycoated Kraft		Inner liner is primary(stays with die-cut part); Outer liner is secondary (removed first)
Secondary Liner Type	Polycoated Kraft		Inner liner is primary(stays with die-cut part); Outer liner is secondary (removed first)
Primary Liner Thickness	0.107 mm	4.2 mil	
Secondary Liner Thickness	0.157 mm	6.2 mil	

Typical Performance Characteristics

Property	Values		Method	Test Condition	Substrate	Backing
Tensile Strength	1.099 N/mm ²	159.4 lb/in ²	ASTM D897	10mm/min	Stainless Steel	
Dynamic Shear	1.084 N/mm ²	157.2 lb/in ²	ASTM D1002	10mm/min	Stainless Steel	Polyester Film
Impact Shear Strength	1.545 J/in ²		ASTM D950	Pendulum Impact	Stainless Steel	

Faceside Adhesive 180° Peel Adhesion		Dwell/Cure Time
6.18 N/cm	56.5 oz/in	20 min @ Room Temperature
7.9 N/cm	72.2 oz/in	72 hr @ Room Temperature

Property: Faceside Adhesive 180° Peel Adhesion
 Method: ASTM D3330
 Substrate: Stainless Steel
 Backing: 2 mil Polyester Film

Backside Adhesive 180° Peel Adhesion		Dwell/Cure Time	Substrate
7.7 N/cm	70.4 oz/in	20 min @ Room Temperature	Stainless Steel
8.24 N/cm	75.3 oz/in	72 hr @ Room Temperature	Stainless Steel
6.19 N/cm	56.6 oz/in	72 hr @ Room Temperature	ABS
7.74 N/cm	70.7 oz/in	72 hr @ Room Temperature	Polypropylene (PP)
3.76 N/cm	34.4 oz/in	72 hr @ Room Temperature	High Density Polyethylene (HDPE)

Property: Backside Adhesive 180° Peel Adhesion
 Method: ASTM D3330
 Backing: 2 mil Polyester Film

Storage and Shelf Life

Store at room temperature conditions of 70°F (21°C) and 50% relative humidity.
 If stored properly, product retains its performance and properties for 24 months from date of manufacture.

Information

Technical Information: The technical information, guidance, and other statements contained in this document or otherwise provided by 3M are based upon records, tests, or experience that 3M believes to be reliable, but the accuracy, completeness, and representative nature of such information is not guaranteed. Such information is intended for people with knowledge and technical skills sufficient to assess and apply their own informed judgment to the information. No license under any 3M or third party intellectual property rights is granted or implied with this information.

Product Selection and Use: Many factors beyond 3M's control and uniquely within user's knowledge and control can affect the use and performance of a 3M product in a particular application. As a result, customer is solely responsible for evaluating the product and determining whether it is appropriate and suitable for customer's application, including conducting a workplace hazard assessment and reviewing all applicable regulations and standards (e.g., OSHA, ANSI, etc.). Failure to properly evaluate, select, and use a 3M product and appropriate safety products, or to meet all applicable safety regulations, may result in injury, sickness, death, and/or harm to property.

Warranty, Limited Remedy, and Disclaimer: Unless a different warranty is specifically stated on the applicable 3M product packaging or product literature (in which case such warranty governs), 3M warrants that each 3M product meets the applicable 3M product specification at the time 3M ships the product. 3M MAKES NO OTHER WARRANTIES OR CONDITIONS, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR ARISING OUT OF A COURSE OF DEALING, CUSTOM, OR USAGE OF TRADE. If a 3M product does not conform to this warranty, then the sole and exclusive remedy is, at 3M's option, replacement of the 3M product or refund of the purchase price.

Limitation of Liability: Except for the limited remedy stated above, and except to the extent prohibited by law, 3M will not be liable for any loss or damage arising from or related to the 3M product, whether direct, indirect, special, incidental, or consequential (including, but not limited to, lost profits or business opportunity), regardless of the legal or equitable theory asserted, including, but not limited to, warranty, contract, negligence, or strict liability.

Trademarks

3M is a trademark of 3M Company

References

Safety Data Sheet (SDS)

https://www.3m.com/3M/en_US/company-us/SDS-search/results/?gsaAction=msdsSRA&msdsLocale=en_US&co=ptn&q=93005LE

For Additional Information

To request additional product information or to arrange for sales assistance, call 3M Technical Service at 651-736-8205. Address correspondence to: 3M Industrial Adhesives and Tapes Division, 3M Center, Building 230-2E-10, St. Paul, MN 55144-1000.



X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Thermal Interface Products](#) category:

Click to view products by [3M](#) manufacturer:

Other Similar products are found below :

[7721-9PPS](#) [FGN80-2](#) [PFM-172-60](#) [A-40](#) [174-9-230P](#) [9601-7](#) [5300AC](#) [1.500G](#) [08133](#) [V6622C](#) [TVQF-1225-07S](#) [TP0001](#) [4860](#) [SC80-W2](#)
[V6516C](#) [A17536-04](#) [A17713-06](#) [A17713-05](#) [A17775-03](#) [A17690-05](#) [A17653-02](#) [A17690-04](#) [A17775-05](#) [A17775-06](#) [A17690-08](#) [A17689-](#)
[06](#) [A17653-06](#) [A17690-12](#) [A17653-03](#) [A17536-02](#) [A17752-04](#) [A17752-07](#) [A17634-12](#) [19-36565-0001-1](#) [A17752-10](#) [A17752-09](#) [22000-](#)
[001A](#) [A17752-20](#) [A17752-12](#) [A17653-04](#) [A17634-10](#) [A17634-07](#) [A17156-02](#) [TA-1.75](#) [30195](#) [A17751-04](#) [V6516A](#) [SPT400-12-13.5-25](#)
[189651F00000G](#) [A17883-14](#) [A17883-15](#)