3M[™] Through-Board Socket

2.54 mm x 2.54 mm, Dual Entry, Surface Mount



- High temperature dielectric
- "No lead" reflow solder compatible
- Dual row design, 4–60 pins
- Mates with pin headers for board stacking applications
- Dual entry design allows mating from top side or bottom side through the printed circuit board
- RoHS Compliant. See the Regulatory Information Appendix (RIA) in the RoHS compliance section of www.3Mconnectors.com for compliance information (RIA E1 & C1 apply)

Date Modified: November 26, 2012

TS-2191-D Sheet 1 of 2

Physical

Insulation	
Material:	High Temperature Thermoplastic
Flammability:	UL 94V-0
Color:	Black
Contact	
Material:	Copper Alloy
Plating	
Underplating:	1.25–2.5 μm [50–100 μ"] Nickel
Wiping Area:	Flash Gold
Solder Tail Area:	1–3 μm [40–118 μ"] Matte Tin

Electrical

 $\label{eq:current} \begin{array}{ll} \mbox{Current Rating:} & 2 \mbox{ A} \\ \mbox{Insulation Resistance:} & > 5 \ x \ 10^8 \ Ohm \ at \ 100 \ V_{_{DC}} \\ \mbox{Withstanding Voltage:} & 1000 \ V_{_{DC}} \end{array}$

Environmental

Temperature Range:-25 °C to +105 °CProcessing Temperature:max. 260 °C (Profile per J-STD-020C)Moisture Sensitivity Level:1 (per J-STD-020C)

UL File No.: E68080

3M[™] Through-Board Socket

2.54 mm x 2.54 mm, Dual Entry, Surface Mount

PCB Layout n/2 x 2.54±0.25[.10±.01] Through hole (no plating) 1.02 [.04] 10.16 [.40] .54 |.10| \$ 1.02 [.04] 7.60 [.30] [.26] ₩ ⊕ ₫ .20 [.07] 6.50 5.08 ŧ 83 0.50 [.02] 2.54 [.10] .05 2,54 [.10] In/2-11x 2.54 [.10] 3.10 [.12] ·22 ln/2-1)x2.54 [.10] PP - Pad (optional) [°29] 4.25 [.17] 7°40 ¥V ेल 6.60 [.26] n = No. of Contacts Tape & Reel Option Tolerance Unless Noted [mm] Nominal Size Contact 0.5-3 3–6 6-30 30-120 12-16 18-24 26-34 36-44 46-56 10 58-60 Quantity +/- 0.1 +/- 0.1 +/- 0.2 +/- 0.3 Linear Dim Tape Width 24 32 44 56 72 88 104 +/- 0.2 +/- 0.5 +/- 1 +/- 1 [mm] Radii **Ordering Information** 9632XX - 2000 - AR - XX (RIA E1 & C1 Apply) Packaging: TP = Tube without Pad (4 to 60 pos) PT = Tube with Pad (10 to 60 pos) Contact Quantity: PR = Tape & Reel with Pad (10 to 60 pos) 04-60 Pins / 2 Row TS-2191-D Sheet 2 of 2

Important Notice

All statements, technical information, and recommendations related to 3M's products are based on information believed to be reliable, but the accuracy or completeness is not guaranteed. Before using this product, you must evaluate it and determine if it is suitable for your intended application. You assume all risks and liability associated with such use. Any statements related to the product which are not contained in 3M's current publications, or any contrary statements contained on your purchase order shall have no force or effect unless expressly agreed upon, in writing, by an authorized officer of 3M.

Warranty; Limited Remedy; Limited Liability.

This product will be free from defects in material and manufacture for a period of ninety (90) days from the time of purchase. **3M MAKES NO OTHER WARRANTIES INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.** If this product is defective within the warranty period stated above, your exclusive remedy shall be, at 3M's option, to replace or repair the 3M product or refund the purchase price of the 3M product. **Except where prohibited by law, 3M will not be liable for any indirect, special, incidental or consequential loss or damage arising from this 3M product, regardless of the legal theory asserted.**



3M Electronics Solutions Division 6801 River Place Blvd. Austin, TX 78726-9000 U.S.A. 1-800-225-5373 www.3Mconnectors.com

Please recycle. Printed in USA. © 3M 2012. All rights reserved. RIA-2217A-E

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Headers & Wire Housings category:

Click to view products by 3M manufacturer:

Other Similar products are found below :

 892-18-020-10-001101
 58102-G61-06LF
 582553-1
 0009485154
 009176003701906
 0050291907
 LY20-4P-DT1-P1E-BR
 02.125.8002.8

 609-3404
 61062-3
 622-0430
 622-3653LF
 63453-116
 636-1030
 636-1427
 636-3427
 636-4007
 641938-9
 641991-4
 644827-2
 65817-010LF

 65817-015LF
 65863-015LF
 66207-023LF
 67095-007LF
 67601157
 68648-049
 70.362.1628.0
 70-4210
 70-4226B
 70-4853B
 707-5020
 707

 5028
 71.350.2428.0
 71918-208LF
 71961-016LF
 733-134
 733-162
 754199-000
 760-3052
 787-8014-00
 79531-3000
 FCN-360C032-B
 FCN

 367T-T012/H
 FCN-723D010/2
 80.063.4001.1
 800-90-001-10-001000
 800-90-010-10-002000
 801-43-002-10-013000
 801-43-006-10-002000