## TH-450 Scissors Style

The most versatile heavy-duty tool we've ever offered.

- Made of 1.40" (35,5 mm) high-strength, heat-treated carbon steel
- Tool is lightweight without sacrificing strength
- Handles a variety of terminal and conductor styles, including flags, closedend connectors, crimp sleeves and standard parts, insulated and noninsulated
- Range of 26-6 AWG
- 3M Terminals and Connectors are ULListed and CSACertified when crimped with the TH-450

## Features:


1. Anvil-type wire cutter.

2–3. Crimp dies for 26–10 AWG insulated terminals and closed-end connectors.

4. Cut-off dies for mild steel and non-ferrous screws.

5. Crimp dies for 12–6 AWG non-insulated terminals, connectors, flags, disconnects, crimp sleeves and high-temperature terminals.

6. Crimp dies for 6–8 AWG insulated terminals and butt connectors.




8. Wire-stripping stations for circumferencial cut-less effort.

9. Strip length guide.

10. Textured, cushioned grips, red.

For specific tooling applications, refer to the smallest unit container or the Tool Selection Guides in the Appendix.

Product		Miro	Teele/	Toolo/
(add package code	UPC	Wire	Tools/	Tools/
when ordering)	(054007-)	Range	Carton	Case
TH-450	13760	26-6	1	10



## **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for 3m manufacturer:

Other Similar products are found below :

<u>SC401U 98-0003-3071-6 80-0012-6467-2 00-054007-70220-7 00-054007-34717-0 021200-40230 6840-2X50-GRAY 701-W 7993MP-</u> 2CIRCLE-100 FDV14-187C FE-5100-5126-4 FE-5100-5273-4 FE-5100-5492-0 8124/14 812510-100 8125/17 813216 8204-3LFM 8425-8 MNG14BCX FP301-1-6"-Clear FV14-6C 920102-01-25-R 927739-40 929835-01-28-RK 929974-01-40-R 951240-2520-AR-PR 960X/980X 98-0003-3075-7 HF36564-100 HF625/26-30 1/2-5-4492W 1/2-5-5430 1/2-5-850S 1/2-5-3431 12X12-6-4056B 12X12-6-433 12X12-6-4930 1311 13-500-NB 14526-EZ5B-300-02C 1-4-4658F 14520-EZAB-300-0EC DSTK9013-3420 DSTK9015-3402 14T26-SZLB-200-0LC 14T50-SZWB-100-0NC 1-5-3437 1-5-4496W 1-5-4943F