

# 3M™ Copper-Coated Polyester Cloth Tape X-7001 Double-Coated with Conductive Adhesive

Data Sheet

April 2013

## Product Description

3M™ Copper-Coated Polyester Cloth Tape X-7001 consists of a flexible copper-plated polyester fabric backing that is coated on both sides with a unique electrically conductive pressure-sensitive acrylic adhesive.

- Copper-plated polyester woven fabric backing
- Conductive acrylic adhesive on both sides

## Agency Approvals & Self Certifications

**RoHS**  
2011/65/EU

"RoHS 2011/65/EU" means that the product or part does not contain any of the substances in excess of the maximum concentration values ("MCVs") in EU RoHS Directive 2011/65/EU. The MCVs are by weight in homogeneous materials. This information represents 3M's knowledge and belief, which may be based in whole or in part on information provided by third party suppliers to 3M.

## Applications

The X-7001 tape is typically used to bond two surfaces together, both electrically and physically. An example would be adhering a conductive gasket to another conductive gasket to a conductive surface as part of the EMI shielding solution for an electronic enclosure. The unique metallized fabric backing offers the additional benefits of excellent flexibility and conformability. The fabric backing also minimizes the possibility of finger lacerations.

## Typical Properties

Properties	Typical Value
Total thickness (backing plus adhesive) <sup>1</sup>	5.0 mil (0,13 mm)
Adhesion to steel <sup>1</sup>	58 oz/in (6,4 N/10 mm)
Electrical resistance through adhesive <sup>2</sup>	0.015 Ω (over a 25 x 25 mm area)

\* Foot notes: 1. ASTM-D-1000 Test method

2. S/3M Test method 1

## 3M™ Copper-Coated Polyester Cloth Tape X-7001 Double-Coated with Conductive Adhesive

---

**Conductivity** Since X-7001 tape double-sided metallized fabric conductive tape would typically be used as an electrical path between two surfaces, its most important feature is its conductivity. Conductive particles in the acrylic adhesive provide a multitude of electrical paths between the application substrate and the surface of the aluminum foil on each side. The resistance of the conductive path through the adhesive (measured over a 25 x 25 mm area) typically measures 15-20 milliohms

---

**Specifications** 3M Copper-Coated Polyester Cloth Tape X-7001 consists of a flexible copper-plated polyester fabric backing that is coated on both sides with a unique electrically conductive pressure-sensitive acrylic adhesive.

The tape shall be coated on one side with pressure-sensitive adhesive, which shall not require heat, moisture or other preparation prior to or subsequent to application. The adhesive coating shall be smooth and uniform and be free of lumps and bare spots. There shall be no separator between adjacent layers of the roll. The tape shall perform at a temperature of -40F° (-40°C) to 266°F (130°C) without substantial loss of tensile or electrical properties.

---

**Shelf-Life** This product has a 5-year shelf life from date of manufacture when stored in a humidity controlled storage (10°C/50°F to 27°C/80°F and <75% relative humidity).

---

**Availability** The X-7001 tape is available in standard and custom widths and lengths. Standard length is 10 m.

Please contact your local distributor; available from [3M.com/electrical](http://3M.com/electrical) [Where to Buy] or call 1.800.676.8381.

---

**Important Notice** All statements, technical information, and recommendations related to 3M's products are based on information believed to be reliable, but the accuracy or completeness is not guaranteed. Before using this product, you must evaluate it and determine if it is suitable for your intended application. You assume all risks and liability associated with such use. Any statements related to the product, which are not contained in 3M's current publications, or any contrary statements contained on your purchase order, shall have no force or effect unless expressly agreed upon, in writing, by an authorized officer of 3M.

---

**Warranty; Limited Remedy; Limited Liability** This product will be free from defects in material and manufacture at the time of purchase. **3M MAKES NO OTHER WARRANTIES INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.** If this product is defective within the warranty period stated above, your exclusive remedy shall be, at 3M's option, to replace or repair the 3M product or refund the purchase price of the 3M product. **Except where prohibited by law, 3M will not be liable for any indirect, special, incidental or consequential loss or damage arising from this 3M product, regardless of the legal theory asserted.**

---

3M is a trademark of 3M Company.



### Electrical Markets Division

6801 River Place Blvd.  
Austin, TX 78726-9000  
800.245.3573  
FAX: 800.245.0329  
[www.3M.com/electrical](http://www.3M.com/electrical)

Please recycle  
© 3M 2013 All rights reserved  
78-8126-6595-4 Rev B

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Adhesive Tapes](#) category:*

*Click to view products by [3M](#) manufacturer:*

Other Similar products are found below :

[56-YELLOW-34"X72YD](#) [00-021200-13972-7](#) [021200-64630](#) [60 TAPE \(1"\)](#) [62-GRAY-12"X36YD](#) [62-GRAY-1"X36YD](#) [69-1"X36YD](#) [764-1"x36yd-Red](#) [764-1"x36yd-White](#) [9500PC-3/4](#) [967454-1](#) [1181 19MM X 16,5 METERS](#) [130C-1X15FT](#) [E39-RS1-CA](#) [1900-48mm](#) [22-1/2X36YD](#) [88-SUPER-34X44FT](#) [890103N001](#) [2670](#) [96](#) [EVK-TA-TM047NBH01](#) [20-1"X60YDS](#) [2020-18mmx55m](#) [H150](#) [363](#) [3900-Blue](#) [3939-24mmx55m](#) [44-TAN-14"X90YD](#) [4504-34x18](#) [471-Trans-1"x36yd-Bulk](#) [5414 34X36](#) [35-Gray-1/2](#) [4008-12"X36YD](#) [4104-34"x18yd](#) [4116](#) [444-1"x36yd](#) [4466 1"](#) [4466W-1/2"x36yd](#) [4492B-12"x72yd](#) [4492B-1"x72yd](#) [4496W-12"x36yd](#) [4508-1"x36yd](#) [4516-3/8x36](#) [4726](#) [1/2"X36YD](#) [054007-43154](#) [054007-43152](#) [06149](#) [11-32-2857](#) [5419 1/2"](#) [56 TAPE \(1/2"\)](#)