

## Datasheet for part number MS3100R24-28SY

Our Catalog Part Number: MS3100R24-28SY

Brand: Cannon Product Category: Circular Product Line: MIL-DTL 5015 Series I Series: MIL-C-5015

Product Datasheet	
Thread	Connector with threaded coupling
Shell Style	Wall mounting receptacle
Endbell Style	Shortened light-weight endbell without cable clamp
Gender	Socket
Shell Size	24
Contact Arrangement	24-28
Number of contacts	24 contacts size 16
Contact Type	Solder Cup
Contact Plating	Hard silver
Contacts installed	yes
Shielding	no
Insulator Rotation	250°
Contact Rating at +20 °C (68 °F) (Size 15/15S/16/16S)	22 A
Contact Resistance (Size 15/15S/16/16S)	6 mΩ
Operating Voltage	In case of voltages greater than 50V the connector must be used in accordance with DIN VDE part 410, IEC 60364-4-41.
Insulator Resistance	Acc. To VG95319, part 2, test no. 5.12 and VG95210, part 32, test conditions B, standard insulator material > 1000 M $\Omega$
Test Voltage	1050 Vrms
Air and Creepage Paths (Min)	0,7 mm
Ambient Temperature	Standard insulator material -55°/+125°C (-67/257°F)
Safety Provisions	IP65 acc. to DIN 40 050
Salt Spray Resistance	500 hours salt spray resistant
Mating Cycles	500 min
Sep. Force per Contact (Size 15/15S/16/16S)	1,0 N
Gage	For infos on Gage please see catalog VG95234, part 1
Coupling Torque	Closing: 14 Nm max / Opening: 0,8 Nm min
Contact Retention (Size 15/15S/16/16S)	35 N
Shell Material	Aluminium alloy
Shell Plating	Olive drab chromate coating over cadmium plating
Insulator and Gromet Material	Neoprene
Contact Material	Copper alloy
Harnessing Info: Contact Cross-Section	See assembly instruction
Harnessing Info: Insulator Diameter	See assembly instruction
Wire Stripping (Size 15/15S/16/16S)	6,2 mm
General Info	All tests in accordance with VG95319 and/or if applicable with VG95210
SC_P_Code	CA

Specifications and dimensions subject to change.

## **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for itt manufacturer:

Other Similar products are found below :

BKAF3-68102-25 MDM-37PCBR-F222 CA3108E14S-5PBA176A232 KPSE06F20-41SA206F0 CB2-18-3SCA232 MS3106E22-14P CT6E18-11SCA206 CA3101E10SL-4SF80DN MS3100F14S-7S CA3101E10SL-4PBA176F42 MS3101E181SW 024251-0016-R 024253-0025 024265-0001 024270-0015 024271-0022 024273-0043 024288-0001 M24308/24-21F CT1F22-7SS CT2-20-23SWS CT2-20-23SXS CT2-36-10PCAU CT6-24-11PSA206 CT6F36-10PCA152 CT6F9767-14-4-14S-5PC CT6T9767-14-4-14SA7SS D38999/20FG16PA-LC -MD1-21PS MDM-15PH001B-A174 MDM-15PH003B-A174 MDM-21SCBR-A174 MDM-21SCBRP-A174 MDM-21SH003B MDM25PH003BF222 MDM-31SBRP MDM-37PBRT MDM37SH004PA174 MDM-37SH013P MDM-51PSF MDM-51SCBRPL56 MDM96514-336 MDM-9PCBRM7 MDM-9PH006B-A174 MDM9SSM5 MDMV96638-13 MDVB1-21SL1 MEB97318-219 MIKQ67SH019 MIKQ67SH030