





PROJECTION	ANGLE TOLERANCE	GENERAL TOLERANCE	X. ±0.60	X. ±0.38	X. ±0.25
UNITS	mm	X. ±5.	X. ±3.	X. ±2.	X. ±2.
TITLE	FEMALE HEADER PITCH 1.27mm	S.M.T TYPE	DS1065-05		
SHEET SIZE	A4	SERIES	DS1065-05		

DRAWING NO. C-DS1065-05-XXXXX		SCALE 1:1		SHEET 1 OF 1	
DRAWING TYPE CUSTOMER					



- MOUNTING TYPE S:SMT TYPE
- HOUSING COLOR B:BLACK
- CONTACT PLATING 8: FULL GOLD FLASH
- CONNECTOR TYPE S:SOCKET
- NO.OF CONTACTS 2*1-2*40

NOTES:

- SPECIFICATIONS
 - Current Rating: 1A
 - Insulation Resistance: 500MΩ Min
 - Dielectric Withstanding: 300V AC
 - Contact Resistance: 30mΩ Max
 - Operating Temperature: -40°C to +105°C
- PART NUMBER: DS1065-05
- PRODUCT NUMBER CODE: DS1065-05 - X X X X X X X X X X

REV.	A	DESCRIPTION	NEW RELEASE	YCH 11/05/08	CHECKED	APPROVED

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Headers & Wire Housings](#) category:

Click to view products by [Connfly](#) manufacturer:

Other Similar products are found below :

[95000-104TRLF](#) [10135584-644402LF](#) [DF62W-EP2022PCA](#) [95000-106TRLF](#) [DF62W-2022SCA](#) [DF62W-EP2022PC](#) [2203348](#) [DF62W-2022SC](#) [1084018](#) [1029039](#) [1084017](#) [802-10-012-10-002000](#) [1112640](#) [1112639](#) [891-007-9SS-BST1T](#) [000-34000](#) [0008550134](#) [0009482033](#) [0009507031](#) [57102-F02-18ULF](#) [57102-S06-03LF](#) [57202-S52-04LF](#) [PCN6-15S-2.5E](#) [0039019024](#) [58102-G61-06LF](#) [582553-1](#) [0009485154](#) [0009508121](#) [0022285053](#) [0050291907](#) [018731A](#) [LY20-4P-DT1-P1E-BR](#) [02.125.8002.8](#) [60101931](#) [60598-1 \(Cut Strip\)](#) [M1625-3R/100](#) [61062-3](#) [61082-181009](#) [CSU011177004](#) [636-1427](#) [638009-1](#) [641938-9](#) [641991-4](#) [644168-1](#) [644827-2](#) [647662-1](#) [65039-019ELF](#) [65692-001LF](#) [65781-018](#) [65781-047](#)