Audible Signals INDUSTRIÄL AIRHORNS



SOUNDERS

ø127mm ø8mm Fixing Holes @135mm centres AP198 AP360 AP450 = 198mm = 360mm = 450mm 1/4 inch BSF m_F ø100mm

Features

Continuous signal direct air supply available

125dB @ 1m

MATERIAL

Aluminium Body **Brass Horn**





1		
	14	

The AP Series of air horns are suitable for general purpose signalling where high output is required such as foundries, steelworks and petrochemical plants. Operated from a

compressed air supply, their powerful low frequency sound cuts through background noise to provide an effective alarm. Optional compressor available for applications which do not have an on-site air supply.

Code No:	Air Consumption:	Air Pressure:	Frequency:	
AP198M	50-133 L/min	55-140 psi	660 Hz	
AP360M	50-133 L/min	55-140 psi	387 Hz	
AP450M	50-133 L/min	55-140 psi	307 Hz	
APTD-Compressor 24v Dc (90mm O/D x 165mm L 50PSI)				

Kg 1.4

°C -30+90

IP 66

dB 125

INDUSTRIAL





X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Audio Indicators & Alerts category:

Click to view products by Moflash Signalling manufacturer:

Other Similar products are found below :

M2BJ-BH24E 6-4 68S1240-PA MBA-624 F/BC 40P-DR LF FDG111PLF F/NRMB 24 BLACK LF PF-35N29WQ PFD-27A35PQ PL-27A35PSQ PS-531Q AB2020B-2-LW1 EBPT-401 PB06SD12AP PB-1220PEQ S6109 SC2036ACP SC616N-2 SC628FW SC628MPG SC648D SCS045MD9DT3S AB2025B-LW50-R ESZ-25B-5-250B F/BC 35-DR LF FCM12PLF F/EB20P-DR LF F/HU110MP24V-IP67B LF AI-2835-TF-LW150-2-R AI-4228-TF-LW305-R FSMD8585JSLF FSS-26T F/SU 21-02 LF F/TCW 05 WITH LABEL LF F/UCW 03 WITH LABEL LF F/UCW 06 WITH LABEL LF PKM22EPPH40S1-B0 PKM35-4A0 PL-35N29WQ PLD-27A35PQ PS-552Q CM-5 M2BJ-BH24E-D REF-202 LSC628ANR 5-100 PAL-328 03-810.001 RTO-1R07-001 PL-21N31PQ PF-27A25PSQ