


HDAM-11-12.0-S-13-2



HDAF-11-08.0-S-13-2

(2.00 mm) .0787"

HDAM, HDAF SERIES

RUGGED ELEVATED HIGH-DENSITY ARRAY

HDAM Mates with:
HDAF
HDAF Mates with:
HDAM

SPECIFICATIONS

For complete specifications and recommended PCB layouts see www.samtec.com?HDAM or www.samtec.com?HDAF

Insulator Material:

Black LCP

Contact Material:

Copper Alloy

Plating:

Au or Sn over

50 μm (1.27 μm) Ni

Current Rating:

3.4 A per pin

(6 adjacent pins powered)

Operating Temp Range:

-55 °C to +125 °C

Contact Resistance: 19 mΩ

Working Voltage: 200 VAC

Mated Cycles: 100

RoHS Compliant: Yes

Lead-Free Solderable: Yes

RECOGNITIONS

For complete scope of recognitions see www.samtec.com/quality



FILE NO. E111594

HDAM	NO. OF PINS PER ROW	LEAD STYLE	PLATING OPTION	NO. OF ROWS	SOLDER TYPE	OTHER OPTION
	-11, -15, -23	Specify LEAD STYLE from chart	-S = 30 μm (0.76 μm) Gold on contact area, Matte Tin on tails and guide pins	-13	-2 = Lead-Free Tin Alloy 95.5% Sn/ 3.8% Ag/ 0.7% Cu Solder Charge	-P = Pick & Place Pad

(22.50) .886

(2.00) .0787

(1.20) .0472

1A

1M

No. of Pins Per Row x (2.00) .0787 + (16.06) .632

A


No. of Pins Per Row x (2.00) .0787 + (11.55) .455

(5.09) .200

LEAD STYLE	A
-12.0	(14.41) .567
-17.0	(19.41) .764

• Integrated guide posts

DIFFERENTIAL APPLICATIONS



ARRAY	PAIR COUNT*
11x13	44
15x13	60
23x13	92

*2:1 S:G Ratio

ALSO AVAILABLE (MOQ Required)

- Tin-Lead Solder Charge
 - Other platings
- Contact Samtec.

Note: HD Mezz is a trademark of Molex Incorporated

Note: Some lengths, styles and options are non-standard, non-returnable.

HDAF	NO. OF PINS PER ROW	LEAD STYLE	PLATING OPTION	NO. OF ROWS	SOLDER TYPE	OTHER OPTION
	-11, -15, -23	Specify LEAD STYLE from chart	-S = 30 μm (0.76 μm) Gold on contact area, Matte Tin on tails and weld tabs	-13	-2 = Lead-Free Tin Alloy 95.5% Sn/ 3.8% Ag/ 0.7% Cu Solder Charge	-P = Pick & Place Pad

(22.50) .886

(2.00) .0787

(1.20) .0472

1A

1M

No. of Pins Per Row x (2.00) .0787 + (11.55) .455

A

No. of Pins Per Row x (2.00) .0787 + (17.92) .706

LEAD STYLE	A
-08.0	(10.51) .414
-18.0	(20.51) .807

• Integrated guide posts

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Board to Board & Mezzanine Connectors](#) category:

Click to view products by [Samtec](#) manufacturer:

Other Similar products are found below :

[10135583-642402LF](#) [89885-310LF](#) [589158040000018](#) [6-1393048-0](#) [68683-613](#) [MDF7-12DP-2.54DSA](#) [MDF7-18P-2.54DSA\(01\)](#) [MDF7-20DP-2.54DSA](#) [MDF7-26D-2.54DSA\(55\)](#) [MDF7-3P-2.54DSA\(01\)](#) [MDF7B-3P-2.54DSA\(55\)](#) [MDF7C-11P-2.54DSA\(55\)](#) [MDF7C-18P-2.54DSA\(55\)](#) [MDF7C-5P-2.54DSA\(01\)](#) [MDF7P-5P-2.54DSA\(55\)](#) [75234-0516](#) [FCN-230C068-11](#) [FCN-268F012-G/BD](#) [FCN-268F036-G/BD](#) [FCN-268M012-G/0D](#) [FCN-268M024-G/1D](#) [FCN-360C008-C](#) [FCN-360C040-C](#) [FCN-723J004/1](#) [MIS-048-01-F-D-DP-K](#) [832-10-034-10-001000](#) [93696-325LF](#) [11828-1FA](#) [AXK630345P](#) [18097-0013](#) [ICA-328STT](#) [2007042-2](#) [304400-2](#) [FCN-214Q030-G/0](#) [FCN-215Q040-G/0](#) [FCN-230C068-ESA](#) [FCN-234P048-G/0](#) [FCN-235D050-G/C](#) [FCN-360A3](#) [FCN-360C040-B](#) [210-93-314-41-105000](#) [2-22603-0](#) [379-064-521-202](#) [MDF7-12P-2.54DSA\(01\)](#) [MDF7-16P-2.54DS\(56\)](#) [MDF7-40DP-2.54DSA\(55\)](#) [MDF7-8P-2.54DSA\(55\)](#) [MDF7B-16P-2.54DSA\(55\)](#) [AXG720047](#) [5031084030](#)