



## SOT-23 Plastic-Encapsulate Transistors


### BCW66 TRANSISTOR (NPN)

#### FEATURES

Complementary to BCW68

BCW66 is subdivided into three groups F,G and H according to DC current gain

#### SOT-23



#### MAXIMUM RATINGS ( $T_a=25^\circ\text{C}$ unless otherwise noted)

Symbol	Parameter	Value	Unit
$V_{\text{CBO}}$	Collector-Base Voltage	75	V
$V_{\text{CEO}}$	Collector-Emitter Voltage	45	V
$V_{\text{EBO}}$	Emitter-Base Voltage	5	V
$I_C$	Collector Current	800	mA
$P_C$	Collector Power Dissipation	200	mW
$R_{\text{QJA}}$	Thermal Resistance From Junction To Ambient	625	$^\circ\text{C}/\text{W}$
$T_j$	Junction Temperature	150	$^\circ\text{C}$
$T_{\text{stg}}$	Storage Temperature	-55~+150	$^\circ\text{C}$








#### ELECTRICAL CHARACTERISTICS ( $T_a=25^\circ\text{C}$ unless otherwise specified)

Parameter	Symbol	Test conditions	Min	Typ	Max	Unit
Collector-base breakdown voltage	$V_{(\text{BR})\text{CBO}}$	$I_C= 10 \mu\text{A}, I_E=0$	75			V
Collector-emitter breakdown voltage	$V_{(\text{BR})\text{CEO}}$	$I_C= 10\text{mA}, I_B=0$	45			V
Emitter-base breakdown voltage	$V_{(\text{BR})\text{EBO}}$	$I_E=10 \mu\text{A}, I_C=0$	5			V
Collector cut-off current	$I_{\text{CBO}}$	$V_{\text{CB}}=45 \text{V}, I_E=0$			0.02	$\mu\text{A}$
Collector cut-off current	$I_{\text{EBO}}$	$V_{\text{EB}}=4 \text{V}, I_C=0$			0.02	$\mu\text{A}$
DC current gain	$h_{\text{FE}1}$	$V_{\text{CE}}=10\text{V}, I_C=0.1\text{mA}$	<b>F</b> 35 <b>G</b> 50 <b>H</b> 80			
	$h_{\text{FE}2}$	$V_{\text{CE}}=1\text{V}, I_C= 10\text{mA}$	<b>F</b> 75 <b>G</b> 110 <b>H</b> 180			
	$h_{\text{FE}3}$	$V_{\text{CE}}=1\text{V}, I_C=100\text{mA}$	<b>F</b> 100 <b>G</b> 160 <b>H</b> 250		250 400 630	
	$h_{\text{FE}4}$	$V_{\text{CE}}=2\text{V}, I_C=500\text{mA}$	<b>F</b> 35 <b>G</b> 60 <b>H</b> 100			
Collector-emitter saturation voltage	$V_{\text{CE}(\text{sat})}$	$I_C=100\text{mA}, I_B=10\text{mA}$			0.3	V
		$I_C=500\text{mA}, I_B=50\text{mA}$			0.7	V
Base-emitter saturation voltage	$V_{\text{BE}(\text{sat})}$	$I_C=500\text{mA}, I_B=50\text{mA}$			2	V
Transition frequency	$f_T$	$V_{\text{CE}}=10\text{V}, I_C=20\text{mA}, f=100\text{MHz}$	100			MHz
Output capacitance	$C_{\text{ob}}$	$V_{\text{CB}}=10\text{V}, I_E=0, f=1\text{MHz}$			12	pF
Input capacitance	$C_{\text{ib}}$	$V_{\text{EB}}=0.5\text{V}, I_E=0, f=1\text{MHz}$			80	pF
Noise figure	NF	$V_{\text{CE}}=5\text{V}, I_C=0.2\text{mA}, f=1\text{KHz}, R_s=1\text{K}\Omega, \text{BW}=200\text{Hz}$			10	dB




#### MARKING

Rank	F	G	H	
Range	100-250	160-400	250-630	
Marking	EF	EG	EH	

## Typical Characteristics




## SOT-23 Package Outline Dimensions



Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min	Max	Min	Max
A	0.900	1.150	0.035	0.045
A1	0.000	0.100	0.000	0.004
A2	0.900	1.050	0.035	0.041
b	0.300	0.500	0.012	0.020
c	0.080	0.150	0.003	0.006
D	2.800	3.000	0.110	0.118
E	1.200	1.400	0.047	0.055
E1	2.250	2.550	0.089	0.100
e	0.950 TYP		0.037 TYP	
e1	1.800	2.000	0.071	0.079
L	0.550 REF		0.022 REF	
L1	0.300	0.500	0.012	0.020
θ	0°	8°	0°	6°

## SOT-23 Suggested Pad Layout




Note:  
1. Controlling dimension: in millimeters.  
2. General tolerance:  $\pm 0.05$ mm.  
3. The pad layout is for reference purposes only.

### NOTICE

JCET reserve the right to make modifications, enhancements, improvements, corrections or other changes without further notice to any product herein. JCET does not assume any liability arising out of the application or use of any product described herein.

## SOT-23 Tape and Reel

### SOT-23 Embossed Carrier Tape




#### Packaging Description:


SOT-23 parts are shipped in tape. The carrier tape is made from a dissipative (carbon filled) polycarbonate resin. The cover tape is a multilayer film (Heat Activated Adhesive in nature) primarily composed of polyester film, adhesive layer, sealant, and anti-static sprayed agent. These reeled parts in standard option are shipped with 3,000 units per 7" or 17.8cm diameter reel. The reels are clear in color and is made of polystyrene plastic (anti-static coated).

Dimensions are in millimeter										
Pkg type	A	B	C	d	E	F	P0	P	P1	W
SOT-23	3.15	2.77	1.22	Ø1.50	1.75	3.50	4.00	4.00	2.00	8.00
(Tolerance)	+/-0.1	+/-0.1	+/-0.1	+/-0.1	+/-0.1	+/-0.1	+/-0.1	+/-0.1	+/-0.1	+0.3/-0.1

### SOT-23 Tape Leader and Trailer



### SOT-23 Reel



Dimensions are in millimeter								
Reel Option	D	D1	D2	G	H	I	W1	W2
7"Dia	Ø178.00	54.40	13.00	R78.00	R25.60	R6.50	9.50	12.30
Tolerance	+/-2	+/-1	+/-1	+/-1	+/-1	+/-1	+/-1	+/-1

REEL	Reel Size	Box	Box Size(mm)	Carton	Carton Size(mm)	G.W.(kg)
3000 pcs	7 inch	45,000 pcs	203×203×195	180,000 pcs	438×438×220	

# X-ON Electronics

Largest Supplier of Electrical and Electronic Components

***Click to view similar products for Bipolar Transistors - BJT category:***

***Click to view products by Changjiang manufacturer:***

Other Similar products are found below :

[619691C](#) [MCH4017-TL-H](#) [MJ15024/WS](#) [MJ15025/WS](#) [BC546/116](#) [BC556/FSC](#) [BC557/116](#) [BSW67A](#) [HN7G01FU-A\(T5L,F,T\)](#)  
[NJVMJD148T4G](#) [NSVMMBT6520LT1G](#) [NTE187A](#) [NTE195A](#) [NTE2302](#) [NTE2330](#) [NTE2353](#) [NTE316](#) [IMX9T110](#) [NTE63](#) [NTE65](#)  
[C4460](#) [SBC846BLT3G](#) [2SA1419T-TD-H](#) [2SA1721-O\(TE85L,F\)](#) [2SA1727TLP](#) [2SA2126-E](#) [2SB1202T-TL-E](#) [2SB1204S-TL-E](#) [2SC5488A-TL-H](#)  
[2SD2150T100R](#) [SP000011176](#) [FMC5AT148](#) [2N2369ADCSM](#) [2SB1202S-TL-E](#) [2SC2412KT146S](#) [2SC4618TLN](#) [2SC5490A-TL-H](#)  
[2SD1816S-TL-E](#) [2SD1816T-TL-E](#) [CMXT2207 TR](#) [CPH6501-TL-E](#) [MCH4021-TL-E](#) [BC557B](#) [TTC012\(Q\)](#) [BULD128DT4](#) [JANTX2N3810](#)  
[Jantx2N5416](#) [US6T6TR](#) [KSF350](#) [068071B](#)