




2SD1691

NPN SILICON TRANSISTOR

LOW COLLECTOR
SATURATION VOLTAGE
LARGE CURRENT

■ FEATURES

- *High Power Dissipation
- *Complementary to 2SB1151



■ ORDERING INFORMATION

Ordering Number		Package	Pin Assignment			Packing
Lead Free Plating	Halogen Free		1	2	3	
2SD1691L-x-TA3-T	2SD1691G-x-TA3-T	TO-220	B	C	E	Tube
2SD1691L-x-TF1-T	2SD1691G-x-TF1-T	TO-220F1	B	C	E	Tube
2SD1691L-x-TM3-T	2SD1691G-x-TM3-T	TO-251	B	C	E	Tube
2SD1691L-x-TN3-T	2SD1691G-x-TN3-T	TO-252	B	C	E	Tape Reel
2SD1691L-x-T60-K	2SD1691G-x-T60-K	TO-126	E	C	B	Bulk
2SD1691L-x-T6C-K	2SD1691G-x-T6C-K	TO-126C	E	C	B	Bulk

Note: Pin Assignment: B: Base C: Collector E: Emitter

<p>2SD1691L-x-TA3-T</p>	<p>(1) K: Bulk, T: Tube, R: Tape Reel (2) TA3: TO-220, TF1: TO-220F1, TN3: TO-252 TM3: TO-251, T60: TO-126, T6C: TO-126C (3) x: refer to Classification of h_{FE2} (4) L: Lead Free, G: Halogen Free and Lead Free</p>
-------------------------	---

■ MARKING

TO-220 / TO-220F1 / TO-251 / TO-252	TO-126 / TO-126C

■ ABSOLUTE MAXIMUM RATINGS ($T_A=25^\circ\text{C}$, unless otherwise specified)

PARAMETER		SYMBOL	RATING	UNIT
Collector-Base Voltage		V_{CBO}	60	V
Collector-Emitter Voltage		V_{CEO}	60	V
Emitter-Base Voltage		V_{EBO}	7	V
Collector Current	DC	I_C	5	A
	Pulse ($PW \leq 10\text{ms}$, Duty Cycle $\leq 50\%$)	I_{CP}	8	
Base Current		I_B	1	A
Collector Power Dissipation ($T_c=25^\circ\text{C}$)	TO-220F1	P_C	23	W
	TO-220		54	
	TO-251/TO-252		36	
	TO-126/ TO-126C		20	
Junction Temperature		T_J	150	$^\circ\text{C}$
Storage Temperature Range		T_{STG}	-55 ~ +150	$^\circ\text{C}$

Note: Absolute maximum ratings are those values beyond which the device could be permanently damaged. Absolute maximum ratings are stress ratings only and functional device operation is not implied.

■ ELECTRICAL CHARACTERISTICS ($T_A=25^\circ\text{C}$, unless otherwise specified)







CHARACTERISTIC		SYMBOL	TEST CONDITIONS	MIN	TYP	MAX	UNIT
Collector Cut-off Current		I_{CBO}	$V_{CB}=50\text{V}, I_E=0$			10	μA
Emitter Cut-off Current		I_{EBO}	$V_{EB}=7\text{V}, I_C=0$			10	μA
DC Current Gain		h_{FE1}	$V_{CE}=1\text{V}, I_C=0.1\text{A}$	60			
		h_{FE2}	$V_{CE}=1\text{V}, I_C=2\text{A}$	160		400	
		h_{FE3}	$V_{CE}=2\text{V}, I_C=5\text{A}$	50			
Collector-Emitter Saturation Voltage		$V_{CE(SAT)}$ (Note)	$I_C=2\text{A}, I_B=0.2\text{A}$		0.1	0.3	V
Base-Emitter Saturation Voltage		$V_{BE(SAT)}$ (Note)	$I_C=2\text{A}, I_B=0.2\text{A}$		0.9	1.2	V
Switching Time	Turn On Time	T_{ON}			0.2	1	μs
	Storage Time	T_{STG}			1.1	2.5	
	Fall Time	T_F			0.2	1	

Note: Pulse test: $P_W \leq 50\mu\text{s}$, Duty Cycle $\leq 2\%$ Pulse

■ CLASSIFICATION OF h_{FE2}

RANK	O	Y
RANGE	160-320	200-400

TYPICAL CHARACTERISTICS



UTC assumes no responsibility for equipment failures that result from using products at values that exceed, even momentarily, rated values (such as maximum ratings, operating condition ranges, or other parameters) listed in products specifications of any and all UTC products described or contained herein. UTC products are not designed for use in life support appliances, devices or systems where malfunction of these products can be reasonably expected to result in personal injury. Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner. The information presented in this document does not form part of any quotation or contract, is believed to be accurate and reliable and may be changed without notice.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Bipolar Transistors - BJT category](#):

Click to view products by [Unisonic manufacturer](#):

Other Similar products are found below :

[619691C](#) [MCH4017-TL-H](#) [MJ15024/WS](#) [MJ15025/WS](#) [BC546/116](#) [BC556/FSC](#) [BC557/116](#) [BSW67A](#) [HN7G01FU-A\(T5L,F,T](#)
[NJVMJD148T4G](#) [NSVMMBT6520LT1G](#) [NTE187A](#) [NTE195A](#) [NTE2302](#) [NTE2330](#) [NTE2353](#) [NTE316](#) [IMX9T110](#) [NTE63](#) [NTE65](#)
[C4460](#) [SBC846BLT3G](#) [2SA1419T-TD-H](#) [2SA1721-O\(TE85L,F\)](#) [2SA1727TLP](#) [2SA2126-E](#) [2SB1202T-TL-E](#) [2SB1204S-TL-E](#) [2SC5488A-](#)
[TL-H](#) [2SD2150T100R](#) [SP000011176](#) [FMC5AT148](#) [2N2369ADCSM](#) [2SB1202S-TL-E](#) [2SC2412KT146S](#) [2SC4618TLN](#) [2SC5490A-TL-H](#)
[2SD1816S-TL-E](#) [2SD1816T-TL-E](#) [CMXT2207 TR](#) [CPH6501-TL-E](#) [MCH4021-TL-E](#) [BC557B](#) [TTC012\(Q\)](#) [BULD128DT4](#) [JANTX2N3810](#)
[Jantx2N5416](#) [US6T6TR](#) [KSF350](#) [068071B](#)