



**SPECIFICATION**

**Poles: 2-24**  
**Voltage rating: AC, DC 250V**  
**Current rating: AC, DC, 7A**  
**Withstand voltage: 1500V AC/min.**  
**Insulation resistance: 1000M Ω/min.**  
**Temperature range: -25℃ ~ +85℃**  
**Applicable PC board thickness: 0.031" ~ 0.063" (0.8 ~ 1.6mm)**  
**Contact resistance: Initial value/10mΩ max.**  
**After environmental testing/20mΩ max.**

**Material: Nylon66 UL94V-2**

**TOLERANCE TABLE**

.0	±0.20
.00	±0.10
.000	±0.05

<b>APPROVED:</b>	<b>DATE:</b>	<b>深圳市灿科盟实业有限公司</b> <b>CKimtW CHANKLEMENT INDUSTRYCO., LTD</b>
<b>CHECKED:</b>	<b>DATE:</b>	
<b>DRAWN:</b>	<b>DATE:</b>	<b>CLIENT P/N /</b> <b>5557HP-2*XP</b>
<b>LXF</b>	<b>2008-04-07</b>	
<b>UNIT</b>	<b>mm</b>	<b>SCALE</b> free
<b>FILE NO.</b>	<b>CKimtW-5557-0007</b>	
	<b>REV.</b>	<b>A</b>

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Headers & Wire Housings](#) category:*

*Click to view products by [Cankemeng](#) manufacturer:*

Other Similar products are found below :

[95000-104TRLF](#) [10135584-644402LF](#) [DF62W-EP2022PCA](#) [95000-106TRLF](#) [DF62W-2022SCA](#) [DF62W-EP2022PC](#) [2203348](#) [DF62W-2022SC](#) [1084018](#) [1029039](#) [1084017](#) [802-10-012-10-002000](#) [1112640](#) [1112639](#) [000-34000](#) [0008550134](#) [0009482033](#) [0009507031](#) [57102-S06-03LF](#) [57202-S52-04LF](#) [PCN6-15S-2.5E](#) [0039019024](#) [58102-G61-06LF](#) [582553-1](#) [0009485154](#) [0009508121](#) [0022285053](#) [0050291907](#) [018731A](#) [LY20-4P-DT1-P1E-BR](#) [02.125.8002.8](#) [60101931](#) [60598-1 \(Cut Strip\)](#) [M1625-3R/100](#) [61062-3](#) [61082-181009](#) [636-1427](#) [638009-1](#) [641938-9](#) [641991-4](#) [644168-1](#) [647662-1](#) [65039-019ELF](#) [65781-018](#) [65781-047](#) [65817-002LF](#) [65817-015LF](#) [65863-015LF](#) [66207-023LF](#) [67016-026LF](#)