



PCB Layout

SPECIFICATIONS

1. Rating : DC 30V 1.0A
2. Contact Resistance: $\leq 50m\Omega$
3. Insulation Resistance: $\geq 1000m\Omega$ Min DC250V
4. Operating Temperature Range: $-40^{\circ}C + 85^{\circ}C$

PART NO.	
U-G-04WD-W-01	U-G-04WD-W-02
Housing & Black	Housing & White

③	Shell	—	1	SPCC	NI Plated	—
②	Contact	—	4	Copper Alloy	Ag Plated	—
①	Housing	—	1	Nylon	White/Black	—
ITEM	PART NAME	TER'NO.	QTY.	MATERIAL	FINISHING	REMARK

APPROVALS		DATE
DRAWN	JKUN.LU	2014/9/29
TITLE:		ELECTRONICS CO.,LTD
CHECKED		USB CONNECTOR

ECN NO.	REV.	DATE.	DESCRIPTION.	CHANGE.	CHECK.	APPRO.
	A		NEW			
TOLERANCES ARE		30~12.5 ±0.30	ANGLE	±2'	DRAWING NO.	
		10~30 ±0.25	UNIT: mm		SCALE: 1:1	
		5~10 ±0.20	UNIT: mm		PROJ.:	
		~5 ±0.15	UNIT: mm		SHEET 1 OF 1	

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [USB Connectors](#) category:

Click to view products by [HRO parts manufacturer](#):

Other Similar products are found below :

[10033527-N3112MLF](#) [17-210561](#) [GMCB05B11124H1EU](#) [17-200931](#) [65-647-8-BK-BU](#) [690-010-295-484](#) [73725-1191BLF](#) [950](#) [E8144-B01021-L](#) [A-USB A-LP-SMT-C](#) [A-USB B-TOP-C](#) [MUSBA511N5](#) [MUSBB15131](#) [MUSBC111M5](#) [MUSBD11135](#) [217450-1](#) [CA 6 W LD](#) [896-30-004-00-000000](#) [KUSBVX-BS1N-W30](#) [KUSBX-AP-KIT-SCBLK](#) [KUSBX-AS2N-W](#) [KUSBX-SMT2AP1S-W](#) [KUSBX-SMTBS1NBTR](#) [30-498-6](#) [SK-60A-2](#) [17-200261](#) [17-210051](#) [1734082-1](#) [FK-37-32SL](#) [30-1574](#) [30-470](#) [30-489](#) [30-572-3](#) [30-9503](#) [M9177/2-1](#) [MAB 5 S](#) [MIKROE-1451](#) [33UBBR-04SW11R](#) [USBFTV2PEM2G](#) [USBFTVC6ZN](#) [USBFTVSCCG](#) [KUSBX-AS2N-W30](#) [KUSBX-SLAS1N-W](#) [KUSBX-SLAS1N-W30](#) [1-1734084-2](#) [E8110-001-01](#) [MUSBC11135](#) [33UBAR-04SW11](#) [USBF21ZNSCC](#) [USBBFTV6ZC](#)