

## VD 型片式铝电解电容

### VD Series Chip Type Aluminum Electrolytic Capacitors

#### 特点 Features

- 低阻抗。Low impedance.
- 适用于再流焊。Reflow soldering is available.
- 适用于高密度表面组装。available for high density surface mounting.
- 工作温度范围宽（-55℃ ~ +105℃）Operating over wide temperature range.
- ROHS 指令已对应完毕。Adapted to the ROHS directive.

#### 主要技术性能 Specifications

| 项目 Items  | 特性 Characteristics   |  |            |            |            |            |            |
|---|--|--|------------|------------|------------|------------|------------|
| 工作温度范围<br>Operating Temperature Range                               | -55℃ ~ +105℃   |  |            |            |            |            |            |
| 额定电压范围<br>Rated Voltage Range                                       | 6.3V ~ 50V   |  |            |            |            |            |            |
| 标称容量范围<br>Nominal Capacitance Range                                 | 1 ~ 1000μF   |  |            |            |            |            |            |
| 标称容量允许偏差<br>Nominal Capacitance Tolerance                           | ±20% (20℃, 120Hz)  |  |            |            |            |            |            |
| 漏电流<br>Leakage Current  | I ≤ 0.01C <sub>R</sub> V <sub>R</sub> or 3(μA), 取较大者 (2 分钟) C <sub>R</sub> : 标称容量 (μF) U <sub>R</sub> : 额定电压 (V)<br>I ≤ 0.01C <sub>R</sub> V <sub>R</sub> or 3(μA) Whichever is greater (at 20℃, after 2 minutes)<br>C <sub>R</sub> : Nominal Capacitance (μF) U <sub>R</sub> : Rated voltages (V) |  |            |            |            |            |            |
| 损耗角正切 (tgδ)<br>Dissipation Factor (Max)<br>20℃, 120Hz               | U <sub>R</sub> (V)   | 6.3  | 10         | 16         | 25         | 35         | 50         |
|   | tgδ  | 0.26(0.28)   | 0.20(0.24) | 0.16(0.20) | 0.14(0.16) | 0.12(0.14) | 0.12(0.14) |
| 注: ( ) 为 Φ8 以上产品。   |  |  |            |            |            |            |            |
| 耐久性<br>Load Life  | +105℃施加额定电压 5000 小时后 (ΦD=4, 5 和 6.3 为 2000 小时), 电容器应满足以下要求:<br>After 5000 hours (2000 hours for φD = 4, 5 and 6.3) . application of rated voltage at 105℃, the capacitor shall meet the following requirement:   |  |            |            |            |            |            |
|   | 容量变化率<br>Capacitance Change  | ±30%初始值以内<br>Within ±30% of the initial value                    |            |            |            |            |            |
|   | 损耗角正切<br>Dissipation Factor  | ≤ 300%初始规定值<br>Not more than 300% of the initial specified value |            |            |            |            |            |
|   | 漏电流<br>Leakage Current   | ≤ 初始规定值<br>Not more than the initial specified value             |            |            |            |            |            |
| 高温贮存<br>Shelf Life  | +105℃贮存 1000 小时后, 电容器应满足以上耐久性要求<br>After storage for 1000 hours at +105℃, the capacitors shall meet the requirement of load life above   |  |            |            |            |            |            |
| 低温特性<br>Low Temperature Stability<br>阻抗比<br>Impedance Ratio (120Hz) | U <sub>R</sub> (V)   | 6.3  | 10         | 16         | 25         | 35         | 50         |
|   | Z(-25℃)/Z(+20℃)  | 3  | 2          | 2          | 2          | 2          | 2          |
|   | Z(-40℃)/Z(+20℃)  | 5  | 4          | 4          | 3          | 3          | 3          |
| 耐焊接热<br>Resistance to Soldering Heat                                | 在 250℃的条件下, 电容器在热板上保持 30 秒, 然后从热板上取出电容器, 让其在室温下恢复, 电容器应满足以下要求: The capacitors shall be kept on the hot plate maintained at 250℃ for 30 seconds. After removing from the hot plate and restored at room temperature, they meet the following requirement.   |  |            |            |            |            |            |
|   | 容量变化率<br>Capacitance Change  | ±10%初始值以内<br>Within ±10% of the initial value                    |            |            |            |            |            |
|   | 损耗角正切 (tgδ)<br>Dissipation Factor  | ≤ 初始规定值<br>Not more than the initial specified value             |            |            |            |            |            |
|   | 漏电流<br>Leakage Current   | ≤ 初始规定值<br>Not more than the initial specified value             |            |            |            |            |            |



## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Aluminium Electrolytic Capacitors - SMD category](#):*

*Click to view products by [Huawei manufacturer](#):*

Other Similar products are found below :

[GA0402A270FXBAC31G](#) [RVB-50V330MG10UQ-R](#) [RVJ-50V101MH10U-R](#) [RVZ-35V151MH10U-R2](#) [RC0J226M04005VR](#)  
[RC0J476M05005VR](#) [RC1A227M08010VR](#) [RC1C226M05005VR](#) [RC1C476M6L005VR](#) [RC1E107M6L07KVR](#) [RC1E336M6L005VR](#)  
[RC1H106M6L005VR](#) [RC1H475M05005VR](#) [RC1V227M10010VR](#) [RC1V476M6L006VR](#) [50SEV1M4X5.5](#) [TYEH1A336E55MTR](#)  
[TYEH1H106F55MTR](#) [TYEH1V106E55MTR](#) [35SEV47M6.3X8](#) [35SGV220M10X10.5](#) [VES2R2M1HTR-0405](#) [VZH102M1ATR-1010](#)  
[50SEV10M6.3X5.5](#) [50SGV1M4X6.1](#) [SC1C476M05005VR](#) [SC1E107M0806BVR](#) [SC1E227M08010VR](#) [SC1H106M05005VR](#)  
[SC1H106M6L005VR](#) [SC1H227M10010VR](#) [SC1H335M04005VR](#) [CE4.7/50-SMD](#) [VEJ4R7M1VTR-0406](#) [VZH331M1ETR-0810](#)  
[VES101M1CTR-0605](#) [TYEH1H475E55MTR](#) [6.3SEV22M4X5.5](#) [6.3SEV47M4X5.5](#) [EEEFK1H151GP](#) [EEEFK1A681GP](#) [EEE0GA471XP](#)  
[EEEFK1V151GP](#) [RC1V107M6L07KVR](#) [VZH101M1VTR-0810](#) [VE010M1HTR-0405](#) [GYA1V151MCQ1GS](#) [EEH-ZC1J680P](#) [EEH-](#)  
[ZK1V181P](#) [GYA1V271MCQ1GS](#)