



Dimension antitheses list		
ITEM	PC	PA
Standard	6.25	6.25
	6.25	15.00

### Ordering Information

1625-12 XX C N XX S XXX 0 01

- 25=Hz,5mm
- Plastic High
- No. of Pins
- Per Row
- 01~40P
- Insulator Material
- Contact Picking
- G00.8U" Gold
- G1:1U" Gold
- A=PB1
- B=PA66
- G2:1.5U" Gold
- C=PA61
- D=PA46
- G4:3U" Gold
- G5:5U" Gold
- E=PA9T
- F=LCP
- S0:Gold Flash/Tin
- SN:tin
- Pin Length
- 116=11.6mm
- Packing
- code stream
- 01~99
- A=FRY
- T=tube
- R=tube+Cap
- M=Reel+Myfor

深圳市华宇创精密电子有限公司



SCALE:1:1 SIZE: A4		UNIT: mm [inch]	
X.X ±2 X.X' ±0.5		X.XX ±0.15	
X.X ±0.30		X.XX ±0.25	
TOLERANCE:		X.X' ±2 X.X' ±0.5	
DRAWN BY: 陈一鸣	DATE: 2014-02-23	CHECKED BY: 马跃	DATE: 2014-02-23
APPROVED BY:	DATE:	APPROVED BY:	DATE:
PART NAME: 2.54X2.5PH 2XNP 180 ° L15.0		PART NO. 1625-12XXCNXXSXXX001	
MOLD NO.		DRAW NO. HYC-1812011124	
SHEET NO. 1 OF 1			

Dimen Sions List	Contacts		Dimensions	
	Per row	A	B	Per row
1	21	53.34	50.80	50.80
2	22	55.88	53.34	53.34
3	23	58.42	55.88	55.88
4	24	60.96	58.42	58.42
5	25	63.50	60.96	60.96
6	26	66.04	63.50	63.50
7	27	68.58	66.04	66.04
8	28	71.12	68.58	68.58
9	29	73.66	71.12	71.12
10	30	76.20	73.66	73.66
11	31	78.74	76.20	76.20
12	32	81.28	78.74	78.74
13	33	83.82	81.28	81.28
14	34	86.36	83.82	83.82
15	35	88.90	86.36	86.36
16	36	91.44	88.90	88.90
17	37	93.98	91.44	91.44
18	38	96.52	93.98	93.98
19	39	99.06	96.52	96.52
20	40	101.6	99.06	99.06

**SPECIFICATIONS**  
 Rated Current:3.0AMP  
 Contact Resistance:20mΩ Max  
 Withstand Voltage:100V AC/DC  
 Insulation Resistance:1000MΩ Min  
 Operation Temperature:-40°C to +105°C  
 Contact Material:Brass  
 Contact Plating:Au Over Ni  
 Insulator Material:Polyester(UL94V-0)  
 Standard: PA6T  
 Max.Processing Temp: 230°C for 30~60 seconds  
 (260°C for 10 seconds)

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Headers & Wire Housings](#) category:*

*Click to view products by [HOAUC](#) manufacturer:*

Other Similar products are found below :

[95000-104TRLF](#) [10135584-644402LF](#) [DF62W-EP2022PCA](#) [95000-106TRLF](#) [DF62W-2022SCA](#) [DF62W-EP2022PC](#) [2203348](#) [DF62W-2022SC](#) [1084018](#) [1029039](#) [1084017](#) [802-10-012-10-002000](#) [1112640](#) [1112639](#) [891-007-9SS-BST1T](#) [000-34000](#) [0008550134](#) [0009482033](#) [0009507031](#) [57102-F02-18ULF](#) [57102-S06-03LF](#) [57202-S52-04LF](#) [PCN6-15S-2.5E](#) [0039019024](#) [58102-G61-06LF](#) [582553-1](#) [0009485154](#) [0009508121](#) [0022285053](#) [0050291907](#) [018731A](#) [LY20-4P-DT1-P1E-BR](#) [02.125.8002.8](#) [60101931](#) [60598-1 \(Cut Strip\)](#) [M1625-3R/100](#) [61062-3](#) [61082-181009](#) [CSU011177004](#) [636-1427](#) [638009-1](#) [641938-9](#) [641991-4](#) [644168-1](#) [644827-2](#) [647662-1](#) [65039-019ELF](#) [65692-001LF](#) [65781-018](#) [65781-047](#)