

Ordering Information

26 85 Y-1 XX X W XX S N X 01

- 85=H:8.5mm
- Plastic high
- No.of Pins Per Row 01~40P
- W=with Post
- Material
- Option
- Insulator
- Post
- Contact Plating
- 00:0.8U" Gold
- 01:1U" Gold
- G2:1.5U" Gold
- G3:2U" Gold
- G4:3U" Gold
- G5:5U" Gold
- G6:10U" Gold
- G7:15U" Gold
- S0:Gold Flash/Tin
- SN:Tin
- F=LCP
- E=PA9T
- D=PA46
- C=PA6T
- B=PA66
- A=BT
- N=w/o post
- Post
- 0=PC Bag
- Packing code stream 01~99
- M=Reel+Mylar
- R=Reel+Cap
- P=Tube+Cap
- A=Troy
- T=Tube
- X.X ±0.30
- X.XX ±0.25
- X.X ±2
- X.X' ±0.5'




深圳市华字创精密电子有限公司

SCALE:1:1 SIZE: A4		UNIT: mm [inch]	
TOLERANCE: X.X ±0.30 X.XX ±0.25 X.X' ±2 X.X' ±0.5'		DRAWN BY: 陈一鸣	
CHECKED BY: 马跃		DATE: 2014-02-23	
APPROVED BY:		DATE: 2014-02-23	
SHEET NO. 1 OF 1		DRAW NO.: HYC-1812011106	
PART NAME: 2.54X8.5FH 1XNP1N 180° 弯型		PART NO.: 2685Y-1XXXMXSXSX01	

SPECIFICATIONS
 Rated Current:3.0AMP
 Contact Resistance:20mΩ Max
 Withstand Voltage:100V AC/DC
 Insulation Resistance:1000MΩ Min
 Operation Temperature:-40°C to +105°C
 Contact Material:Brass
 Contact Plating:Au or Sn Over Ni
 Insulator Material:Polyester(UL94V-0)
 Standard: PA6T
 Max.Processing Temp: 230°C for 30-60 seconds
 (260°C for 10 seconds)

Dimensions List

Contacts	A	21	53.74	50.80
Contacts	B	0	53.74	50.80
Dimensions	A	2.94	53.74	50.80
Dimensions	B	2.94	53.74	50.80
		22	56.28	53.34
		23	58.82	55.88
		24	61.36	58.42
		25	63.90	60.96
		26	66.44	63.50
		27	68.98	66.04
		28	71.52	68.58
		29	74.06	71.12
		30	76.60	73.66
		31	79.14	76.20
		32	81.68	78.74
		33	84.22	81.28
		34	86.76	83.82
		35	89.30	86.36
		36	91.84	88.90
		37	94.38	91.44
		38	96.92	93.98
		39	99.46	96.52
		40	102.00	99.06
		41	104.54	101.60
		42	107.08	104.14
		43	109.62	106.68
		44	112.16	109.22
		45	114.70	111.76
		46	117.24	114.30
		47	119.78	116.84
		48	122.32	119.38
		49	124.86	121.92
		50	127.40	124.46
		51	129.94	127.00
		52	132.48	129.54
		53	135.02	132.08
		54	137.56	134.62
		55	140.10	137.16
		56	142.64	139.70
		57	145.18	142.24
		58	147.72	144.78
		59	150.26	147.32
		60	152.80	149.86
		61	155.34	152.40
		62	157.88	154.94
		63	160.42	157.48
		64	162.96	160.02
		65	165.50	162.56
		66	168.04	165.10
		67	170.58	167.64
		68	173.12	170.18
		69	175.66	172.72
		70	178.20	175.26
		71	180.74	177.80
		72	183.28	180.34
		73	185.82	182.88
		74	188.36	185.42
		75	190.90	187.96
		76	193.44	190.50
		77	195.98	193.04
		78	198.52	195.58
		79	201.06	198.12
		80	203.60	200.66
		81	206.14	203.20
		82	208.68	205.74
		83	211.22	208.28
		84	213.76	210.82
		85	216.30	213.36
		86	218.84	215.90
		87	221.38	218.44
		88	223.92	220.98
		89	226.46	223.52
		90	229.00	226.06
		91	231.54	228.60
		92	234.08	231.14
		93	236.62	233.68
		94	239.16	236.22
		95	241.70	238.76
		96	244.24	241.30
		97	246.78	243.84
		98	249.32	246.38
		99	251.86	248.92
		100	254.40	251.46



X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Headers & Wire Housings](#) category:

Click to view products by [HOAUC](#) manufacturer:

Other Similar products are found below :

[95000-104TRLF](#) [10135584-644402LF](#) [DF62W-EP2022PCA](#) [95000-106TRLF](#) [DF62W-2022SCA](#) [DF62W-EP2022PC](#) [2203348](#) [DF62W-2022SC](#) [1084018](#) [1029039](#) [1084017](#) [802-10-012-10-002000](#) [1112640](#) [1112639](#) [891-007-9SS-BST1T](#) [000-34000](#) [0008550134](#) [0009482033](#) [0009507031](#) [57102-F02-18ULF](#) [57102-S06-03LF](#) [57202-S52-04LF](#) [PCN6-15S-2.5E](#) [0039019024](#) [58102-G61-06LF](#) [582553-1](#) [0009485154](#) [0009508121](#) [0022285053](#) [0050291907](#) [018731A](#) [LY20-4P-DT1-P1E-BR](#) [02.125.8002.8](#) [60101931](#) [60598-1 \(Cut Strip\)](#) [M1625-3R/100](#) [61062-3](#) [61082-181009](#) [CSU011177004](#) [636-1427](#) [638009-1](#) [641938-9](#) [641991-4](#) [644168-1](#) [644827-2](#) [647662-1](#) [65039-019ELF](#) [65692-001LF](#) [65781-018](#) [65781-047](#)