



### Ordering Information

26 85 Y-1 XX X W XX S N X 01

- 85=H:8.5mm Plastic high
- 01~40P Per Row
- No.of Pins Insulator Material
- W=with Post
- Post
- Contact Plating
- 00:0.8U" Gold
- 01:1U" Gold
- G2:1.5U" Gold
- G3:2U" Gold
- G4:3U" Gold
- G5:5U" Gold
- G6:10U" Gold
- G7:15U" Gold
- S0:Gold Flash/Tin
- SN:Tin
- F=LCP
- E=PA9T
- D=PA46
- C=PA6T
- B=PA66
- A=BT
- Option
- Material
- M=Reel+Mylar
- R=Reel+Cap
- P=Tube+Cap
- T=Tube
- A=Troy
- 0=PE Bag
- Packing code stream 01~99



深圳市华字创精密电子有限公司

SCALE:1:1 SIZE: A4		UNIT: mm [inch]	
X: ±2 X.X' ±0.5'		X.XX ±0.15	
X.X ±0.30		X.XX ±0.25	
TOLERANCE:			
DRAWN BY: 陈一鸣	DATE: 2014-02-23	CHECKED BY: 马跃	DATE: 2014-02-23
APPROVED BY:	DATE:		
PART NAME: 2.54X8.5FH 1XNP1N 180° 弯型		PART NO.:	2685Y-1XXXMXSXXSX01
MOLD NO.:		DRAW NO.:	HYC-1812011106
SHEET NO.:	2014-02-23	1 OF 1	

Contacts	Dimensions	A	B	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	
Contacts	Dimensions	A	B	2.94	0	2.94	5.48	8.02	10.56	13.10	15.64	18.18	20.72	23.26	25.80	28.34	30.88	33.42	35.96	38.50	41.04	43.58	46.12	48.66
Contacts	Dimensions	A	B	53.74	50.80	53.74	56.28	58.82	61.36	63.90	66.44	68.98	71.52	74.06	76.60	79.14	81.68	84.22	86.76	89.30	91.84	94.38	96.92	99.46

Dimensions List

**SPECIFICATIONS**  
 Rated Current:3.0AMP  
 Contact Resistance:20mΩ Max  
 Withstand Voltage:100V AC/DC  
 Insulation Resistance:1000MΩ Min  
 Operation Temperature:-40°C to +105°C  
 Contact Material:Brass  
 Contact Plating:Au or Sn Over Ni  
 Insulator Material:Polyester(UL94V-0)  
 Standard: PA6T  
 Max.Processing Temp: 230°C for 30-60 seconds  
 (260°C for 10 seconds)

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Headers & Wire Housings](#) category:*

*Click to view products by [HOAUC](#) manufacturer:*

Other Similar products are found below :

[95000-104TRLF](#) [10135584-644402LF](#) [DF62W-EP2022PCA](#) [95000-106TRLF](#) [DF62W-2022SCA](#) [DF62W-EP2022PC](#) [2203348](#) [DF62W-2022SC](#) [1084018](#) [1029039](#) [1084017](#) [802-10-012-10-002000](#) [1112640](#) [1112639](#) [891-007-9SS-BST1T](#) [000-34000](#) [0008550134](#) [0009482033](#) [0009507031](#) [57102-F02-18ULF](#) [57102-S06-03LF](#) [57202-S52-04LF](#) [PCN6-15S-2.5E](#) [0039019024](#) [58102-G61-06LF](#) [582553-1](#) [0009485154](#) [0009508121](#) [0022285053](#) [0050291907](#) [018731A](#) [LY20-4P-DT1-P1E-BR](#) [02.125.8002.8](#) [60101931](#) [60598-1 \(Cut Strip\)](#) [M1625-3R/100](#) [61062-3](#) [61082-181009](#) [CSU011177004](#) [636-1427](#) [638009-1](#) [641938-9](#) [641991-4](#) [644168-1](#) [644827-2](#) [647662-1](#) [65039-019ELF](#) [65692-001LF](#) [65781-018](#) [65781-047](#)