





MINTRON CO., LTD.		TITLE: MTE10-XXSL		DWG NO.:		SCALE: 1/1		SHEET: 1/1		REV. A	
NAME (INTENDED USE)		PART NO. (INTENDED USE)		APPD.: SUNNY		CHKD.: LISA		DR: ZOE		2006-11-28	
UNITS: mm		MATL:		FINISH:		QTY:		EJECTOR HEADER CONNECTOR			
X. ± 0.30	X. ± 0.20	.XX ± 0.10	.XXX ± 0.05								
X. ± 2°	.X ± 2°	.XX ± 1°	.XXX ± 0.5°								

No. of Pins Latch Type
 06 24 L=Long Latch
 08 26 S=Short Latch
 10 30 N=Without Latch
 12 34
 14 40
 16 50
 18 60
 20 64

MTE10-XXSX

Ordering Information

NOTES:
 Current Rating: 3.0AMP
 Contact Resistance: 20mΩ Max
 Insulation Resistance: 1000MΩ Min
 Withstand Voltage: 1000V AC/Minute
 Operation Temperature: -40°C to +105°C
 Contact Material: Brass
 Contact plating: Sn or Au Over Ni
 Insulator Material: PBT or PA6T+30%GF(UL94V-0)
 No side slot "A" and "B" from 6 to 16Pin
 No side slot "A" from 18 to 58Pin



APPD.	ECN. NO.	REV.	A
-------	----------	------	---

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Headers & Wire Housings](#) category:

Click to view products by [MINTRON](#) manufacturer:

Other Similar products are found below :

[95000-104TRLF](#) [10135584-644402LF](#) [DF62W-EP2022PCA](#) [95000-106TRLF](#) [DF62W-2022SCA](#) [DF62W-EP2022PC](#) [2203348](#) [DF62W-2022SC](#) [1084018](#) [1029039](#) [1084017](#) [802-10-012-10-002000](#) [1112640](#) [1112639](#) [891-007-9SS-BST1T](#) [000-34000](#) [0008550134](#) [0009482033](#) [0009507031](#) [57102-F02-18ULF](#) [57102-S06-03LF](#) [57202-S52-04LF](#) [PCN6-15S-2.5E](#) [0039019024](#) [58102-G61-06LF](#) [582553-1](#) [0009485154](#) [0009508121](#) [0022285053](#) [0050291907](#) [018731A](#) [LY20-4P-DT1-P1E-BR](#) [02.125.8002.8](#) [60101931](#) [60598-1 \(Cut Strip\)](#) [M1625-3R/100](#) [61062-3](#) [61082-181009](#) [CSU011177004](#) [636-1427](#) [638009-1](#) [641938-9](#) [641991-4](#) [644168-1](#) [644827-2](#) [647662-1](#) [65039-019ELF](#) [65692-001LF](#) [65781-018](#) [65781-047](#)