



| | | | | | | |
|------|--------------|------------|------|-----------|-------------------|-----------------------------------|
| REV. | DESCRIPTION | DATE | NAME | X.XX±0.05 | ANGLE | DRAWN NO. : A1010HB-XPNNXXXXXX20X |
| A0 | NEW RELEASE | 2013.05.20 | 陳錦慶 | X.XX±0.15 | | |
| A1 | EN1608250008 | 2013.08.31 | 賴永強 | X.X±0.25 | | |
| | | | | | GENERAL TOLERANCE | |
| | | | | | 2013.05.20 | |
| | | | | | 陳彥兆 | |
| | | | | | 謝瑞清 | |
| | | | | | APPROVED BY | |
| | | | | | mm | |
| | | | | | 1 : 1 | |
| | | | | | 1 of 1 | |
| | | | | | SHEET | |
| | | | | | SCALE | |
| | | | | | UNIT | |

| | | | | |
|---------|------------|-------|-------|-------|
| Circuit | No. | A | B | C |
| | Dimensions | 10.00 | 12.00 | 11.35 |
| Circuit | No. | A | B | C |
| | Dimensions | 9.00 | 11.00 | 10.35 |
| Circuit | No. | A | B | C |
| | Dimensions | 8.00 | 10.00 | 9.35 |
| Circuit | No. | A | B | C |
| | Dimensions | 7.00 | 9.00 | 8.35 |
| Circuit | No. | A | B | C |
| | Dimensions | 6.00 | 8.00 | 7.35 |
| Circuit | No. | A | B | C |
| | Dimensions | 5.00 | 7.00 | 6.35 |
| Circuit | No. | A | B | C |
| | Dimensions | 4.00 | 6.00 | 5.35 |
| Circuit | No. | A | B | C |
| | Dimensions | 3.00 | 5.00 | 4.35 |
| Circuit | No. | A | B | C |
| | Dimensions | 2.00 | 4.00 | 3.35 |
| Circuit | No. | A | B | C |
| | Dimensions | 1.00 | 3.00 | 2.35 |
| Circuit | No. | A | B | C |
| | Dimensions | 11.00 | 13.00 | 12.35 |
| Circuit | No. | A | B | C |
| | Dimensions | 12.00 | 14.00 | 13.35 |
| Circuit | No. | A | B | C |
| | Dimensions | 13.00 | 15.00 | 14.35 |
| Circuit | No. | A | B | C |
| | Dimensions | 14.00 | 16.00 | 15.35 |
| Circuit | No. | A | B | C |
| | Dimensions | 15.00 | 17.00 | 16.35 |
| Circuit | No. | A | B | C |
| | Dimensions | 16.00 | 18.00 | 17.35 |
| Circuit | No. | A | B | C |
| | Dimensions | 17.00 | 19.00 | 18.35 |
| Circuit | No. | A | B | C |
| | Dimensions | 18.00 | 20.00 | 19.35 |
| Circuit | No. | A | B | C |
| | Dimensions | 19.00 | 21.00 | 20.35 |
| Circuit | No. | A | B | C |
| | Dimensions | 20.00 | 22.00 | 21.35 |
| Circuit | No. | A | B | C |
| | Dimensions | 21.00 | 23.00 | 22.35 |
| Circuit | No. | A | B | C |
| | Dimensions | 22.00 | 24.00 | 23.35 |
| Circuit | No. | A | B | C |
| | Dimensions | 23.00 | 25.00 | 24.35 |
| Circuit | No. | A | B | C |
| | Dimensions | 24.00 | 26.00 | 25.35 |

SPECIFICATIONS
 Current Rating: 1A AC,DC
 Voltage Rating: 50V AC,DC
 Temperature Range: -25°C ~ +85°C
 Contact Resistance: 20mΩ Max.
 Insulation Resistance: 100MΩ Min.
 Withstanding Voltage: 500V AC/minute

P/N LEGEND

| | | |
|---|-------------------------------|-------------------|
| ① | Series No. | A1001 |
| ② | Connector type: | HB=Housing B type |
| ③ | No. of circuits | |
| ④ | N=Halogen Free | |
| ⑤ | Material: 0=Nylon 66-VO+15%GF | |
| ⑥ | Color: W=White | |
| ⑦ | Plating code: NP=Non-plating | |
| ⑧ | Plating code: N=Non-plating | |
| ⑨ | Option code: 20=Without ear | |
| ⑩ | Packing code: G=Bag | |

燦達電子工業股份有限公司
 JOINT TECH ELECTRONIC IND. CO., LTD.
 TITLE: 1.00mm PITCH WITHOUT PROTRUSIONS

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Headers & Wire Housings](#) category:

Click to view products by [Joint manufacturer](#):

Other Similar products are found below :

[95000-104TRLF](#) [10135584-644402LF](#) [DF62W-EP2022PCA](#) [95000-106TRLF](#) [DF62W-2022SCA](#) [DF62W-EP2022PC](#) [2203348](#) [DF62W-2022SC](#) [1084018](#) [1029039](#) [1084017](#) [802-10-012-10-002000](#) [1112640](#) [1112639](#) [891-007-9SS-BST1T](#) [000-34000](#) [0008550134](#) [0009482033](#) [0009507031](#) [57102-F02-18ULF](#) [57102-S06-03LF](#) [57202-S52-04LF](#) [PCN6-15S-2.5E](#) [0039019024](#) [58102-G61-06LF](#) [582553-1](#) [0009485154](#) [0009508121](#) [0022285053](#) [0050291907](#) [018731A](#) [LY20-4P-DT1-P1E-BR](#) [02.125.8002.8](#) [60101931](#) [60598-1 \(Cut Strip\)](#) [M1625-3R/100](#) [61062-3](#) [61082-181009](#) [CSU011177004](#) [636-1427](#) [638009-1](#) [641938-9](#) [641991-4](#) [644168-1](#) [644827-2](#) [647662-1](#) [65039-019ELF](#) [65692-001LF](#) [65781-018](#) [65781-047](#)