



17 16 15 14 13 12 11




E E D C B A

REV.	A
ECN. NO.	
APPD.	

Recommended P.C.B Layout(Top Side)  
(PCB BOARD TOLERANCE±0.05)



NOTES:  
 Current Rating:1.5AMP  
 Contact Resistance:20mΩ max  
 Withstand Voltage:500V AC/DC  
 Insulation Resistance:100MΩ min  
 Operation Temperature:-40°C to +105°C  
 Contact Material:Brass  
 Contact plating:Au or Sn Over Ni  
 Insulator Material:PA6T+30%GF(UL94V-0)



NAME(INTENDED USE)		PART NO.(INTENDED USE)		TITLE: MTB11-XXS		DWG NO.:	
UNITS mm		FINISH		APPD: SUNNY		CHKD: LISA	
X. ±0.30		X. ±0.20		X. ±0.10		X.XX ±0.05	
X. ±0.5°		X. ±2°		X. ±1°		X.XX ±0.5°	
QTY		DR: ZOE		2006-11-28		SCALE 1/1	
CONNECTOR		BOX HEADER		REV. A		SHEET 1/1	

17 16 15 14 13 12 11

E E D C B A

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Headers & Wire Housings](#) category:*

*Click to view products by [MINTRON](#) manufacturer:*

Other Similar products are found below :

[95000-104TRLF](#) [10135584-644402LF](#) [DF62W-EP2022PCA](#) [95000-106TRLF](#) [DF62W-2022SCA](#) [DF62W-EP2022PC](#) [2203348](#) [DF62W-2022SC](#) [1084018](#) [1029039](#) [1084017](#) [802-10-012-10-002000](#) [1112640](#) [1112639](#) [891-007-9SS-BST1T](#) [000-34000](#) [0008550134](#) [0009482033](#) [0009507031](#) [57102-F02-18ULF](#) [57102-S06-03LF](#) [57202-S52-04LF](#) [PCN6-15S-2.5E](#) [0039019024](#) [58102-G61-06LF](#) [582553-1](#) [0009485154](#) [0009508121](#) [0022285053](#) [0050291907](#) [018731A](#) [LY20-4P-DT1-P1E-BR](#) [02.125.8002.8](#) [60101931](#) [60598-1 \(Cut Strip\)](#) [M1625-3R/100](#) [61062-3](#) [61082-181009](#) [CSU011177004](#) [636-1427](#) [638009-1](#) [641938-9](#) [641991-4](#) [644168-1](#) [644827-2](#) [647662-1](#) [65039-019ELF](#) [65692-001LF](#) [65781-018](#) [65781-047](#)