



N-channel Enhancement mode TO-220F/TO-220/TO-251/TO-252 MOSFET**Features**

- High ruggedness
- $R_{DS(ON)}$ (Typ 1.05Ω)@ $V_{GS}=10V$
- Gate Charge (Typ 30nC)
- Improved dv/dt Capability
- 100% Avalanche Tested
- Application:UPS, Inverter, TV-POWER

 **$BV_{DSS} : 600V$** **$I_D : 7A$** **$R_{DS(ON)} : 1.05\Omega$** **General Description**

This power MOSFET is produced with advanced technology of SAMWIN.

This technology enable power MOSFET to have better characteristics, such as fast switching time, low on resistance, low gate charge and especially excellent avalanche characteristics.

Order Codes

Item	Sales Type	Marking	Package	Packaging
1	SW F 7N60D	SW7N60D	TO-220F	TUBE
2	SW P 7N60D	SW7N60D	TO-220	TUBE
3	SW I 7N60D	SW7N60D	TO-251	TUBE
4	SW D 7N60D	SW7N60D	TO-252	REEL

Absolute maximum ratings

Symbol	Parameter	Value				Unit
		TO220F	TO220	TO251	TO252	
V_{DSS}	Drain to Source Voltage	600				V
I_D	Continuous Drain Current (@ $T_C=25^\circ C$)	7				A
	Continuous Drain Current (@ $T_C=100^\circ C$)	4.2				A
I_{DM}	Drain current pulsed	(note 1)	28			A
V_{GS}	Gate to Source Voltage		± 30			V
E_{AS}	Single pulsed Avalanche Energy	(note 2)	420			mJ
E_{AR}	Repetitive Avalanche Energy	(note 1)	49			mJ
dv/dt	Peak diode Recovery dv/dt	(note 3)	5			V/ns
P_D	Total power dissipation (@ $T_C=25^\circ C$)	23.76	208	113	125	W
	Derating Factor above 25°C	0.19	1.67	0.9	1.0	W/°C
T_{STG}, T_J	Operating Junction Temperature & Storage Temperature		-55 ~ + 150			°C
T_L	Maximum Lead Temperature for soldering purpose, 1/8 from Case for 5 seconds.		300			°C

*. Drain current is limited by junction temperature.

Thermal characteristics

Symbol	Parameter	Value				Unit
		TO220F	TO220	TO251	TO252	
R_{thjc}	Thermal resistance, Junction to case	5.26	0.6	1.1	1.0	°C/W
R_{thja}	Thermal resistance, Junction to ambient	49.21	60	80		°C/W

Electrical characteristic ($T_C = 25^\circ\text{C}$ unless otherwise specified)

Symbol	Parameter	Test conditions	Min.	Typ.	Max.	Unit
Off characteristics						
BV_{DSS}	Drain to source breakdown voltage	$V_{\text{GS}}=0\text{V}, I_D=250\mu\text{A}$	600			V
$\Delta \text{BV}_{\text{DSS}} / \Delta T_J$	Breakdown voltage temperature coefficient	$I_D=250\mu\text{A}$, referenced to 25°C		0.47		$^\circ\text{C}$
I_{DSS}	Drain to source leakage current	$V_{\text{DS}}=600\text{V}, V_{\text{GS}}=0\text{V}$			1	μA
		$V_{\text{DS}}=480\text{V}, T_C=125^\circ\text{C}$			50	μA
I_{GSS}	Gate to source leakage current, forward	$V_{\text{GS}}=30\text{V}, V_{\text{DS}}=0\text{V}$			100	nA
	Gate to source leakage current, reverse	$V_{\text{GS}}=-30\text{V}, V_{\text{DS}}=0\text{V}$			-100	nA
On characteristics						
$V_{\text{GS(TH)}}$	Gate threshold voltage	$V_{\text{DS}}=V_{\text{GS}}, I_D=250\mu\text{A}$	2.5		4.5	V
$R_{\text{DS(ON)}}$	Drain to source on state resistance	$V_{\text{GS}}=10\text{V}, I_D = 3.5\text{A}$		1.05	1.2	Ω
G_{fs}	Forward Transconductance	$V_{\text{GS}}=30\text{V}, I_D = 3.5\text{A}$	6			S
Dynamic characteristics						
C_{iss}	Input capacitance	$V_{\text{GS}}=0\text{V}, V_{\text{DS}}=25\text{V}, f=1\text{MHz}$		1000		pF
C_{oss}	Output capacitance			115		
C_{rss}	Reverse transfer capacitance			25		
$t_{\text{d(on)}}$	Turn on delay time	$V_{\text{DS}}=300\text{V}, I_D=7\text{A}, R_G=25\Omega$ (note 4, 5)		14		ns
t_{r}	Rising time			32		
$t_{\text{d(off)}}$	Turn off delay time			67		
t_f	Fall time			35		
Q_g	Total gate charge	$V_{\text{DS}}=480\text{V}, V_{\text{GS}}=10\text{V}, I_D=7\text{A}$ (note 4, 5)		30		nC
Q_{gs}	Gate-source charge			5		
Q_{gd}	Gate-drain charge			15		

Source to drain diode ratings characteristics

Symbol	Parameter	Test conditions	Min.	Typ.	Max.	Unit
I_s	Continuous source current	Integral reverse p-n Junction diode in the MOSFET			7	A
I_{SM}	Pulsed source current				28	A
V_{SD}	Diode forward voltage drop.	$I_s=7\text{A}, V_{\text{GS}}=0\text{V}$			1.5	V
T_{rr}	Reverse recovery time	$I_s=7\text{A}, V_{\text{GS}}=0\text{V}, dI_F/dt=100\text{A/us}$		315		ns
Q_{rr}	Breakdown voltage charge			3.1		μC

※. Notes

- Repetitive rating : pulse width limited by junction temperature.
- $L = 17.7\text{mH}, I_{AS} = 7\text{A}, V_{DD} = 50\text{V}, R_G=25\Omega$, Starting $T_J = 25^\circ\text{C}$
- $I_{SD} \leq 10\text{A}, di/dt = 100\text{A/us}, V_{DD} \leq \text{BV}_{\text{DSS}}$, Starting $T_J = 25^\circ\text{C}$
- Pulse Test : Pulse Width $\leq 300\text{us}$, duty cycle $\leq 2\%$
- Essentially independent of operating temperature.

Fig. 1. On-state characteristics




Fig. 2. On-resistance variation vs. drain current and gate voltage




Fig. 3. Gate charge characteristics




Fig. 4. On state current vs. diode forward voltage




Fig 5. Breakdown Voltage Variation vs. Junction Temperature




Fig. 6. On resistance variation vs. junction temperature




Fig. 7. Maximum safe operating area (TO-220F)




Fig. 8. Transient thermal response curve (TO-220F)




Fig. 9. Maximum safe operating area (TO-220)




Fig. 10. Transient thermal response curve (TO-220)




Fig. 11. Maximum safe operating area (TO-251)




Fig. 12. Transient thermal response curve (TO-251)




Fig. 13. Maximum safe operating area (TO-252)




Fig. 14. Transient thermal response curve (TO-252)




Fig. 15. Capacitance Characteristics




Fig. 16. Gate charge test circuit & waveform





Fig. 17. Switching time test circuit & waveform




Fig. 18. Unclamped Inductive switching test circuit & waveform





Fig. 19. Peak diode recovery dv/dt test circuit & waveform



Samwin®
内部保密

DISCLAIRATION:

- * All the data&curve within this document was tested in XI' AN SEMIPOWER TESTING&APPLICATION CENTER.
- * This product has passed the PCT,TC,HTRB,HTGB,HAST,PC and Solderdunk reliability testing.
- * Qualification Standards can also be found on the Web site (<http://www.semipower.com.cn>)
- * Any advice, please send your proposal to samwin@samwinsemi.com



X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for MOSFET category:

Click to view products by Sam&wing manufacturer:

Other Similar products are found below :

[614233C](#) [648584F](#) [MCH3443-TL-E](#) [MCH6422-TL-E](#) [FDPF9N50NZ](#) [FW216A-TL-2W](#) [FW231A-TL-E](#) [APT5010JVR](#) [NTNS3A92PZT5G](#)
[IRF100S201](#) [JANTX2N5237](#) [2SK2464-TL-E](#) [2SK3818-DL-E](#) [FCA20N60_F109](#) [FDZ595PZ](#) [STD6600NT4G](#) [FSS804-TL-E](#) [2SJ277-DL-E](#)
[2SK1691-DL-E](#) [2SK2545\(Q,T\)](#) [D2294UK](#) [405094E](#) [423220D](#) [MCH6646-TL-E](#) [TPCC8103,L1Q\(CM](#) [367-8430-0972-503](#) [VN1206L](#)
[424134F](#) [026935X](#) [051075F](#) [SBVS138LT1G](#) [614234A](#) [715780A](#) [NTNS3166NZT5G](#) [751625C](#) [873612G](#) [IRF7380TRHR](#)
[IPS70R2K0CEAKMA1](#) [RJK60S3DPP-E0#T2](#) [RJK60S5DPK-M0#T0](#) [APT5010JVFR](#) [APT12031JFLL](#) [APT12040JVR](#) [DMN3404LQ-7](#)
[NTE6400](#) [JANTX2N6796U](#) [JANTX2N6784U](#) [JANTXV2N5416U4](#) [SQM110N05-06L-GE3](#) [SIHF35N60E-GE3](#)