

0603, RoHS Compliant & Pb-Free SURFACE MOUNT CHIP FUSE (FAST-BLOW) 表面贴装片式保险丝 (速断型)

INTERRUPTING CAPACITY / 分断能力:

50A 32V AC (200mA-1A) 35A 32V AC (1.2A-5A)
50A 63V DC (200mA-250mA) 50A 32V DC (300mA-1A)
35A 32V DC (1.2A-5A)

TECHNICAL PARAMETERS/ 技术参数:

CATALOG NO. 目录编号	CURRENT RATING 额定电流	SAFETY APPROVALS 安全认证				REFERENCE (A ² .Sec.) (RoHS) I ² T 参考值
		UR		cUR		
		L1	L2	L1	L2	
06F-0200L	200mA	●	●	●	●	0.00056
06F-0250L	250mA	●	●	●	●	0.00078
06F-0315L	315mA	●		●		0.00083
06F-0375L	375mA	●		●		0.00115
06F-0400L	400mA	●		●		0.00135
06F-0500L	500mA	●		●		0.0069
06F-0630L	630mA	●		●		0.0072
06F-0750L	750mA	●		●		0.017
06F-0800L	800mA	●		●		0.019
06F-010L	1A	●		●		0.041
06F-012L	1.2A	●		●		0.043
06F-013L	1.25A	●		●		0.045
06F-015L	1.5A	●		●		0.078
06F-016L	1.6A	●		●		0.076
06F-020L	2A	●		●		0.130
06F-025L	2.5A	●		●		0.180
06F-030L	3.0A	●		●		0.280
06F-032L	3.15A	●		●		0.32
06F-035L	3.5A	●		●		0.361
06F-040L	4A	●		●		0.408
06F-050L	5A	●		●		1.100


● DENOTES FOR APPROVED ● 表示已取得安全认证
L1 DENOTES FOR 32V L1 代表 32V
L2 DENOTES FOR 63V L2 代表 63V

ELECTRICAL CHARACTERISTICS/ 电气特性:

% of CURRENT RATING 额定电流的 %	BLOWING TIME 熔断时间
100%	4 hours Min. 最快 4 小时
250%	10 seconds Max. 最慢 10 秒 (200mA-3A)
350%	1 second Max. 最慢 1 秒 (3.15A-5A)

Standards/ 标准: UL 248-1, UL 248-14
Operating Temperature/ 工作温度: -55°C ~90°C
Storing Temperature/ 储存温度: -55°C ~85°C
Resistance to soldering heat/ 耐焊接热性: 260°C, 10s Max.
Solderability/ 可焊性: 235°C ±5°C, 3.5s±0.5/-0s


Dimensions/ 尺寸:



PACKING/ 包装:


5,000 PIECES TAPED AND REELED IN ONE BOX
每卷 5,000 只保险丝, 装入一个包装盒

BOX SIZE/ 包装盒尺寸:



06F AVERAGE I-T CHARACTERISTICS CURVE (FOR REFERENCE ONLY)

06F 平均 I-T 曲线图 (仅供参考)



X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Surface Mount Fuses](#) category:

Click to view products by [HOLLY](#) manufacturer:

Other Similar products are found below :

[FHC20402ADTP](#) [FT600-0500-2](#) [NFVC6125S0R50TRF](#) [SFT-125MA](#) [TF16SN2.00TTD](#) [TF16SN3.15TTD](#) [41921000000](#) [TR/3216LR-500MA](#) [CCP2B20TTE](#) [TR-3216FF4-R](#) [SST 1-1K](#) [SST 5 -1K](#) [SST 2-1K](#) [TR2-TCP500-R](#) [F60C500V12AS](#) [FCC16501ABTP](#) [FCC16102ABTP](#) [FHC16322ADTP](#) [0308.250UR](#) [0308.375UR](#) [0308.500UR](#) [0308.750UR](#) [0308001.UR](#) [030801.5UR](#) [FCC16202ABTP](#) [3-122-714](#) [3-122-720](#) [3-122-718](#) [3-122-712](#) [3-122-716](#) [03081.25UR](#) [CQ06LF 5A 32V](#) [CQ06LT 5A 32V](#) [SET 2A 125V \(G\)](#) [SET 1A 125V \(G\)](#) [SEF 10A 125V \(G\)](#) [SEF 3A 125V \(G\)](#) [SEF 4A 125V \(G\)](#) [SEF 6A 125V \(G\)](#) [SEF 7A 125V \(G\)](#) [SET 4A 125V \(G\)](#) [SET 3A 125V \(G\)](#) [SET 5A 125V \(G\)](#) [SET 7A 125V \(G\)](#) [F0603G0R03FNTR](#) [SKY87604-12](#) [SKY87604-11](#) [SKY87604-13](#) [0154002.DRL](#) [0154008.DRL](#)