



- Specifications :**
- Voltage rating: 50V AC / DC
 - Current rating: 1A AC / DC
 - Withstanding voltage: 500V AC/minute
 - Temperature range: -25°C~+85°C
 - Insulation resistance: ≥100MΩ
 - Contact resistance: ≤30mΩ
 - After environmental testing: ≤50mΩ

X1251 W R S-XX HF-XX SN XX

① ② ③ ④ ⑤ ⑥ ⑦ ⑧ ⑨

- ① Series No.
- ② Category: W-wafer
- ③ Welding Board Angle: R- Right Angle 90°
- ④ Welding Way: S-SMT
- ⑤ Row No.-Pin No.: XX-02P~15P
- ⑥ Plug the Pin & Special No.: HF-Halogen free
- ⑦ Material: 9T-PA9T 94V-0 ; 46-PA46 94V-0 ; LP-LCP 94V-0
- ⑧ Plating Category: SN-Bright tin plating ; SW-Fog Tin plating
- ⑨ Color: Blank-natural color

Poles	Dimensions(mm)			Dimensions(mm)		
	A	B	C	A	B	C
02	1.25	5.75	3.75	10.00	14.50	12.50
03	2.50	7.00	5.00	11.25	15.75	13.75
04	3.75	8.25	6.25	12.50	17.00	15.00
05	5.00	9.50	7.50	13.75	18.25	16.25
06	6.25	10.75	8.75	15.00	19.50	17.50
07	7.50	12.00	10.00	16.25	20.75	18.75
08	8.75	13.25	11.25	17.50	22.00	20.00

PART NO	Material	Material (Solder Tabs)	Finish (Solder Tabs)	Suitable XKB Terminal
X1251WRS-XX-46SW	PA46 UL 94V-0	Tin Plating Matte Tin 70u" Min. Over Ni 30u"		
X1251WRS-XXHF-LPSW	LCP UL 94V-0 Halogen Free	Phosphor Bronze Tin Plating Matte Tin 70u" Min. Over Ni 30u"		X1251H
X1251WRS-XX-9TSN	Nylon 9T UL 94V-0	Tin-Plated Bright 70u" Over Ni 30u"		

Recommended P.C.B Layout
General Tolerance±0.05

For and on behalf of
香港星坤工業精密有限公司
KKB INDUSTRIAL PRECISION CO., LIMITED

REVISIONS	DATE	REVISOR	APPROVED	UNSPECIFIED TOLERANCES	DSND	DATE	SCALE: N/A	MODEL TYPE: X1251WRS-XXHF-XXXX		
△ X				ANGULAR L ≤ 4 4 < L ≤ 16 16 < L ≤ 63 L > 63	± 5° ± 0.2 ± 0.3 ± 0.4 ± 0.5	DWN	VIEW:	PART NO.: 1.25mm Crimp Style Connectors		
△ X						CHKD	UNIT: mm	DWG NO.:		
MARK						APPD	SIZE: A4	WEIGHT 1.0g	SHEET 1/1	REVISION A0

KKB INDUSTRIAL PRECISION CO., LIMITED

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Headers & Wire Housings](#) category:

Click to view products by [XKB](#) manufacturer:

Other Similar products are found below :

[95000-104TRLF](#) [10135584-644402LF](#) [DF62W-EP2022PCA](#) [95000-106TRLF](#) [DF62W-2022SCA](#) [DF62W-EP2022PC](#) [2203348](#) [DF62W-2022SC](#) [1084018](#) [1029039](#) [1084017](#) [802-10-012-10-002000](#) [1112640](#) [1112639](#) [891-007-9SS-BST1T](#) [000-34000](#) [0008550134](#) [0009482033](#) [0009507031](#) [57102-F02-18ULF](#) [57102-S06-03LF](#) [57202-S52-04LF](#) [PCN6-15S-2.5E](#) [0039019024](#) [58102-G61-06LF](#) [582553-1](#) [0009485154](#) [0009508121](#) [0022285053](#) [0050291907](#) [018731A](#) [LY20-4P-DT1-P1E-BR](#) [02.125.8002.8](#) [60101931](#) [60598-1 \(Cut Strip\)](#) [M1625-3R/100](#) [61062-3](#) [61082-181009](#) [CSU011177004](#) [636-1427](#) [638009-1](#) [641938-9](#) [641991-4](#) [644168-1](#) [644827-2](#) [647662-1](#) [65039-019ELF](#) [65692-001LF](#) [65781-018](#) [65781-047](#)