



深圳市首韩科技有限公司

SHENZHEN SHOUHAN TECHNOLOGY CO.,LTD

Tel: 0755-27597601

Fax: 0755-27597491

承认书

名称规格: SK12D07VG4

客户料号:

工程部印章 刘小军	客户确认
------------------	------

联络人: 罗孝金

产品规格书

产品系列 TITLE: PUSH SLIDE SWITCH




产品名称 MODEL:

产品规格:

项目、规格测试条件及要求
一、外观规格尺寸 CONSTRUCTION
1. 形状、规格尺寸 依照图形规定 SHAPE AND DIMENSIONS SUBJECT TO ATTACHED CHART REGULATION .
2. 外观 各部分应良好无生锈、裂痕、电镀不良现象。 APPEARANCE: EVERY PART SHOULD BE FINISHED NOT TO EXIST RUST、FLAW、CRACK AND BAD PLATING.
二、机械性能 MECHANICAL STRUCTURE
1. 作动力 OPERATION FORCE:130-330gf
2. 端子强度 于各端子尖端加 400gF 压力, 1 分钟内端子无松动、脱落及端子无破裂。 STAKING TERMINALS: WHEN 400g/FS IN/ARE WEIGHTED ON TOP TERMINAL IN EVERY DIRECTION FOR ONE MINUTE. LOOSE STAKING OF TERMINAL AND DAMAGE ON STATOR BOARD SHOULD NOT EXIST .
3. 柄强度 以一个 1 公斤静负荷力施加在柄部操作方向 1 分钟。柄部无严重变形, 可正常工作。 STAKING KNOB: WITH 1KG QUIET BURDEN OPERATE DIRECTION ON KNOB LAST PART THE KNOB HAS NO SEVERITY TO TRANSFORM AND RUBTUEER,CAN WORK NORMALLY.
三、电气性能 ELECTRICAL STRUCTURE
1. 额定功率 RATING DC 50V 0.5A
2. 时间特性 TIMING NON SHORTING
3. 接触电阻 DC 5V 1A 电压下降法; 1K HZ 20Ma 以下, 接触电阻小于 30mΩ。 CONTACT RESISTANCE: LESS THAN 30mΩ ON DC 5V 1A MEASURED BY VOLTAGE ESREASING METHOD OR MEASURED BY 1K HZ LESS THAN 20Ma.
4. 绝缘电阻 DC 500V 250MΩ 以上。 INSULATION RESISTANCE: MORE THAN 250MΩ ON DC 500V MEASURED BY INSULATION TESTER.
5. 耐电压 50-60HZ AC 500V 1 分钟无异常发生。 WITHSTAND VOLTAGE: AC 500V, 50-60 HZ FOR 1 MIN.
四、耐湿性 放置于温度 40±2℃, 相对湿度 90%—95%以内 48 小时后, 在常温 中放置 1 小时后测定测定绝缘电阻为 10MΩ 以上 HUMIDITY TEST: INSULATION RESISTANCE IS 10 MΩ OVER MEASURED WITHIN 30 MINUTE AFTER REMAINING SWITCH FOR 48 HOUR AT THE CONDITION OF TEMPERATUER 40 ±2℃ AND HUMIDTY 90-95%.
五、耐焊性 人工焊 5 秒内 260±10℃ 自动焊 5 秒内 230±10℃ SOLDER HEAT RESISTANCE: MANUAL SLODERING: WITHIN 4 SECOND 260 ±10℃ AUTOMATIC SLODERING: WITHIN 5 SECOND 230 ±10℃
六、寿命测试 LIFE TEST 5000 次
1. 测试机速度 SPEET OF TESTING MACHINE: 15-18 CYCLE/MIN



CAD FILE:



NO.	PARTS	MATERIALS	Q'TY	FINISE	TOLERANCE UNLESS SPECIFIED	ISSUE	DATE
8							
7							
6	SPRING PLATE	PBS STRIP	1	NATURAL	WITHIN 1.5mm : ±0.1mm		
5	CONTACT CLIP	PBS C5210R-EH	1	Ag PLATED	OVER 1.5mm : ±0.2mm		
4	TERMINAL	BRASS STRIP	3	Ag PLATED OVER Ni PLATED			
3	BASE	PHENOLIC RESIN	1	NATURAL			
2	KNOB	POM	1	BLACK			
1	FRAME	STEEL STRIP	1	Ni PLATED			
					TITLE : HORIZONTAL SLIDE SWITCH		
					MODEL: SK12D07VG4		
					深圳市首韩科技有		

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Toggle Switches](#) category:

Click to view products by [SHOU](#) manufacturer:

Other Similar products are found below :

[A19HV](#) [8A1-C-222](#) [60012L](#) [6006L](#) [6663](#) [7101MD9V30GE](#) [7101SPDV30BE](#) [7103SDV30BE](#) [7105D](#) [7108P3YAV2BE](#) [71YY50282](#)
[7201MD9AVBE](#) [7301K38](#) [7306K36](#) [7310K36](#) [7314K36](#) [7506K4](#) [7592K6](#) [7691K14](#) [7700K1](#) [8396K108](#) [8824K14](#) [8828K13](#) [G2VX](#) [G3VX](#)
[PS83-121G](#) [A101MD9AB04](#) [A101SD9AB04](#) [A101SDCQ04](#) [A103SD9AQ04](#) [A107TZB04](#) [A123P32YZQ](#) [A123S1YZG](#) [A127S1YCQ](#) [1-](#)
[1825192-0](#) [A131S1YZQ](#) [A201SCWZB04](#) [A207SYCB04](#) [A208J61ZQ0004](#) [A221K12KAG](#) [A221S1YZQ](#) [A221T1TCQ](#) [A232K12KZQ](#)
[A232M1YCQ](#) [A323S1CWZQ](#) [A423S1CWZG-M8](#) [A423S1YZQ](#) [12149A-3V](#) [12156AX408](#) [12147AGKX679](#)