



PCB LAYOUT

SPECIFICATION:
Current Rating: 1.5AMP
Contact Resistance: 20m Ω (max)
Insulation Resistance: 1000M Ω Min at 500V DC
Dielectric Strength: 500V AC Per 1 Minute
Operating Temperature: -40°C TO +105°C

MATERIALS:
Insulator: Nylon66 or 6T+30% Glass Fiber, UL94V-0
Contact: Brass
Contact plated: Gold Over Nickel

Poles	Part No.	Dimension mm		
		A	B	C
10	300-2S-10P	17.34	16.24	8.00
12	300-2S-12P	19.34	18.24	10.00
14	300-2S-14P	21.34	20.24	12.00
16	300-2S-16P	23.34	22.24	14.00
18	300-2S-18P	25.34	24.24	16.00
20	300-2S-20P	27.34	26.24	18.00
24	300-2S-24P	31.34	30.24	22.00
26	300-2S-26P	33.34	32.24	24.00
30	300-2S-30P	37.34	36.24	28.00
34	300-2S-34P	41.34	40.24	32.00
40	300-2S-40P	47.34	46.24	38.00
44	300-2S-44P	51.34	50.24	42.00
50	300-2S-50P	57.34	56.24	48.00

TOLERANCE TABLE

.0	±0.20
.00	±0.10
.000	±0.05

APPROVED:	DATE:		TITLE:				
CHECKED:	DATE:		Part No.	B-3002SXP-0110			
DRAWN:	DATE:	UNIT	mm	SCALE	free	REV.	A
LYP	2008-07-17	FILE NO.	Chankw-300-0006	REV.	A	/	

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Headers & Wire Housings](#) category:

Click to view products by [Cankemeng](#) manufacturer:

Other Similar products are found below :

[95000-104TRLF](#) [10135584-644402LF](#) [DF62W-EP2022PCA](#) [95000-106TRLF](#) [DF62W-2022SCA](#) [DF62W-EP2022PC](#) [2203348](#) [DF62W-2022SC](#) [1084018](#) [1029039](#) [1084017](#) [802-10-012-10-002000](#) [1112640](#) [1112639](#) [891-007-9SS-BST1T](#) [000-34000](#) [0008550134](#) [0009482033](#) [0009507031](#) [57102-F02-18ULF](#) [57102-S06-03LF](#) [57202-S52-04LF](#) [PCN6-15S-2.5E](#) [0039019024](#) [58102-G61-06LF](#) [582553-1](#) [0009485154](#) [0009508121](#) [0022285053](#) [0050291907](#) [018731A](#) [LY20-4P-DT1-P1E-BR](#) [02.125.8002.8](#) [60101931](#) [60598-1 \(Cut Strip\)](#) [M1625-3R/100](#) [61062-3](#) [61082-181009](#) [CSU011177004](#) [636-1427](#) [638009-1](#) [641938-9](#) [641991-4](#) [644168-1](#) [644827-2](#) [647662-1](#) [65039-019ELF](#) [65692-001LF](#) [65781-018](#) [65781-047](#)