



**PCB LAYOUT**

TOLERANCE TABLE	
.0	±0.30
.00	±0.20
.000	±0.05

APPROVED:	DATE:	 深圳市灿科盟实业有限公司 CHANKLEMENT INDUSTRYCO., LTD
CHECKED:	DATE:	
DRAWN:	DATE:	TITLE:
SXA	2019-04-27	USB-A/F-1*4P 侧插 短体 弯脚 无卷边 铁壳
		PROD. P/N
		U-USBAN04P-F005
		UNIT
		mm
		SCALE
		Free
		FILE NO.
		REV.
		A
		HLW0

- NOTES:
- MATERIAL:
    - Housing: thermoplastic plastics
    - thrninals: Copper Alloy
    - Gold plated in acontact area:
    - Tin plated in termination
    - Nickel Plated overall
    - Shell: Steel&Copper Alloy
    - Nickel Plated overall
  - ELECTRICAL CHARACTERISTICS:
    - Rating Current: 1.5 Ampere
    - Rating Voltage: 30 V Max
    - Contact Resistance: 30 Milli ohms Min
    - Insulation Resistance: 1000 Mega ohms Min.
  - MECHANICAL CHARACTERISTICS:
    - Connector Mating force: 35N MAX (3.57Kgf)
    - Connector Umating force: 10N min (1.02Kgf)
    - Durability: 1500Cycles:
  - ENVIRONMENT CHARACTERISTICS:
    - Operating temperature: -0° C to +50° C
    - Storage temperature: -20° C to +60° C

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [USB Connectors](#) category:*

*Click to view products by [Cankemeng](#) manufacturer:*

Other Similar products are found below :

[10033527-N3112MLF](#) [17-210561](#) [GMCB05B11124H1EU](#) [17-200931](#) [65-647-8-BK-BU](#) [690-010-295-484](#) [73725-1191BLF](#) [950](#) [E8144-B01021-L](#) [A-USB A-LP-SMT-C](#) [A-USB B-TOP-C](#) [MUSBA511N5](#) [MUSBB15131](#) [MUSBC111M5](#) [MUSBD11135](#) [217450-1](#) [CA 6 W LD](#) [896-30-004-00-000000](#) [KUSBVX-BS1N-W30](#) [KUSBX-AP-KIT-SCBLK](#) [KUSBX-AS2N-W](#) [KUSBX-SMT2AP1S-W](#) [KUSBX-SMTAS1NBTR](#) [KUSBX-SMTBS1NBTR](#) [30-498-6](#) [SK-60A-2](#) [17-200261](#) [17-210051](#) [1734082-1](#) [FK-37-32SL](#) [30-1574](#) [30-470](#) [30-489](#) [30-541](#) [30-572-3](#) [30-9503](#) [M9177/2-1](#) [MAB 5 S](#) [MIKROE-1451](#) [33UBBR-04SW11R](#) [USBFTV2PEM2G](#) [USBFTVC6ZN](#) [USBFTVSCCG](#) [KUSBX-AS2N-W30](#) [KUSBX-SLAS1N-W](#) [KUSBX-SLAS1N-W30](#) [1-1734084-2](#) [E8110-001-01](#) [MUSBC11135](#) [NK-27-32SL](#)