



Material:
 Insulator: PBT+30% Glass Fiber (UL94V-0).
 Contact: Copper Alloy.
 Contact Plated: Gold or Tin over Nickel Plated.
 Specification:
 Current Rating: 1 Amp.
 Withstanding Voltage: AC 500V for 1 Minute.
 Insulation Resistance: 1000M Min. at DC 500V.
 Contact Resistance: 15m Max..
 Operating Temperature: -40°C ~ +105°C.

| Pos. | Part No. | Dim. A | Dim. B | Dim. C | Dim. D | Dim. E | Dim. F |
|------|------------|--------|--------|--------|--------|--------|--------|
| 8 | 300F-8P有耳 | 7.62 | 15.61 | 20.41 | 8.89 | 25.26 | 34.46 |
| 10 | 300F-10P有耳 | 10.16 | 18.15 | 22.95 | 11.43 | 27.80 | 37.00 |
| 14 | 300F-14P有耳 | 15.24 | 23.23 | 28.03 | 16.51 | 32.88 | 42.08 |
| 16 | 300F-16P有耳 | 17.78 | 25.77 | 30.57 | 19.05 | 35.42 | 44.62 |
| 20 | 300F-20P有耳 | 22.86 | 30.85 | 35.65 | 24.13 | 40.50 | 49.70 |
| 24 | 300F-24P有耳 | 27.94 | 35.93 | 40.73 | 29.21 | 45.58 | 54.78 |
| 26 | 300F-26P有耳 | 30.48 | 38.47 | 43.27 | 31.75 | 48.12 | 57.32 |
| 30 | 300F-30P有耳 | 35.56 | 43.55 | 48.35 | 36.83 | 53.20 | 62.40 |
| 34 | 300F-34P有耳 | 40.64 | 48.63 | 53.43 | 41.91 | 58.28 | 67.48 |
| 40 | 300F-40P有耳 | 48.26 | 56.25 | 61.05 | 49.53 | 65.90 | 75.10 |
| 50 | 300F-50P有耳 | 60.96 | 68.95 | 73.75 | 62.23 | 78.60 | 87.80 |
| 60 | 300F-60P有耳 | 73.66 | 81.65 | 86.45 | 74.93 | 91.30 | 100.50 |
| 64 | 300F-64P有耳 | 78.74 | 86.73 | 91.53 | 80.01 | 96.38 | 105.58 |

TOLERANCE TABLE

| | |
|------|-------|
| .0 | ±0.30 |
| .00 | ±0.20 |
| .000 | ±0.05 |

APPROVED:

DATE:

CHECKED:

DATE:

DRAWN:

DATE:

SXA

2019-02-20

TITLE:

300F-XP 压线式 有耳 灰白色

深圳市灿科盟实业有限公司
 Ckmtw CHANKEMENG INDUSTRYCO., LTD

CLIENT P/N B-3000FXXP-E800

| | | | | | |
|----------|-----------------|-------|------|--------|-------|
| UNIT | mm | SCALE | Free | REV. A | QTY/2 |
| FILE NO. | Chkmtw-300-0008 | | | | |

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Headers & Wire Housings](#) category:

Click to view products by [Cankemeng](#) manufacturer:

Other Similar products are found below :

[95000-104TRLF](#) [10135584-644402LF](#) [DF62W-EP2022PCA](#) [95000-106TRLF](#) [DF62W-2022SCA](#) [DF62W-EP2022PC](#) [2203348](#) [DF62W-2022SC](#) [1084018](#) [1029039](#) [1084017](#) [802-10-012-10-002000](#) [1112640](#) [1112639](#) [891-007-9SS-BST1T](#) [000-34000](#) [0008550134](#) [0009482033](#) [0009507031](#) [57102-F02-18ULF](#) [57102-S06-03LF](#) [57202-S52-04LF](#) [PCN6-15S-2.5E](#) [0039019024](#) [58102-G61-06LF](#) [582553-1](#) [0009485154](#) [0009508121](#) [0022285053](#) [0050291907](#) [018731A](#) [LY20-4P-DT1-P1E-BR](#) [02.125.8002.8](#) [60101931](#) [60598-1 \(Cut Strip\)](#) [M1625-3R/100](#) [61062-3](#) [61082-181009](#) [CSU011177004](#) [636-1427](#) [638009-1](#) [641938-9](#) [641991-4](#) [644168-1](#) [644827-2](#) [647662-1](#) [65039-019ELF](#) [65692-001LF](#) [65781-018](#) [65781-047](#)