

PCB LAYOUT

NOTES:

1. MATERIAL:

- 1.1 Housing:thermoplastic plastics
- 1.2 thrminals:Copper Alloy
- Gold plated in acontact area:
- Tin plated in termination
- Nickel Plated overall
- 1.3 Shell:Steel&Copper Alloy
- Nickel Plated overall

2. ELECTRICAL CHARACTERISTICS:


- 2.1 Rating Current:1.5 Ampere
- 2.2 Rating Voltage:30 V Max
- 2.3 Contact Resistance:30 Milli ohms Min
- 2.4 Insulation Resistance:1000 Mega ohms Min.

3. MECHANICAL CHARACTERISTICS:

- 3.1 Connector Mating force:35N MAX(3.57Kgf)
- 3.2 Connector Umating force:10N min(1.02Kgf)
- 3.3 Durability:1500Cycles:

4. ENVIRONMENT CHARACTERISTICS:

- 4.1 Operating temperature:-0° C to +50° C
- 4.2 Storage temperature:-20° C to +60° C

APPROVED:	DATE:	 深圳市灿科盟实业有限公司 CHANKLEMENT INDUSTRYCO., LTD	
CHECKED:	DATE:	TITLE: USB-A/F-1*4P 180度直插 K脚 H=15.0mm 白胶 铜壳	
DRAWN: SXA		PROD. P/N	U-USBAS04P-F001
DATE: 2019-04-27		UNIT	mm
SCALE		SCALE	Free
REV. A		FILE NO.	/
TOLERANCE TABLE		REV.	A
.0	±0.30	HLW0	
.00	±0.20		
.000	±0.05		

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [USB Connectors](#) category:

Click to view products by [Cankemeng](#) manufacturer:

Other Similar products are found below :

[10033527-N3112MLF](#) [17-210561](#) [GMCB05B11124H1EU](#) [17-200931](#) [65-647-8-BK-BU](#) [690-010-295-484](#) [73725-1191BLF](#) [950](#) [E8144-B01021-L](#) [A-USB A-LP-SMT-C](#) [A-USB B-TOP-C](#) [MUSBA511N5](#) [MUSBB15131](#) [MUSBC111M5](#) [MUSBD11135](#) [217450-1](#) [CA 6 W LD](#)
[896-30-004-00-000000](#) [KUSBVX-BS1N-W30](#) [KUSBX-AP-KIT-SCBLK](#) [KUSBX-AS2N-W](#) [KUSBX-SMT2AP1S-W](#) [KUSBX-SMTAS1NBTR](#) [KUSBX-SMTBS1NBTR](#) [30-498-6](#) [SK-60A-2](#) [17-200261](#) [17-210051](#) [1734082-1](#) [FK-37-32SL](#) [30-1574](#) [30-470](#) [30-489](#) [30-541](#) [30-572-3](#) [30-9503](#) [M9177/2-1](#) [MAB 5 S](#) [MIKROE-1451](#) [33UBBR-04SW11R](#) [USBFTV2PEM2G](#) [USBFTVC6ZN](#) [USBFTVSCCG](#)
[KUSBX-AS2N-W30](#) [KUSBX-SLAS1N-W](#) [KUSBX-SLAS1N-W30](#) [1-1734084-2](#) [E8110-001-01](#) [MUSBC11135](#) [NK-27-32SL](#)