


# D20SB10 Thru D20SB100

**High Current Glass Passivated Molding Single-Phase Bridge Rectifier**

**Reverse Voltage 100 to 1000V Forward Current 20 A**

## FEATURES

- Plastic Package has Underwriters Laboratory Flammability Classification 94V-0
- High current capacity with small package
- Glass passivated chip junctions
- Superior thermal conductivity
- High IFSM



## 1. Maximum & Thermal Characteristics Ratings at 25°C ambient temperature unless otherwise specified.

Parameter Symbol		Symbol	D20SB10	D20SB20	D20SB40	D20SB60	D20SB80	D20SB100	Unit		
Maximum repetitive voltage		VRRM	100	200	400	600	800	1000	V		
Maximum RMS Voltage		VRMS	70	140	280	420	560	700	V		
Maximum DC Blocking Voltage		VDC	100	200	400	600	800	1000	V		
Maximum DC reverse current TA=25 °C	IR	5							μA		
at rated DC blocking voltage TA=125°C		500									
Maximum average forward rectified output current at	With heatsink Tc=100°C <sup>(1)</sup> Without heatsink Ta=25°C <sup>(2)</sup>	Io	20							A	
			3.5							A	
Peak forward surge current 8.3ms single half sine-wave superimposed on rated load	IFSM		300							A	
Rating of fusing (t<8.3ms)	I <sup>2</sup> t		373							A <sup>2</sup> sec	
Dielectric strength terminals to case, AC 1 minute Current 1mA	Vdia		2.5							KV	
Max instantaneous forward voltage at 10A	VF		1.05							V	
Operating junction temperature	TJ		-55~150							°C	
Maximum thermal on P.C.B. without heat-sink resistance per leg on Al plate heat-sink	R <sub>θJA</sub>		22							°C/W	
Storage temperature	Tstg		-55~150							°C	
Mounting torque	Tor		Rating Torque : 0.8 (Suggests 0.45~0.65)							N.m	

Notes:

(1) Unit case mounted on aluminum plate heatsink

(2) Units mounted on P.C.B. without heatsink

# D20SB10 Thru D20SB100

## 2. Ratings and Characteristic Curves ( $T_A = 25^\circ\text{C}$ unless otherwise noted)

Fig. 1 Derating Curve




Fig.3 Forward Voltage




Fig.2 Typical Reverse Characteristics






Fig.4 Peak Surge Forward Capability



# D20SB10 Thru D20SB100

## 3. Marking Identification




### Note:

生产日期码包含4位数字，例如“1010”，前两个数字“10”表示为2010年，另外二个数字“18”是指第18周，即表示该产品为2010年18周生产。

型号： **D** **20** **SB** **80**

bridge reverse voltage=800V  
mean: single -in-line bridge  
average rectified forward Current=20A  
mean: D series bridge

## 4. Dimension



# X-ON Electronics

Largest Supplier of Electrical and Electronic Components

***Click to view similar products for [Bridge Rectifiers](#) category:***

***Click to view products by [Leshan manufacturer](#):***

Other Similar products are found below :

[G3SBA60-E351](#) [GBJ1504-BP](#) [GBU10B-BP](#) [GBU15J-BP](#) [GBU15K-BP](#) [GBU4A-BP](#) [GBU4D-BP](#) [GBU6B-E3/45](#) [GSIB680-E3/45](#) [DB101-BP](#) [DF10SA-E345](#) [RMB2S RCG](#) [APT30DF100HJ](#) [APT60DF20HJ](#) [B2S-E3/80](#) [BU1506-E351](#) [BU15085S-E345](#) [BU1508-E3/45](#) [BU1510-E3/45](#) [RS404GL-BP](#) [RS405GL-BP](#) [G3SBA20-E3/51](#) [G5SBA20-E3/51](#) [G5SBA60-E3/51](#) [GBJ1502-BP](#) [GBL02-E351](#) [GBL10-E3/45](#) [GBU10J-BP](#) [GBU4J-BP](#) [GBU4K-BP](#) [GBU8B-E3/45](#) [GBU8D-BP](#) [GBU8J-BP](#) [GSIB1520-E3/45](#) [MB1510](#) [MB352W](#) [MB6M-G](#) [B2M-E345](#) [B40C7000A](#) [B500C7000A](#) [MP5010W-BP](#) [MP501W-BP](#) [MP502-BP](#) [BR1005-BP](#) [BR101-BP](#) [BU1006-E345](#) [BU12065S-E3/45](#) [BU1508-E3/51](#) [BU2006-E3/45](#) [BU2008-E345](#)