



## P-Channel MOSFET

### AO4407

#### ■ Features

- $V_{DS} (V) = -30V$
- $I_D = -12 A (V_{GS} = -20V)$
- $R_{DS(ON)} < 13m\Omega (V_{GS} = -20V)$
- $R_{DS(ON)} < 14m\Omega (V_{GS} = -10V)$
- $R_{DS(ON)} < 30m\Omega (V_{GS} = -5V)$



#### ■ Absolute Maximum Ratings $T_a = 25^\circ C$

Parameter	Symbol	Rating	Unit	
Drain-Source Voltage	$V_{DS}$	-30	V	
Gate-Source Voltage	$V_{GS}$	$\pm 25$		
Continuous Drain Current	$I_D$	$T_A = 25^\circ C$	A	
		$T_A = 70^\circ C$		-10
Pulsed Drain Current	$I_{DM}$	-60		
Avalanche Current	$I_{AS}, I_{AR}$	26		
Power Dissipation	$P_D$	$T_A = 25^\circ C$	3.1	W
		$T_A = 70^\circ C$	2	
Avalanche energy	$L = 0.3mH$	$E_{AS}, E_{AR}$	101	mJ
Thermal Resistance.Junction- to-Ambient	$R_{thJA}$	$t \leq 10s$	40	$^\circ C/W$
		Steady-State	75	
Thermal Resistance.Junction- to-Case	Steady-State	$R_{thJC}$	24	
Junction Temperature	$T_J$	150	$^\circ C$	
Junction Storage Temperature Range	$T_{stg}$	-55 to 150		

## P-Channel MOSFET

### AO4407

#### ■ Electrical Characteristics Ta = 25°C

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
Drain-Source Breakdown Voltage	V <sub>DSS</sub>	I <sub>D</sub> =-250 μA, V <sub>GS</sub> =0V	-30			V
Zero Gate Voltage Drain Current	I <sub>DSS</sub>	V <sub>DS</sub> =-30V, V <sub>GS</sub> =0V			-1	μA
		V <sub>DS</sub> =-30V, V <sub>GS</sub> =0V, T <sub>J</sub> =55°C			-5	
Gate-Body leakage current	I <sub>GSS</sub>	V <sub>DS</sub> =0V, V <sub>GS</sub> =±25V			±100	nA
Gate Threshold Voltage	V <sub>GS(th)</sub>	V <sub>DS</sub> =V <sub>GS</sub> I <sub>D</sub> =-250 μA	-1.7		-2.8	V
Static Drain-Source On-Resistance	R <sub>DS(on)</sub>	V <sub>GS</sub> =-20V, I <sub>D</sub> =-12A			13	mΩ
		V <sub>GS</sub> =-10V, I <sub>D</sub> =-12A			14	
		V <sub>GS</sub> =-10V, I <sub>D</sub> =-12A T <sub>J</sub> =125°C			19	
		V <sub>GS</sub> =-5V, I <sub>D</sub> =-7A			30	
On state drain current	I <sub>D(ON)</sub>	V <sub>GS</sub> =-10V, V <sub>DS</sub> =-5V	-60			A
Forward Transconductance	g <sub>FS</sub>	V <sub>DS</sub> =-5V, I <sub>D</sub> =-10.5A		27		S
Input Capacitance	C <sub>iss</sub>	V <sub>GS</sub> =0V, V <sub>DS</sub> =-15V, f=1MHz		2060	2600	pF
Output Capacitance	C <sub>oss</sub>			370		
Reverse Transfer Capacitance	C <sub>rss</sub>			295		
Gate resistance	R <sub>g</sub>	V <sub>GS</sub> =0V, V <sub>DS</sub> =0V, f=1MHz	1.2	2.4	3.6	Ω
Total Gate Charge	Q <sub>g</sub>	V <sub>GS</sub> =-10V, V <sub>DS</sub> =-15V, I <sub>D</sub> =-12A	24	30	36	nC
Gate Source Charge	Q <sub>gs</sub>			4.6		
Gate Drain Charge	Q <sub>gd</sub>			10		
Turn-On DelayTime	t <sub>d(on)</sub>	V <sub>GS</sub> =-10V, V <sub>DS</sub> =-15V, R <sub>L</sub> =1.25 Ω, R <sub>G</sub> =3 Ω		11		ns
Turn-On Rise Time	t <sub>r</sub>			9.4		
Turn-Off DelayTime	t <sub>d(off)</sub>			24		
Turn-Off Fall Time	t <sub>f</sub>			12		
Body Diode Reverse Recovery Time	t <sub>rr</sub>	I <sub>F</sub> =-12A, di/dt=100A/μs		30	40	nC
Body Diode Reverse Recovery Charge	Q <sub>rr</sub>			22		
Maximum Body-Diode Continuous Current	I <sub>S</sub>				-4	A
Diode Forward Voltage	V <sub>SD</sub>	I <sub>S</sub> =-1A, V <sub>GS</sub> =0V			-1	V

#### ■ Marking

Marking	4407
	KC****

## P-Channel MOSFET AO4407

■ Typical Characteristics




Fig 1: On-Region Characteristics (Note E)




Figure 2: Transfer Characteristics (Note E)




Figure 3: On-Resistance vs. Drain Current and Gate Voltage (Note E)




Figure 4: On-Resistance vs. Junction Temperature (Note E)




Figure 5: On-Resistance vs. Gate-Source Voltage (Note E)




Figure 6: Body-Diode Characteristics (Note E)

## P-Channel MOSFET AO4407

■ Typical Characteristics




Figure 7: Gate-Charge Characteristics




Figure 8: Capacitance Characteristics




Figure 10: Maximum Forward Biased Safe Operating Area (Note F)




Figure 11: Single Pulse Power Rating Junction-to-Ambient (Note F)




Figure 12: Normalized Maximum Transient Thermal Impedance (Note F)

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [MOSFET](#) category:*

*Click to view products by [KEXIN](#) manufacturer:*

Other Similar products are found below :

[614233C](#) [648584F](#) [MCH3443-TL-E](#) [MCH6422-TL-E](#) [FDPF9N50NZ](#) [FW216A-TL-2W](#) [FW231A-TL-E](#) [APT5010JVR](#) [NTNS3A92PZT5G](#)  
[IRF100S201](#) [JANTX2N5237](#) [2SK2464-TL-E](#) [2SK3818-DL-E](#) [FCA20N60\\_F109](#) [FDZ595PZ](#) [STD6600NT4G](#) [FSS804-TL-E](#) [2SJ277-DL-E](#)  
[2SK1691-DL-E](#) [2SK2545\(Q,T\)](#) [D2294UK](#) [405094E](#) [423220D](#) [MCH6646-TL-E](#) [TPCC8103,L1Q\(CM](#) [367-8430-0972-503](#) [VN1206L](#)  
[424134F](#) [026935X](#) [051075F](#) [SBVS138LT1G](#) [614234A](#) [715780A](#) [NTNS3166NZT5G](#) [751625C](#) [873612G](#) [IRF7380TRHR](#)  
[IPS70R2K0CEAKMA1](#) [RJK60S3DPP-E0#T2](#) [RJK60S5DPK-M0#T0](#) [APT5010JVFR](#) [APT12031JFLL](#) [APT12040JVR](#) [DMN3404LQ-7](#)  
[NTE6400](#) [JANTX2N6796U](#) [JANTX2N6784U](#) [JANTXV2N5416U4](#) [SQM110N05-06L-GE3](#) [SIHF35N60E-GE3](#)