

**SURFACE MOUNT  
GLASS PASSIVATED RECTIFIERS**

**REVERSE VOLTAGE – 50 to 1000 Volts  
FORWARD CURRENT – 3.0 Amperes**


**FEATURES**

- Glass passivated chip
- For surface mounted applications
- Low reverse leakage current
- Low forward voltage drop
- High current capability

**MECHANICAL DATA**

- Case: Molded plastic
- Case Material molding compound, UL flammability classification 94V-0, (No Br. Sb. Cl.) “Halogen-free”.
- Polarity: Color band denotes cathode
- Weight : 0.102 grams ( Approximated )

**SMB**



SMB		
DIM.	MIN.	MAX
A	4.06	4.57
B	3.30	3.94
C	1.96	2.21
D	0.15	0.31
E	5.21	5.59
F	0.05	0.20
G	2.01	2.50
H	0.76	1.52
All dimension in millimeter		

**MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS**

Ratings at 25°C ambient temperature unless otherwise specified.

**ABSOLUTE RATINGS**

PARAMETER	SYMBOL	S3AB	S3BB	S3DB	S3GB	S3JB	S3KB	S3MB	UNIT	
Maximum repetitive peak reverse voltage	$V_{RRM}$	50	100	200	400	600	800	1000	V	
Maximum DC blocking voltage	$V_{DC}$	50	100	200	400	600	800	1000	V	
Maximum average forward rectified current @ $T_L=75^\circ\text{C}$	$I_{(AV)}$	3.0							A	
Peak forward surge current 8.3ms single half sine-wave superimposed on rated load	$I_{FSM}$	@ $T_J=25^\circ\text{C}$							120	A
		@ $T_J=125^\circ\text{C}$							100	A
Peak forward surge current 1ms single half sine-wave superimposed on rated load	$I_{FSM}$	@ $T_J=25^\circ\text{C}$							240	A
		@ $T_J=125^\circ\text{C}$							200	A
$I^2 t$ rating for fusing ( t = 8.3ms)	$I^2 t$	42							$\text{A}^2\text{S}$	
Typical junction capacitance (Note1)	$C_J$	40							pF	
Operation and storage temperature range	$T_J, T_{STG}$	-55 to +150							$^\circ\text{C}$	

**STATIC ELECTRICAL CHARACTERISTICS**

PARAMETER	TEST CONDITIONS	SYMBOL	MAX.	UNIT
Forward voltage	$I_F=3.0\text{A}$ $T_J=25^\circ\text{C}$	$V_F$	1.15	V
Leakage current	$V_R$ rated $T_J=25^\circ\text{C}$ $T_J=125^\circ\text{C}$	$I_R$	10 250	$\mu\text{A}$

**THERMAL CHARACTERISTICS**

PARAMETER	SYMBOL	TYP.	UNIT
Typical thermal resistance (Note2)	$R_{thJA}$	55	$^\circ\text{C/W}$
	$R_{thJL}$	12	
	$R_{thJC}$	12	

**DYNAMIC ELECTRICAL CHARACTERISTICS**

PARAMETER	TEST CONDITIONS	SYMBOL	TYP.	UNIT
Reverse recovery time	$I_F=0.5\text{A}$ , $I_{RR}=0.25\text{A}$ , $I_R=1.0\text{A}$	$T_{RR}$	2000	ns

**Note :**

- (1) Measured at 1.0MHz and applied reverse voltage of 4.0V DC.
- (2) Thermal resistance junction to ambient, lead and case.

# RATING AND CHARACTERISTIC CURVES S3AB thru S3MB



FIG.1- FORWARD CURRENT DERATING CURVE




FIG.2- MAXIMUM NON-REPETITIVE SURGE CURRENT




FIG.3- TYPICAL FORWARD CHARACTERISTICS




FIG.4- TYPICAL REVERSE CHARACTERISTICS





FIG.5- NON-REPETITIVE SURGE CURRENT



## **Important Notice and Disclaimer**

LSC reserves the right to make changes to this document and its products and specifications at any time without notice. Customers should obtain and confirm the latest product information and specifications before final design, purchase or use.

LSC makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does LSC assume any liability for application assistance or customer product design. LSC does not warrant or accept any liability with products which are purchased or used for any unintended or unauthorized application.

No license is granted by implication or otherwise under any intellectual property rights of LSC.

LSC products are not authorized for use as critical components in life support devices or systems without express written approval of LSC.

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for* [Diodes - General Purpose, Power, Switching category:](#)

*Click to view products by* [Lite-On manufacturer:](#)

Other Similar products are found below :

[MCL4151-TR3](#) [MMBD3004S-13-F](#) [RD0306T-H](#) [RD0506LS-SB-1H](#) [RGP30G-E373](#) [DSE010-TR-E](#) [BAQ333-TR](#) [BAQ335-TR](#) [BAQ33-GS18](#) [BAS1602VH6327XT](#) [BAV17-TR](#) [BAV19-TR](#) [BAV301-TR](#) [BAW27-TAP](#) [HSC285TRF-E](#) [NSVBAV23CLT1G](#) [NTE525](#) [1SS181-TP](#) [1SS184-TP](#) [1SS193,LF](#) [1SS193-TP](#) [1SS400CST2RA](#) [SBAV99LT3G](#) [SDAA13](#) [LL4448-GS18](#) [SHN2D02FUTW1T1G](#) [LS4150GS18](#) [LS4151GS08](#) [SMMD7000LT3G](#) [FC903-TR-E](#) [1N4449](#) [1N4934-E3/73](#) [1SS226-TP](#) [APT100DL60HJ](#) [RFUH20TB3S](#) [RGP30G-E354](#) [RGP30M-E3/73](#) [D291S45T](#) [MCL4151-TR](#) [BAS 16-02V H6327](#) [BAS 21U E6327](#) [BAS 28 E6327](#) [BAS33-TAP](#) [BAS 70-02V H6327](#) [BAV300-TR](#) [BAV303-TR3](#) [BAW27-TR](#) [BAW56DWQ-7-F](#) [BAW56M3T5G](#) [BAW75-TAP](#)