





MPR METAL PLATE NON-INDUCTIVE CEMENT TYPE RESISTOR

DIMENSION









AMBIENT TEMPERATURE

RATED LEAD (%)

TYPE	POWER RATING	DIMENSIONS(mm)					MAXIMUN	MAXIMUN	RESISTANCE
		Ľ.	Н	W	d	Р	WORKING VOLTAGE	OVERLOAD VOLTAGE	RANGE
CR-E	3W	14 ± 1.5	13 ± 1.5	5 ± 1.0	0.8 ± 0.1	10 ± 1	350V	700V	0.01 Ω ~1 Ω
	5W	14 ± 1.5	18 ± 1.5	5 ± 1.0	0.8 ± 0.1	10 ± 1	350V	700V	
	3W+3W	26 ± 1.5	13 ± 1.5	5 ± 1.0	0.8 ± 0.1	10 ± 1	350V	700V	
	5W+5W	26 ± 1.5	18 ± 1.5	5 ± 1.0	0.8 ± 0.1	10 ± 1	350V	700V	
	7W+7W	26 ± 1.5	20 ± 1.5	5 ± 1.0	0.8 ± 0.1	10 ± 1	350V	700V	

CHARACTERISTICS

CHARACTERISTICS	SPECIFICATIONS	TEST METHODS JIS 5202	
TEMPERATURE COEFFICIENT	± 350PPM/C	5.2 条件 B	
SHORT TIME OVERLOAD	∆R ≤ ± (2%Ro+0.05 Ω)	2.5倍. 5SEC	
DIELECTRIC WITHSTANDING VOLTAGE	500V	5.7	
LOAD LIFE IN HUMIDITY	∆R ≤ ± (3%Ro+0.05 Ω)	7.9	
LOAD LIFE	∆R ≤ ± (3%Ro+0.05 Ω)	7.10	
THERMAL SHOCK	∆R ≤ ± (2%Ro+0.05 Ω)	JIS 5026 6.7	

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Wirewound Resistors - Through Hole category:

Click to view products by SR Passives manufacturer:

Other Similar products are found below:

75822-2K4 90J56R AC03000001208JAC00 EP3WS47RJ C1010KJL C1015RJL C3A10KJT 27J1K0 ES3W47RJ AC04000001500JAC00 AC10000002208JAB00 AC10000004708JAB00 SQMW5R39J SQPW5R22J SQPW5R33J 1879927-3 FCB2100RJ T505 FSQ5WR47J FW10A33R0JA CPCC03R5000JB31 CPCC0510R00JE32 CPCC051R000JB31 CPCP10500R0JE32 CPW05700R0JE143 CPW152K500JE313 C1010RJL C10R47JL C141K0JL C144R7JL ES05W100RJ SQMW1047RJ SQMW210RJ CPCC03R2000JB31 CPCC0515R00JE01 CPW055R000JB143 CPW103K300JE143 CPW202R000JB14 ULW5-39R0JT075 W31-R47JA1 ULW5-68RJT075 SQBW401K0JFASTON SPH1001JLF 65888-3R3 CPCC10R5100JE66 SQP500JB-400R SQBW403R3JFASTON 280-PRM7-4.7-RC CW02B9R100JE73 CPCP05R1000JE32